



SERIES 9533 Exterior Acrylic Athletic Field Marking Paint

Conco® 9533 Series Exterior Acrylic Athletic Field Marking Paint is a professional quality paint for use on athletic playing fields. Ideal for marking and striping grass or artificial turf. Formulated for quick drying, ease of application and high visibility. Bright White Formula enhanced with an optical brightener for exceptional brightness under natural and artificial light.

Recommended Uses

- Grass
- Artificial Turf
- Football, Soccer and Baseball Fields

Performance Benefits

- Bright White Formula enhanced with an optical brightener
- Concentrated Formula-May Reduce up to 200%
- High Visibility Whites
- Accent Colors
- Easy Application
- Brush, Roll or Spray or Gravity-Fed Field Marking Equipment
- Quick Drying

Recommended Systems

Grass, Artificial Turf

1 Coat Conco® 9533 Series Exterior Acrylic Athletic Field Marking Paint

Technical Information

Finish:	Flat 0-5 @ 85°
Colors:	Ultra Bright White, Bright White, Custom Tint Accent Colors
Drying Time (@ 77°F, 50% Rel. Humidity)	
To Touch:	30 Min - 1 hour
To Recoat:	4 Hours
Spread Rate:	300-350 Sq. Ft. /Gal (approximately 400-450 linear yards of 3" striping)
Volume Solids:	
Ultra Bright White	45% ± 2%
Bright White	26% ± 2%
Weight Solids:	
Ultra Bright White	66% ± 2%
Bright White	43% ± 2%
Weight per Gallon:	
Ultra Bright White	12.09 lbs
Bright White	10.92 lbs
Vehicle Type:	Vinyl Acrylic
Flash Point:	Not Applicable
V.O.C. Level:	
Ultra Bright White	VOC < 50 g/l- 0.55 lb/gal as per 40 CFR 59.406
Bright White	VOC < 50 g/l- 0.55 lb/gal as per 40 CFR 59.406
Accent Base	VOC < 50 g/l- 0.15 lb/gal as per 40 CFR 59.406
Reduction:	Water
Cleanup:	Soap and Water
Size:	Available in Fives

Warranty:

20 YEAR LIMITED WARRANTY: If this product, when applied according to label instructions, fails to perform to your complete satisfaction, upon presentation of proof of purchase to the store where the product was purchased we will, as your exclusive remedy, either replace an equivalent quantity of product free of charge or refund the purchase price. This warranty covers paint that is applied according to label instructions and excludes failure due to improper surface preparation, structural defects, or failure of the previous paint. This warranty does not include (1) labor or costs associated with labor for the application of any product and/or (2) any indirect, special, incidental or consequential damages with labor for the application of any product and/or (2) any indirect, special, incidental or consequential damages.

Surface Preparation

Surface should be clean and dry.

Cleanup Information

Clean hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using mineral spirits.



CONCO PAINTS
Pro Technology... Engineered For The Job™

SERIES
9533

**Exterior Acrylic Athletic
Field Marking Paint**

Application

Do not apply at air, surface or product temperatures below 50°F or if rain is expected within 24 hours.

Gravity-Fed Field Marking Equipment

Follow equipment manufacturer's recommendations.

Spray – Airless

Pressure.....2000 psi

Tip.....0.015"-0.019"

May be thinned up to 200% with water.

Brush

Use a quality nylon/polyester brush.

Roller

Use a 3/8" nap synthetic roller cover.

Tips for Better Performance

- Stir well before using
- Apply to dry surface

Cautions

- Keep from freezing

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Conco Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Conco Paint retailer or sales representative to obtain the most recent Product Data Sheet.