



**KITCHEN | BATH**

**TUB & TILE**

**Siliconized  
Acrylic  
Latex Caulk**



White Lightning® Tub & Tile is a Siliconized Acrylic Latex Caulk that offers watertight protection for sinks, showers and baths. The latex formula provides easy application and water clean-up. White Lightning® Tub & Tile seals cracks between wood, glass, ceramic tile, marble and porcelain.

- Cured Caulk is Mildew and Rust Resistant
- Dries Tack Free in Minutes



**PAINTABLE**



**WATER  
CLEANUP**

PART #	UPC	Color	SIZE
W22000010	0-23275-02510-3	White	10 fl oz
W22000005	0-23275-50501-0	White	5.5 fl oz

**WHITE**



**KITCHEN | BATH**

**TUB &  
TILE**

- Cured Caulk is Mold and Mildew Resistant
- Easy Application

**SILICONIZED  
ACRYLIC LATEX  
CAULK**



**PAINTABLE**



**WATER CLEANUP**

**Product Description:**

White Lightning® Tub & Tile is a Siliconized Acrylic Latex Caulk that offers watertight protection for sinks, showers and baths. The latex formula provides easy application and water clean-up. White Lightning® Tub & Tile seals cracks between wood, glass, ceramic tile, marble and porcelain.

**Physical Properties:**

**Type:** Styrene Acrylic

**Colors:** White

**Shelf Life:** 24 Months

**Flash Point:** n/a (water based)

**Flammability:** n/a (water based)

**Full Cure Time:** 3 to 4 days

**Tack Free Time:** 45 Minutes at 75° F

**Application Temperature:** 40° F to 140° F

**Service Temperature:** -30° F to 180° F

**Vehicle:** Styrene Acrylic

**Solids by Weight:** 67+/-2%

**Weight/Gallon:** 11.09+/-1.23

**Painting:** Paintable

**Primers:** Not required

**Mildew Resistance:** Excellent

**Water Resistance:** Excellent

**Odor:** Low

**Shrinkage:** Low

**Performance Data:**

**Joint Size:** 1/8" x 1/8" to 1/2" x 1/2"

**Freeze-Thaw Stability:** Passes Through 5 Cycles

**Shelf Life:** 24 Months

**Clean Up:** Water, promptly clean tools and excess caulk with water or a damp cloth.

**Flexibility:** Excellent

**Linear Coverage** 10oz cartridge 24ft at 1/4" wide by 1/4" deep bead; 5.5oz squeeze tube 12ft at 1/4" wide by 1/4" deep bead

**Painting:** A minimum of 4 hours dry time is required before painting with latex or oil based paint. Allow extra dry time during periods of high humidity and/or cool temperatures.

**Application:**

1. Remove all existing caulk
2. Clean thoroughly to remove all loose material, grease, dirt, oil, wax, loose paint, dust and soap film.
3. Remove mold/mildew with bleach (4:1 mix, water to bleach), and detergent that does not contain ammonia. Rinse surfaces and allow to dry.

**• 10oz cartridge**

- Cut cartridge tip 45° angle.
- Load cartridge into caulk gun.
- Squeeze trigger to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool.

**• 5.5oz squeeze tube**

- Remove cap, cut tube tip 45° angle.
- Squeeze tube to start flow of caulk and work caulk into joint.
- Smooth caulk with proper tool.

**Clean Up:**

Water; promptly clean tools and excess caulk with water or a damp cloth.

**Cautions:**

See MSDS

**Limitations:**

For best results, apply at temperatures above 40° F and allow 24 hours to cure before exposing to moisture. Do not apply to frozen or frost covered surfaces. Not for use below grade, on aquariums or for marine use below the water line

**LIMITED WARRANTY:**

If when applied according to label directions within one year from date of purchase this product fails to perform to your satisfaction, as your sole remedy we will replace the product at no cost or refund the original purchase price with proof of purchase. Labor or costs associated with labor not included. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER.

**For more information please call or write:**

White Lightning® Products | 101 Prospect Ave. NW | Cleveland, OH 44115  
1-800-241-5295 Option 1 Customer Service | 1-800-241-5295 Option 2 Technical Service  
[www.wlcaulk.com](http://www.wlcaulk.com)