



Dura Clean® Interior Acrylic Paint + Primer

DB100 Series – Flat
DB110 Series – Eggshell
DB120 Series – Satin
DB130 Series – Semi-Gloss

Product Data Sheet

COVERAGE:



400 sq. ft./gal (smooth)
125 - 300 sq. ft./gal
(rough surface)

DRY TIME (@77°F, 50% R.H.):



Touch: 1 hour
Recoat: 4 hours

APPLICATION:



Brush: nylon/polyester
Roller: 1/4" - 1/2" synthetic nap
Spray (Airless): 2000 psi Tip
.015"-.019"

CLEAN UP:



Warm soapy water

Features

- Paint + Primer with Stay-Clean Formula keeps your home looking clean and beautiful
- Paint + Primer feature enables Dura Clean® coating to be applied directly to most previously painted or uncoated drywall, plaster, masonry and non-bleeding wood without the use of a separate primer
- Washable, scrubbable, stain-resistant finish for easy maintenance
- Excellent hide and even coverage
- Beautiful, smooth finish
- Backed by a lifetime warranty

Where To Use

Properly prepared interior walls, trim and ceilings of previously painted or bare drywall, plaster, masonry, wood and primed metal.

Recommended Systems

The Paint + Primer feature enables Dura Clean® coating to be applied directly to most previously painted or uncoated drywall, plaster, masonry and non-bleeding wood without the use of a separate primer.

Previously Painted Surfaces:

- Use Dura Clean® Paint + Primer to spot prime bare areas, allow to dry, then paint entire surface.
- 1-2 coats of Dura Clean® Paint + Primer

Bare Surfaces: Drywall, Plaster, Masonry, Non-Ferrous Metal, and Wood:

- 1-2 coats of Dura Clean® Paint + Primer
- The first coat of Dura Clean® Paint + Primer serves as a priming coat and the second coat provides final appearance and performance.

Severely Stained/Bleeding Surfaces:

- Extreme household stains, watermarks, wood knots, bleeding woods such as cedar and redwood, or other surfaces where paint adhesion or stain suppression is a particular problem, use an appropriate primer.
- 1-2 coats of Dura Clean® Paint + Primer

Technical Data

Vehicle:	Vinyl Acrylic
Finish:	
Flat	0-5 units @ 85°
Eggshell	10-20 units @ 85°
Satin	10-20 units @ 85°
Semi-Gloss	25-35 units @ 60°
Flash Point:	N/A
Weight Solids*:	
Flat	56% ± 2%
Eggshell	59% ± 2%
Satin	59% ± 2%
Semi-Gloss	52% ± 2%
Volume Solids*:	
Flat	39% ± 2%
Eggshell	41% ± 2%
Satin	41% ± 2%
Semi-Gloss	38% ± 2%
Weight per gallon:	
Flat	11.52 lbs/gal
Eggshell	11.83 lbs/gal
Satin	11.83 lbs/gal
Semi-Gloss	10.78 lbs/gal
VOC:	VOC <50 g/L as per 40 CFR 59.406
Film Thickness:	
Flat	@ 4 mils wet; 1.52 mils dry
Eggshell	@ 4 mils wet; 1.64 mils dry
Satin	@ 4 mils wet; 1.64 mils dry
Semi-Gloss	@ 4 mils wet; 1.52 mils dry
Sizes:	Quart, Gallon, Five Gallon

*Product data calculated on Ultra White

Surface Prep

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (In US) or contact your local health authority.

Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull. **Drywall:** Fill cracks and holes with patching paste and sand smooth. **Plaster, Masonry, Block:** New surfaces must cure at least 30 days. Fill rough surfaces if desired. **Wood:** Sand to a fresh surface. Patch imperfections with wood filler. **Priming:** This product can be used to prime patched areas, unpainted surfaces and lightly stained areas before applying it as the finish coat. For best results on heavily stained areas, use a coat of an appropriate stain-blocking primer. For drastic color changes or deep, vivid colors, prime with this product or an appropriate tintable primer for your optimal color accuracy and coverage.

Clean Mildew From the Surface:

Mildew is a fungus that looks like dirt, but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover or a solution of 1-part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.

Application

Stir paint thoroughly. Intermix containers for uniformity. Apply product when surface, air and product temperatures are between 50-90°F. Apply with a premium-quality brush, a synthetic roller cover or airless spray (2000 PSI, .015"- .019" tip). Thinning not required. Paint the ceiling first, then walls and trim. For roller application, cover approximately a 2' x 2' area using an "N" pattern. Finish with light roller strokes in one direction. Some deep or bright colors, surface conditions and application techniques may impact coverage and require multiple coats to achieve your optimal coverage. For additional application tips go to dutchboy.com.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Dutch Boy Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Dutch Boy Paint Retailer or sales representative to obtain the most recent Product Data Sheet.

Clean Up/Disposal

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

Maintenance

Wait at least 7 days before washing with a mild detergent and soft sponge.

Cautions

CONTAINS CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (**NIOSH** approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (**NIOSH** approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

16 (1/10)