







Dura Clean® Cabinet, Door & Trim 100% Acrylic Paint + Primer

DB145 Series – High-Gloss

Product Data Sheet

COVERAGE:  400 sq. ft./gal (smooth) 125 - 300 sq. ft./gal (rough surface)	DRY TIME (@77°F, 50% R.H.):  Touch: 1 hour Recoat: 2-4 hours	APPLICATION:  Brush: nylon/polyester Roller: 1/4" - 1/2" synthetic nap Spray (Airless): 2000 PSI Tip .015"-.019"	CLEAN UP:  Warm soapy water
---	--	---	---

Features <ul style="list-style-type: none"> • Paint + Primer with Smooth Finish Technology is designed to offer advanced protection on accent and high use surfaces both indoors and out • Ultra smooth, highly durable enamel gives the rich look of an oil-based enamel with the convenience of a water-based formula • Tough, 100% acrylic formula provides excellent scratch, scuff and weather-resistance • Anti-Block formula prevents sticking of contact surfaces such as door jambs, windows and cabinets • Backed by a lifetime warranty
--

Technical Data	
Vehicle:	100% Acrylic
Finish:	65+ units @ 60°
Flash Point:	N/A
Weight Solids*:	47 % ± 2%
Volume Solids*:	34% ± 2%
Weight per gallon:	10.27 lb/gal
VOC:	VOC <50 g/L as per 40 CFR 59.406
Film Thickness:	@ 4 mils wet: 1.36 mils dry
Sizes:	Quart, Gallon

Where To Use
For interior and exterior use on properly prepared walls, cabinets, doors and trim of previously painted or bare drywall, plaster, masonry, wood and primed metal

Recommended Systems
The Paint + Primer feature enables Dura Clean® Cabinet, Door & Trim coating to be applied directly to most previously painted or uncoated drywall, plaster, masonry and non-bleeding wood without the use of a separate primer.
Previously Painted Surfaces:
<ul style="list-style-type: none"> • Use Dura Clean® Cabinet, Door & Trim to spot prime bare areas, allow to dry, then paint entire surface. • 1-2 coats of Dura Clean® Cabinet, Door & Trim Paint + Primer
Bare Surfaces: Drywall, Plaster, Masonry, Non-Ferrous Metal, and Wood:
<ul style="list-style-type: none"> • 1-2 coats of Dura Clean® Cabinet Door & Trim Paint + Primer • The first coat of Dura Clean® Cabinet, Door & Trim serves as a priming coat and the second coat provides final appearance and performance.
Severely Stained/Bleeding Surfaces:
<ul style="list-style-type: none"> • Extreme household stains, watermarks, wood knots, bleeding woods such as cedar and redwood, or other surfaces where paint adhesion or stain suppression is a particular problem, use an appropriate primer.
<ul style="list-style-type: none"> • 1-2 coats of Dura Clean® Cabinet, Door & Trim Paint + Primer

*Product data calculated on Ultra White

Surface Prep

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (In US) or contact your local health authority.

To ensure proper adhesion all surfaces should be sound, clean, dull and dry. Remove loose paint. Wash with a mild, non-abrasive, non-oily cleanser and water. Rinse completely, let dry. Fill cracks and holes with patching/spackling paste and sand smooth. Remove sanding dust with a damp cloth before application.

Drywall: Wipe with a damp cloth to remove dust. Allow to dry. Fill cracks & holes with spackling compound and sand smooth. Joint compound must be cured and sanded smooth. Remove all sanding dust.

Plaster: All new surfaces must be hard and cured according to the supplier's recommendations—usually at least 30 days. Treat textured, soft, porous, or powdery plaster with a solution of 1 pint household vinegar to 1 gallon of water. Repeat until the surface is hard, rinse with water and allow to dry.

Masonry: Allow new masonry to cure at least 30 days. Surface must have a pH less than 8. Clean old masonry with a wire bristle brush to remove all loose concrete and efflorescence. Rinse thoroughly and allow to dry. Fill rough surfaces, if desired, with block filler.

Wood: Sand any exposed wood to a fresh smooth surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. Remove all sanding dust.

Aluminum and Galvanized Metal: Wash with appropriate cleaner to remove any oil, grease. Or surfaces contamination using a water-based cleaner-degreaser. Remove all corrosion with sandpaper, steel wool. Or other abrading methods. Wipe with a damp cloth. Apply recommend primer.

Caulking: Fill gaps between walls, ceilings, crown moldings, and other trim with latex or siliconized latex caulk after priming the surface.

Mildew: Remove mildew before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the mildewed area for 10 minutes. Rinse thoroughly with water and allow surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. **DO NOT ADD DETERGENTS OR AMMONIA TO THE BLEACH/WATER SOLUTION.**

Application

- Apply when surface, air and product temperatures are above 50°F. Paint dries best between 65°F and 85°F.
- Stir paint thoroughly. Mix gallons together when using more than one gallon of the same product.
- For optimal appearance and hide over new or uncoated surfaces, dramatic color changes, or when applying dark/vibrant colors, additional coats of Dura Clean® Cabinet, Door & Trim may be necessary

Clean Up/Disposal

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

Maintenance

Freshly painted surfaces may be washed after 30 days. Clean with mild, non-abrasive, non-oily cleanser and water.

Cautions

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (**NIOSH** approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

15 (1/10)

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Dutch Boy Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Dutch Boy Paint Retailer or sales representative to obtain the most recent Product Data Sheet.