







Paver Sealer Gloss

DBC500-16
DBC500-20

Product Data Sheet

COVERAGE:  150-200 sq. ft./gal	DRY TIME (@50-90°F):  Touch: 1 hour Recoat: 4 hours	APPLICATION:  Brush: nylon/polyester Roller: 3/8" - 1/2" synthetic nap Spray (Airless): 0.013-0.017" tip at 500- 1000 psi	CLEAN UP:  Warm soapy water
---	---	--	---

Features Technical Data

- ### Features
- Dutch Boy Paver Sealer adds protection to masonry pavers while locking in joint sand and minimizing weed growth.
 - Provides UV resistance and chemical/abrasion resistance
 - Protects against water and stain damage

Where To Use

Properly prepared interior pavers (covered porches, patios and walkways), exterior pavers, interlocking walkways, concrete patios, pool deck and more. Interior and exterior use.

Recommended Systems

Dutch Boy Paver Sealer is a gloss sealer that penetrates and protects all types of porous pavers as well as bonding joint sand.

A two-coat application is recommended, allowing 4 hours drying time before recoating.

Technical Data

Vehicle:	Acrylic Emulsion
Pigment Type:	N/A
Viscosity:	20-28" / #4 Ford Cup
Weight Solids:	30-34%
Volume Solids:	26% ± 2%
Weight per gallon:	8.57 lbs.
VOC :	< 100 g/L as per 40 CFR 59.406
Sizes:	1 gallon-128 oz/gal 5 gallon-640 oz/gal
*DO NOT TINT	

Regulatory Compliance

Current as of: 1/1/2023	SCAQMD- No CARB 2000 SCM- Yes CARB 2007 SCM- Yes OTC/LADCO- Yes EPA- Yes Colorado AIM- Yes
--------------------------------	---

Surface Prep

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

All surfaces must be clean, dry and free of all loose, peeling paint or contaminants. Bare Concrete: Allow 30 days minimum for new concrete to cure before applying. New, unpainted or smooth-worn concrete must be prepared and etched with a concrete cleaner/degreaser and etching solution for proper penetration and adhesion. Etch surface to the feel of 120-grit sandpaper at minimum and surface immediately absorbs water

Application

Newly installed pavers should weather a minimum of 60 days before sealing. All surfaces must be clean, dry and free of grease, oil, paint, sealers, etc. To spot clean, use a cleaner/degreaser. All excess joint sand should be swept off the surface prior to application of the sealer. Do not apply if rain is expected within 12 hours of application.

For best results, surface and air temperature should be above 50°F and below 90°F. Temperature should not fall below 40°F for 24 hours following application. Stir thoroughly before and during application. DO NOT OVERAPPLY. A minimum of 2 coats is recommended. Apply with brush or 3/8" nap roller for smooth surfaces, 1/2" nap for rough or textured surfaces or an airless sprayer. If spray application is used, back roll to avoid build-up. DO NOT THIN. First Coat: On horizontal surfaces, apply the sealer liberally and evenly, flooding the paving stone joint to achieve maximum joint sand stabilization. Remove excess material by back rolling, squeegee or wiping. It will apply milky white and dry clear in approximately 1 hour. 1 coat is adequate for proper sealing and joint sand stabilizing. Allow a minimum of 4 hours dry time before applying second coat. Second Coat: If second coat is desired, apply crosswise to the first coat for best coverage. Allow 24 to 48 hours under good drying conditions before using the surface for heavy traffic.

Slip Resistance: Some surfaces such as inclined driveways, garages, steps and patios may require a slip-resistant additive for safety. If more than 2 coats are applied, consider using a slip-resistant additive in the final coat.

Clean Up/Disposal

Clean up with warm, soapy water. In case of spills, absorb with inert material such as sand or kitty litter. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. Protect containers from freezing. Dispose of empty container or unused portion in accordance with local, state and federal regulations.

Return To Service

Dries to the touch in 1 hour. Wait 4 hours for light foot traffic or recoat. Dry times will vary depending on weather conditions. For best results apply above 50°F (10°C). Allow 72-96 hours for full cure and return to full service.

Cautions

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Dutch Boy Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Dutch Boy Paint Retailer or sales representative to obtain the most recent Product Data Sheet.