



Dura Hide 1000 Flat Acrylic Latex Paint

DB35207 Series – Ultra White
DB35204 Series – Light/Base B
DB35209 Series – Accent/Base D

Product Data Sheet

COVERAGE:



Up to 400 sq ft/gallon depending on surface texture and porosity

DRY TIME (@77°F, 50% R.H.):



Touch: 1 hour
Recoat: 2-4 hours

APPLICATION:



Brush: Nylon/polyester
Roller: 1/4" – 1/2" synthetic nap
Spray (Airless): 2000 PSI
Tip: .015"-.019"

CLEAN UP:



Warm, soapy water

Features

- Outstanding touch-up & sheen uniformity
- Excellent hide & durability
- Smooth, washable finish
- Great film build & sag resistance
- Fast recoat
- Spray, roll or brush on
- Soap & water cleanup

Where To Use

Properly prepared interior walls, trim and ceilings of previously painted or bare drywall, plaster, masonry, wood and primed metal.

Technical Data

| | |
|--------------------|--|
| Vehicle: | Vinyl Acrylic |
| Finish: | 0-5 units @ 85° |
| Flash Point: | N.A. |
| Weight Solids: | 56 ± 2% |
| Volume Solids: | 39 ± 2% |
| Weight per gallon: | 11.52 lbs/gal |
| VOC: | less than 50 grams per litre as per 40 CFR 59.406 |
| Film Thickness: | 4.0 mils wet; 1.52 mils dry |
| Sizes: | Gallon, 5 Gallon (Ultra White Only) |

*Technical data based on Ultra White

Surface Prep

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Surface Preparation: Thoroughly clean the surface and allow to dry. Remove wall paper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull. **Drywall:** Fill cracks and holes with patching paste and sand smooth. **Plaster, Masonry, Block:** New surfaces must cure at least 30 days. Fill rough surfaces if desired. **Wood:** Sand to a fresh surface. Patch imperfections with wood filler. **Priming:** For best results on bare surfaces, prime with the appropriate Dutch Boy® Primer. For best results on heavily stained areas, use a coat of an appropriate Dutch Boy stain-blocking primer. For drastic color changes or deep, vivid colors, prime with an appropriate tintable primer for optimal color accuracy and coverage.

Clean Mildew from the Surface: Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

DH1000FLT

Application

Application: Stir paint thoroughly. Intermix containers for uniformity. Apply product when surface, air and product temperatures are between 50-90°F. Apply with a premium-quality brush, a synthetic roller cover or airless spray (2000 PSI, .015"-.019" tip). Thinning not required. Paint the ceiling first, then walls and trim. For roller application, cover approximately a 2' x 2' area using an "N" pattern. Finish with light roller strokes in one direction. Certain deep or bright colors may require an additional coat for complete hide. Surface conditions and application technique may impact coverage.

Clean Up/Disposal

Cleanup/Disposal: Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

Maintenance

Washing Instructions: Wait at least 7 days before washing with a mild detergent and soft sponge.

Cautions

DB3527, DB35204: Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

16 (1/10)

DB35209: Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

15 (1/10)

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Dutch Boy Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Dutch Boy Paint Retailer or sales representative to obtain the most recent Product Data Sheet.