



Dura Hide 100 Semi-Gloss Acrylic Latex Paint

DB25718 Series – Antique White
 DB25707 Series – White/Base A
 DB25704 Series – Light/Base B
 DB25709 Series – Accent/Base D

Product Data Sheet

COVERAGE:  Up to 400 sq ft/gallon depending on surface texture and porosity	DRY TIME (@77°F, 50% R.H.):  Touch: 1 hour Recoat: 2-4 hours	APPLICATION:  Brush: Nylon/polyester Roller: 1/4" – 1/2" synthetic nap Spray (Airless): 2000 PSI Tip: .015"-.019"	CLEAN UP:  Warm, soapy water
--	--	---	---

Features Surface Prep

- Excellent touch-up & sheen uniformity
 - Great hide & durability
 - Zero VOC*
 - Good film build & sag resistance
 - Fast recoat
 - Spray, roll or brush on
 - Soap & water cleanup
- *Zero VOC applies only to base paint. VOC level may increase significantly depending on the colorant choice.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Where To Use

Properly prepared interior walls, trim and ceilings of previously painted or bare drywall, plaster, masonry, wood and primed metal.

Surface Preparation: Thoroughly clean the surface and allow to dry. Remove wall paper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull. **Drywall:** Fill cracks and holes with patching paste and sand smooth. **Plaster, Masonry, Block:** New surfaces must cure at least 30 days. Fill rough surfaces if desired. **Wood:** Sand to a fresh surface. Patch imperfections with wood filler. **Priming:** For best results on bare surfaces, prime with the appropriate Dutch Boy® Primer. For best results on heavily stained areas, use a coat of an appropriate Dutch Boy stain-blocking primer. For drastic color changes or deep, vivid colors, prime with an appropriate tintable primer for optimal color accuracy and coverage.

Technical Data

Vehicle:	Acrylic
Finish:	35-45 units @ 60°
Flash Point:	N.A.
Weight Solids:	37 ± 2%
Volume Solids:	26 ± 2%
Weight per gallon:	9.8 lbs/gal
VOC:	less than 50 grams per litre as per 40 CFR 59.406
Film Thickness:	4.0 mils wet; 1.0 mils dry
Sizes:	1 Gallon, 5 Gallon (AW, W/BA only)

Clean Mildew from the Surface: Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

*Technical data based on Antique White

DH100SG

Application

Application: Stir paint thoroughly. Intermix containers for uniformity. Apply product when surface, air and product temperatures are between 50-90°F. Apply with a premium-quality brush, a synthetic roller cover or airless spray (2000 PSI, .015"-.019" tip). Thinning not required. Paint the ceiling first, then walls and trim. For roller application, cover approximately a 2' x 2' area using an "N" pattern. Finish with light roller strokes in one direction. Certain deep or bright colors may require an additional coat for complete hide. Surface conditions and application technique may impact coverage.

Clean Up/Disposal

Cleanup/Disposal: Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

Maintenance

Washing Instructions: Wait at least 7 days before washing with a mild detergent and soft sponge.

Cautions

DB25718, DB25707, DB25704: Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

16 (1/10)

DB25709: Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

15 (1/10)

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Dutch Boy Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Dutch Boy Paint Retailer or sales representative to obtain the most recent Product Data Sheet.