



High Build Primer

Product Data Sheet

DBP015 Series

COVERAGE:



64-400 sq. ft./gal
Depending on film thickness,
surface texture and porosity

DRY TIME (@45-90°F, 50% R.H.):



Touch: 1 hour
Recoat: 4 hours

APPLICATION:



Brush: Nylon/polyester
Roller: 1/2" – 1 1/2" synthetic nap
Spray (Airless): 2500 PSI
Tip .025"

CLEAN UP:



Soap and water

Features

- Fills & surfaces minor imperfections
- Skims & primes in one coat
- Fills & levels minor defects such as pinholes, nicks and sanding grooves
- Evens porosity of drywall for a smooth, uniform topcoat
- Ideal for drywall, plaster and masonry
- Topcoat with latex or alkyd paints

Where To Use

Use on properly prepared interior drywall and plaster surfaces.
Will provide a Level 5 finish over a level 4 drywall surface.

Technical Data

Vehicle:	Vinyl Acrylic
Finish:	Flat 0-5 @ 85°
Flash Point:	Not Applicable
Weight Solids:	63% ± 2%
Volume Solids:	44% ± 2%
Weight per gallon:	12.78 lbs
VOC:	94 g/l- 0.78 lb/gal as per 40 CFR 59.406
Film Thickness:	4.0 - 25.0 mils wet 1.8 – 11.0 mils dry
Sizes:	5 Gallon

Surface Prep

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Surface Preparation: Surfaces must be clean, dry and dull prior to application. Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull. All dust should be removed. **Drywall:** Fill cracks and holes with joint compound and sand smooth. **Plaster:** New surfaces must cure at least 30 days. Fill rough surfaces if desired. See technical data sheet for additional surface prep.

Clean Mildew from the Surface:

Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

HIBLDPRMR

Application

Application: Stir primer thoroughly before and during use. Due to the high solids content of this material, a power agitator is recommended. Use a professional airless sprayer for high build finish. A one-gallon-per-minute or larger direct immersion airless sprayer is recommended. Sprayers with suction tubes will also work but will prime slower. Use tip size 525 or larger (10" fan with 0.025" tip) to meet necessary delivery rate and pattern size. Spray at a pressure of 2200-2500 psi at the gun for best atomization and pattern without excessive overspray. All screens and filters must be clean and in place. Float a small amount of water on top of the paint to avoid drying of paint and formation of skin during spraying. Apply up to 25 mils wet. Measure film thickness with wet mil gauge for most consistent application. Apply only enough material to cover undesirable surface imperfections. May also be applied by polyester or nylon bristle brush, or 1/2"-1 1/2" nap synthetic roller, but will not achieve a high build finish using these application methods.

Clean Up/Disposal

Cleanup/Disposal: Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

Cautions

CRYSTALLINE SILICA

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area.

Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use.

Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.

Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure.

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Dutch Boy Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Dutch Boy Paint Retailer or sales representative to obtain the most recent Product Data Sheet.

For more information, please call 1-800-828-5669, or visit www.dutchboy.com