



Block Filler

Product Data Sheet

DBP951 Series

COVERAGE:



75-125 sq. ft./gal
Depending on surface
texture and porosity

DRY TIME (@45-90°F, 50% R.H.):



Touch: 1-2 hours
Recoat: 18-48 hours

APPLICATION:



Brush: Nylon/polyester
Roller: 3/8" – 3/4" synthetic nap
Spray (Airless): 2300 PSI
Tip .028"

CLEAN UP:



Soap and water

Features

- Heavy-duty filler smooths and levels rough, porous masonry
- Bridges cracks & offers excellent hide to even out surface imperfections
- Good flexibility & elasticity
- Topcoat with latex or alkyd paints
- For concrete block, stucco & other porous masonry

Where To Use

Use on interior or exterior above-grade unpainted porous masonry, concrete, cement and flat surfaced concrete block.

Technical Data

Vehicle:	Vinyl Acrylic
Finish:	Flat
Flash Point:	Not Applicable
Weight Solids:	69% ± 2%
Volume Solids:	49% ± 2%
Weight per gallon:	13.49 lbs
VOC:	< 50 g/l- 0.37 lb/gal as per 40 CFR 59.406
Film Thickness:	16 mils wet 7.8 mils dry
Sizes:	5 Gallon

Surface Prep

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Surface Preparation: Remove all surface contamination, form release agents and moisture curing membranes with an appropriate cleaner, rinse and allow to dry. Remove loose mortar, efflorescence and foreign material with a wire brush or stiff-blade scraper. Pressure wash if needed. **Concrete, Block:** Allow to cure at least 30 days at 75°F, with a moisture content of 15% or less and a surface pH between 5 and 9 before painting.. Remove all form release, curing agents and other foreign matter. Rough surfaces can be filled to provide a smooth surface. **Caulking:** Fill gaps with appropriate caulk after priming.

Clean Mildew from the Surface:

Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

BLCKFILLR

For more information, please call 1-800-828-5669, or visit www.dutchboy.com

Application

Application: Stir primer thoroughly before and during use. Apply with a premium-quality roller, polyester or nylon bristle brush, or airless sprayer. If applying by sprayer, back-roll or back-brush to work primer into the surface. Apply a liberal coat of primer uniformly, working well into the surface. If necessary, may be thinned with up to one pint of water per gallon block filler for spray application. Add water only. Airless spray at 2300 psi using a .028" tip and no filter. Apply a thick coat of material. To ensure a good protective seal, backroll material until all pores, cracks and pinholes are filled. All application methods may be squeegeed to provide a very smooth surface. Apply only when the temperature of the surface, material and air is above 50°F. Do not apply if rain or heavy dew is expected within 24 hours.

Clean Up/Disposal

Cleanup/Disposal: Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

Cautions

CRYSTALLINE SILICA

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area.

Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use.

Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.

Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure.

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Dutch Boy Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Dutch Boy Paint Retailer or sales representative to obtain the most recent Product Data Sheet.