




Metal Roof & Siding Coating

DBSC907 Series – Ultra White
DBSC904 Series – Light/Base B
DBSC909 Series – Accent/Base D

Product Data Sheet

COVERAGE:  150-400 sq ft/gal depending on surface texture and porosity	DRY TIME (@77°F, 50% R.H.):  Touch: 1 hour Recoat: 4 hours	APPLICATION:  Brush: Premium-quality polyester  Roller: Premium-quality  Spray (Airless): Tip:	CLEAN UP:  Warm, soapy water
-----------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------

Features

- Color and protection for barns, pole barns, sheds and outbuildings
- Weather-resistant coating
- Resists rust, chipping and peeling
- UV- and fade-resistant
- For siding and sloped roofs
- 100% acrylic durability

Where To Use

Use on properly prepared exterior siding and sloped roofs of galvanized metal, aluminum, wood & masonry.

Technical Data

Vehicle:	100% Acrylic
Finish:	35-45 units @ 60°
Flash Point:	N/A
Weight Solids:	44 ± 2%
Volume Solids:	32 ± 2%
Weight per gallon:	10.19 lbs/gal
VOC:	< 50 g/L as per 40 CFR 59.406
Film Thickness:	4.0 mils wet; 1.28 mils dry
Sizes:	5 Gallon

*Technical Data based on Ultra White

Surface Prep

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Surface Preparation: Surfaces must be clean, dry and dull prior to application. Thoroughly clean the surface and allow to dry. Remove loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull. All dust should be removed.

Wood: Sand to a fresh surface. Patch imperfections with wood filler. Heavily stained areas, including tannin stains on wood, may require an appropriate stain-blocking primer. **Masonry:** All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. pH should be less than 10. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. **Metal:** New galvanized surfaces should be allowed to age 6 months before painting. Wash to remove any oil, grease or other surface contamination with an appropriate cleaner, rinse thoroughly and allow to dry. Do not use hydrocarbon solvents for cleaning. Remove all corrosion with sandpaper, steel wool or other abrading method. See technical data page for additional surface prep.

Clean Mildew from the Surface: Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

MTLRFSDSG

Application

Application: Stir thoroughly before and during use. Intermix all containers to ensure color uniformity. Do not thin. Apply with a premium-quality polyester brush, roller or airless sprayer. Do not apply in direct sun, on a hot surface, or when air/surface temperature exceeds 90°F (32°C). For metal roofs/large expanses of metal siding, the air, surface, and material temperatures must be 50°F (10°C) or higher. Prior to painting, check to be sure the air, surface and material temperatures are above 35° F (2°C) and at least 5° F (-15°C) above the dew point. Avoid using if rain or snow is expected within 4 hours. Air and surface temperatures must not drop below 35° F (2°C) for 48 hours after application.

Clean Up/Disposal

Cleanup/Disposal: Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

Cautions

DBSC907: CRYSTALLINE SILICA ZINC Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN**
23 (1/10)

DBSC904, DBSC909: Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**
16 (1/10)

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Dutch Boy Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Dutch Boy Paint Retailer or sales representative to obtain the most recent Product Data Sheet.

For more information, please call 1-800-828-5669, or visit www.dutchboy.com