



Barn & Fence Paint

Water-Based Alkyd

Semi-Gloss

DB08210 Series – White
DB08299 Series – Red

COVERAGE:

Up to 400 sq ft/gallon depending on surface texture and porosity

DRY TIME (@77°F, 50% R.H.):



Touch: 1 hour
Recoat: 4 hours

APPLICATION:



Brush: Nylon/polyester
Roller: 1/4" – 1/2" synthetic nap
Spray (Airless): 2000 PSI
Tip: .015"-.019"

CLEAN UP:



Warm, soapy water

Features

- Durable protection for barns, fences, sheds and outbuildings
- Low temperature application; 35-90°F (2-32°C)
- Self-priming
- Fade resistant
- Provides a mold- and mildew-resistant finish
- Soap-and-water cleanup

Where To Use

Ideal for use on properly prepared and primed barns, fences, sheds, silos, factories and general exterior surfaces.

Technical Data

| | |
|---------------------------|--------------------------------------|
| Vehicle: | Waterborne Alkyd |
| Finish: | 76-86 units @ 60° |
| Flash Point: | N/A |
| Weight Solids: | White: 43.81% ±2% Red: 37.85% ±2% |
| Volume Solids: | White: 35.73% ±2% Red: 33.66% ±2% |
| Weight per gallon: | White: 9.45 lbs Red: 8.81 lbs |
| VOC: | < 50 g/L as per 40 CFR 59.406 |
| Film Thickness: | 4.0 mils wet; 0.5–1.5 mils dry |
| Sizes: | Gallon, 5 Gallon |

Surface Prep

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Surface Preparation: Remove surface contaminants with an appropriate cleaner, rinse thoroughly and allow to dry. Remove peeled or damaged paint. Sand glossy surfaces dull. Seal stains with the appropriate primer. **New/Unpainted Surface:** New, bare and badly weathered wood should be primed with this product thinned at a rate of 8 fl. oz. of water per gallon of paint. New or bare metal should have all surface rust removed and then primed with an appropriate metal primer. **Previously Painted Surfaces:** Scrape off loose and peeling paint, sand, then prime. Dull glossy surfaces with a gloss remover or sandpaper. **Hardboard Siding (unprimed, primed or previously painted):** Remove any wax from bleed-through areas by wiping with mineral-spirits-soaked rags, turning often to avoid merely spreading wax around. Prime all hardboard with an exterior oil-based primer. **Masonry:** Wire brush loose material from chalking areas on concrete, brick and concrete blocks. **Metal:** Remove rust on galvanized surfaces and spot-prime with a rust-inhibitive metal primer.

Clean Mildew from the Surface: Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

DBBFWBA

For more information, please call 1-800-828-5669, or visit www.dutchboy.com

Application

Application: Stir paint thoroughly. Intermix containers for uniformity. Apply with a premium-quality brush, roller or airless spray (2000 PSI, .015"- .019" tip). Apply only when surface and air temperatures are 35-90°F (2-32°C).

Clean Up/Disposal

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

Warranty

SATISFACTION GUARANTEE LIMITED WARRANTY:
For complete warranty terms, visit dutchboy.com/warranty or contact customer service at 1-800-828-5669 to request a written copy.

Cautions

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (**NIOSH** approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. DANGER:** Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

1262 (3/11)