

Product Data Sheet

DB0P095 Series – Flat

COVERAGE:



400-600 sq. ft./gal
Depending on surface
texture and porosity

DRY TIME (@45-90°F, 50% R.H.):



Touch: 30 minutes
Recoat: 3 hours

APPLICATION:



Brush: Nylon/polyester
Roller: 3/8" – 3/4" synthetic nap
Spray (Airless): 2000 PSI
Tip .013"-.015"

CLEAN UP:



Soap and water

Features

- Seals and conditions damaged drywall
- Provides a sound drywall surface for patching and priming
- Dries clear
- Prepares surface to prime with an appropriate Dutch Boy primer
- Easy soap-and-water cleanup
- Ideal for drywall and previously painted surfaces

Where To Use

Use on drywall, cured drywall patching compounds, and previously painted surfaces.

Technical Data

Vehicle:	Acrylic
Finish:	72 units @85°
Flash Point:	N.A.
Weight Solids:	16 ± 2%
Volume Solids:	14 ± 2%
Weight per gallon:	8.46 lbs
VOC:	94 grams per litre; .78 lbs. per gallon as per 40 CFR 59.406
Film Thickness:	N.A.
Sizes:	Quart; 1 Gallon

Surface Prep

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Surface Preparation: Surfaces must be clean, dry and dull prior to application. Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull. All dust should be removed. Heavily stained areas, including tannin stains on wood, may require an appropriate stain-blocking primer. **For damaged drywall paper:** If only the drywall paper was damaged, remove any loose paper and then use 80- 120 grit sandpaper to lightly sand the area to help feather the edges where the paper was removed and then apply a uniform coat of Wall-Repair Sealer to the damaged area. Allow 3 hours drying time before applying a skim coat, patch, wallcovering, or primer. **For gouged and damaged drywall:** Remove any loose chunks. Apply a uniform coat of Wall-Repair Sealer to the damaged area. Allow 3 hours drying time before applying a patch or skim coat. Once dry and sanded smooth, the patched or skim coated areas should be primed again with Wall Repair Sealer or other appropriate Dutch Boy® primer.

Clean Mildew From the Surface:

Mildew is a fungus that looks like dirt, but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.

Application

Application: Stir primer thoroughly before and during use. Apply with a nylon/polyester brush, pad applicator, synthetic roller or airless sprayer. If applying by sprayer, back-roll or back-brush to work primer into the surface. Apply a liberal coat of primer uniformly, working well into the surface. Appears milky during application, but will dry clear. Must be topcoated within 14 days with architectural latex or oil finishes or wallcovering.

Clean Up/Disposal

Cleanup/Disposal: Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

Cautions

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area.

Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists.

If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Dutch Boy Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Dutch Boy Paint Retailer or sales representative to obtain the most recent Product Data Sheet.