

## Product Data Sheet

DB0P096 Series – Flat

### COVERAGE:



Up to 400 sq. ft./gal  
Depending on surface  
texture and porosity

### DRY TIME (@45-90°F, 50% R.H.):



Touch: 30 minutes  
Recoat: 1 hour

### APPLICATION:



Brush: Nylon/polyester  
Roller: 3/8" – 3/4" synthetic nap  
Spray (Airless): 2000 PSI  
Tip .015"-.017"

### CLEAN UP:



VOC Compliant  
Cleaner

## Features

- Heavy-duty coverage over household stains and odors
- Seals over tough indoor stains and odors, including from food and pets
- Strong surface adhesion
- Provides outstanding topcoat uniformity
- Helps hide previous color
- Ideal for previously painted surfaces, wood and paneling, plaster

## Where To Use

Use on properly prepared interior drywall, plaster, or wood.

## Technical Data

Vehicle:	Copolymer
Finish:	Flat
Flash Point:	90°F PMCC
Weight Solids:	70 ± 2%
Volume Solids:	55 ± 2%
Weight per gallon:	15.10 lbs
VOC:	94 grams per litre; 0.78 lbs. per gallon as per 40 CFR 59.406
Film Thickness:	4 mils wet; 2.2 mils dry
Sizes:	1 Gallon

## Surface Prep

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**Surface Preparation:** Surfaces must be clean, dry and dull prior to application. Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull. All dust should be removed. **Drywall:** Fill cracks and holes with joint compound and sand smooth. **Plaster:** Must be dry, fully cured and in good condition. Remove all chalky residue. **Wood:** Sand to a fresh surface. Patch imperfections with wood filler. **For smoke and heavily stained areas:** Thoroughly clean the surface before applying primer. After priming, allow to dry 4 hours, test a small area for bleeding by applying the topcoat before painting the entire project. If the stain bleeds through, apply a second coat of primer and allow to dry overnight and retest before topcoating. See technical data page for additional surface prep.

### Clean Mildew From the Surface:

Mildew is a fungus that looks like dirt, but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.

## Application

**Application:** Stir primer thoroughly before and during use. Apply with a natural bristle brush, pad applicator, synthetic roller or airless sprayer. If applying by sprayer, back-roll or back-brush to work primer into the surface. Apply a liberal coat of primer uniformly, working well into the surface.

## Clean Up/Disposal

**Cleanup/Disposal:** Clean brushes and tools with a VOC compliant solvent-based brush and tool cleaner following manufacturer's safety instructions. Wash hands with soap and water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

## Cautions

### AROMATIC HYDROCARBONS

### CRYSTALLINE SILICA

Contents are **FLAMMABLE**. Vapors may cause flash fires. Keep away from heat, sparks, and open flame. During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

**VAPOR HARMFUL.** Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area.

Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use.

Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

**FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician.

If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

**DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure.

**WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Dutch Boy Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Dutch Boy Paint Retailer or sales representative to obtain the most recent Product Data Sheet.