



Dura Weather Elastomeric Stucco & Masonry Paint

DBSCE03 Series – White/Base A
 DBSCE05 Series – Deep/Base C
 DBSCE09 Series – Accent/Base D

Product Data Sheet

COVERAGE:  Up to 160 sq. ft./gal	DRY TIME (@77°F, 50% R.H.):  Touch: 4 hours Recoat: 24 hours	APPLICATION:  Brush: Nylon/polyester Roller: Premium-quality Spray (Airless): 2300 PSI Tip .021"	CLEAN UP:  Warm, soapy water
---	--	--	---

Features Surface Prep

- Tough 4-season protection
- Bridges hairline cracks
- Creates a mold- and mildew-resistant finish
- Flexible finish resists cracking and peeling
- High-build formula
- Outstanding alkali resistance
- Soap & water cleanup

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Where To Use

Properly prepared, masonry-walls surfaces including brick, cement, fiber cement board, cinder block, stucco, concrete, plaster and stone. Do not use on glazed brick, floors or steps.

Surface Preparation: Surface should be clean, dry and dull. Clean areas to remove all loose particles. Peeling paint, efflorescence, concrete dust and heavy chalk should be removed with a power washer and an appropriate cleaner. Rinse the surface thoroughly and allow it to dry. Scrape and sand smooth any remaining peeling surfaces. Make sure the surface is dull. Allow new surfaces to cure for at least 7 days. **Concrete, Stucco, Block:** Remove all form release, curing agents and other foreign matter. Rough surfaces can be filled to provide a smooth surface. May have a pH of 6 to 13. **Caulking:** Fill gaps with appropriate caulk after priming.

Technical Data

Vehicle:	Styrene Acrylic
Finish:	0-10 units @ 85°
Flash Point:	N.A.
Weight Solids:	63 ± 2%
Volume Solids:	48 ± 2%
Weight per gallon:	11.5 lbs/gal
VOC:	< 50 g/L as per 40 CFR 59.406
Film Thickness:	14.0 mils wet; 6.4 mils dry
Sizes:	1 Gallon; 5 Gallon

Clean Mildew from the Surface: Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

DWELSTSM

Application

Application: Apply with a premium-quality polyester brush, roller or airless sprayer. Apply when air, surface and product temperature is between 50°F (10 °C) and 100°F (37,7 °C). Do not apply if temperature might drop within 5 degrees of the dew point before application. No reduction necessary.

Clean Up/Disposal

Cleanup/Disposal: Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

Cautions

DBSCE03, DBSCE05: CRYSTALLINE SILICA ZINC Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN

23 (1/10)

DBSCE09: Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

16 (1/10)

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Dutch Boy Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Dutch Boy Paint Retailer or sales representative to obtain the most recent Product Data Sheet.