

DutchBoy® Traffic & Zone Marking Paint

DBTM007 Series – Striping White
 DBTM006 Series – Striping Yellow
 DBTM002 Series – Accessibility Blue
 DBTM008 Series – Curb Red
 DBATM78 Series – Green
 DBATM79 Series – Black

Product Data Sheet

COVERAGE:  110 sq. ft./gal or 320 lineal ft./gal at 4" width	DRY TIME (@77°F, 50% R.H.):  Touch: 15 minutes Recoat: 4 hours	APPLICATION:  Brush: Nylon/polyester Roller: Medium-nap Spray (Airless): 1800-2700 PSI Tip .015"-.019"	CLEAN UP:  Soap and water
---	--	--	--

Features

- Durable color for marking cured concrete & asphalt
- No traffic pick-up after 15 minutes
- Durable & abrasion resistant
- High-visibility colors
- Apply by brush, roller or sprayer
- 100% acrylic durability
- Soap & water cleanup

Surface Prep

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Where To Use

For striping streets, parking lots, and traffic and vehicle control areas. For use on concrete and asphalt.

Surface Preparation: Surface must be cured, clean, dry and free from loose dirt, dust, grease, oil and peeling paint. Remove concrete sealers and efflorescence on new concrete by extended weathering, etching or abrasive blasting. Etch new concrete surfaces with muriatic acid before painting. Previously painted lines may be repainted without additional surface preparation if the old paint is still tightly adhered to the surface. However, multiple layers of paint will eventually peel and require removal. Allow new asphalt surfaces to age at least 30-60 days before striping. Shrinkage of the paint film during curing and exceeding the recommended film thickness can cause new asphalt to lift or crack. Placing an inconspicuous test stripe to determine if a new asphalt surface has cured sufficiently to paint is recommended. If it is necessary to paint new asphalt surfaces, apply two light coats (7-8 mils wet) to minimize cracking and/or lifting of the asphalt.

Technical Data*

Vehicle:	Acrylic
Finish:	N.A.
Flash Point:	N.A.
Weight Solids:	78 ± 2%
Volume Solids:	61 ± 2%
Weight per gallon:	14.1 lbs/gal
VOC:	56 grams per litre; 0.46 lbs. per gallon as per 40 CFR 59.406
Film Thickness:	15.0 mils wet; 9.15 mils dry
Sizes:	1 Gallon; 5 Gallon

Clean Mildew from the Surface: Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

*Technical data based on Striping White

Application

Application: Stir paint thoroughly. Intermix containers for uniformity. Apply product when surface, air and product temperatures are between 50-90°F Under normal environmental and application conditions, thinning is not required. May be applied by airless (.015-.019 tip) or conventional spray line striping equipment. For small areas, may be applied by nylon/polyester brush or medium nap synthetic roller. Glass beads may be dropped onto wet paint for making reflective markings.

Clean Up/Disposal

Cleanup/Disposal: Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

Cautions

CONTAINS CRYSTALLINE SILICA. Contents are **COMBUSTIBLE.** Keep away from heat and open flame. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (**NIOSH** approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (**NIOSH** approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

352 (4/10)

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Dutch Boy Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Dutch Boy Paint Retailer or sales representative to obtain the most recent Product Data Sheet.