



Concrete Sealer Wet-Look High-Gloss

DBC800-16
DBC800-20

Product Data Sheet

COVERAGE:  100 - 200 sq. ft./gal (smooth & rough surfaces)	DRY TIME (@50-90°F):  Touch: 1 hour Recoat: 2 hours	APPLICATION:  Brush: nylon/polyester Roller: 3/8" - 1/2" synthetic nap Spray (Airless): 0.013" – 0.017" Tip at 500 – 1000 PSI	CLEAN UP:  Warm soapy water
---	---	--	--

Features

- 100% Clear Acrylic Wet-Look High-Gloss sealer that will enhance and protect previously coated and bare concrete surfaces
- This water-based sealer can be used for both interior and exterior applications
- Applies milky white and dries clear
- Protects surface from UV damage, fading, water damage & chemicals

Where To Use

Properly prepared pavers, patios, walkways, stamped concrete, pool decks* and more

Recommended Systems

Dutch Boy Wet Look Sealer provides the surface with a high-gloss finish while sealing and protecting the concrete & masonry.

A two-coat application is recommended, allowing 2 hours drying time before recoating.

Slip Resistance

***Slip Resistance:** Surfaces may be slippery when wet and proper preventative precautions are recommended. To increase resistance, add an anti-skid additive to the coating when applying the final coat. The addition of anti-skid additives will not eliminate the possibility or risk of slipping/skidding or falling.

Technical Data

Vehicle:	Acrylic Emulsion
Pigment Type:	N/A
Viscosity:	10-15" / #4 Ford Cup
Weight Solids:	25.10% +/-1%
Volume Solids:	23.21% +/-1%
Weight per gallon:	8.52 lbs/gal
VOC:	VOC/COV: < 100 g/L
Sizes:	1 gallon-128 oz/gal 5 gallon-640 oz/gal
*DO NOT TINT	

Regulatory Compliance

Current as of: 1/1/2023	SCAQMD- No CARB 2000 SCM- Yes CARB 2007 SCM- Yes OTC/LADCO- Yes EPA- Yes Colorado AIM- Yes
--------------------------------	---

Surface Prep

WARNING! ! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800 424-LEAD or log on to www.epa.gov/lead.

All surfaces must be clean, dry and free of all loose, peeling paint or contaminants. **Bare Concrete:** Allow 30 days minimum for new concrete to cure before applying. New, unpainted or smooth-worn concrete must be prepared and etched with a concrete cleaner/degreaser and etching solution for proper penetration and adhesion. Etch surface to the feel of 120-grit sandpaper at minimum and surface immediately absorbs water.

Application

Avoid using this product on nonporous, sealed surfaces. To test surface, place a few drops of water on the surface. If water immediately sinks in, the surface is porous enough to use this finish. If water remains on the surface, concrete must be etched with an etching solution or muriatic acid, following label instructions. If the surface does not feel like 120-grit sandpaper following the first application, a second etching is required. Allow a minimum of 24 hours to dry before applying Dutch Boy® Wet-Look High-Gloss Clear Sealer.

Previously Stained, Painted or Sealed Concrete: Remove loose or peeling paint with wire brush and degloss surface by sanding (150-200 grit paper). Follow with a concrete cleaner/degreaser and etching solution. Rinse thoroughly and allow to dry completely before applying Dutch Boy Wet-Look High-Gloss Clear Sealer.

For best results, surface and air temperature should be above 50°F and below 90°F. Temperature should not fall below 40°F for 24 hours following application. Stir thoroughly before and during application. **DO NOT OVERAPPLY.** A minimum of 2 coats is recommended. Apply with brush or 3/8" nap roller for smooth surfaces, 1/2" nap for rough or textured surfaces or an airless sprayer. If spray application is used, back roll to avoid build-up. **DO NOT THIN.** **First Coat:** Apply first coat evenly, working in one direction. Allow to dry a minimum of 2 hours before applying second coat. **Second Coat:** Apply second coat crosswise to the first coat for best coverage. Excessively porous surfaces may require a third coat for a uniform appearance. Allow a minimum of 2 hours dry time between each coat. Allow a minimum of 72 to 96 hours under good drying conditions before using the surface for heavy traffic.

Slip Resistance: Surfaces may be slippery when wet and proper preventative precautions are recommended. To increase resistance, add an anti-skid additive to the coating when applying the final coat. The addition of anti-skid additives will not eliminate the possibility or risk of slipping/skidding or falling.

Clean Up/Disposal

Clean up with warm, soapy water. In case of spills, absorb with inert material such as sand or kitty litter. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. Protect containers from freezing. Dispose of empty container or unused portion in accordance with local, state and federal regulations

Return To Service

Recoat within 2 hours, dries to the touch in 1 hour. Dry times will vary depending on weather conditions. Wait 24 hours for light foot traffic and 72-96 hours for full cure and return to full service.

Cautions

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. WARNING: This product contains chemicals known to the State of California to cause birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Dutch Boy Paints. Information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Dutch Boy Paint Retailer or sales representative to obtain the most recent Product Data Sheet.

For more information, please call 1-800-828-5669, or visit www.dutchboy.com