SAFETY DATA SHEET

2557221

Section 1. Identification

Product name	: HGTV HOME™ by Sherwin-Williams OVATION® Plus Interior Semi-Gloss Base C	
Product code	: 2557221	
Other means of identification	Not available.	
Product type	: Liquid.	
Relevant identified uses of	the substance or mixture and uses advised against	
Paint or paint related materia	I.	
Manufacturer	: Manufactured by The Sherwin-Williams Company Cleveland, OH 44115	
Emergency telephone number of the company	: US / Canada: (216) 566-2917 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year	
Product Information Telephone Number	: US / Canada: Not Available Mexico: Not Available	
Transportation Emergency Telephone Number	: US / Canada: (216) 566-2917 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year	

Section 2. Hazards identification

Base C

Date of issue/Date of revision 2557221 HGTV HOME™ by	: 4/19/2024 Date of previous issue : 2/4/2024 Sherwin-Williams OVATION® Plus Interior Semi-Gloss	Version : 10.01 1/13 SHW-85-NA-GHS-US
Response	: IF exposed or concerned: Get medical advice or attention.	
Prevention	: Obtain special instructions before use. Do not handle unti been read and understood. Wear protective gloves, prote protection. Do not breathe vapor. Do not eat, drink or sm Wash thoroughly after handling.	ctive clothing and eye or face
General	: Read label before use. Keep out of reach of children. If n product container or label at hand.	nedical advice is needed, have
Precautionary statements		
Hazard statements	: May cause cancer. Causes damage to organs through prolonged or repeated exposure. (lungs)	
Signal word	: Danger	
Hazard pictograms		
GHS label elements	(oral), 5.5% (dermal), 5.5% (inhalation)	
substance or mixture	: CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EX Percentage of the mixture consisting of ingredient(s) of un	,
Classification of the	(29 CFR 1910.1200).	
OSHA/HCS status	: This material is considered hazardous by the OSHA Haza	rd Communication Standard

Section 2. Hazards identification

Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Kaolin	≤10	1332-58-7
Cristobalite, respirable powder	≤0.3	14464-46-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Section 4. First aid measures

Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.	
Most important symptoms/e	effects, acute and delayed	
Potential acute health effe	<u>cts</u>	
Eye contact	: No known significant effects or critical hazards.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: No known significant effects or critical hazards.	
Ingestion	: No known significant effects or critical hazards.	
Over-exposure signs/symp	<u>ptoms</u>	
Eye contact	: No specific data.	
Inhalation	: No specific data.	
Skin contact	: No specific data.	
Ingestion	: No specific data.	
Indication of immediate mee	dical attention and special treatment needed, if necessary	
Notes to physician	 In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. 	
Specific treatments	: No specific treatment.	
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.	

See toxicological information (Section 11)

Base C

Section 5. Fire-fighting measures

Extinguishing media			
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.		
Unsuitable extinguishing media	: None known.		
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the co	ontainer may burst.	
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides		
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the w there is a fire. No action shall be taken involving any persona training.		
Date of issue/Date of revision	: 4/19/2024 Date of previous issue : 2/4/2024	Version : 10.01 3/13	
2557221 HGTV HOME™ by S	Sherwin-Williams OVATION® Plus Interior Semi-Gloss	SHW-85-NA-GHS-US	

Section 5. Fire-fighting measures

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protect	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ont	ainment and cleaning up
Small spill	÷	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up

Large spill
 Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste

Section 7. Handling and storage

Precautions for safe handlin	ā
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Section 7. Handling and storage

Conditions for safe storage,	: Store in accordance with local regulations. Store in original container protected from
including any	direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials
incompatibilities	(see Section 10) and food and drink. Store locked up. Keep container tightly closed
-	and sealed until ready for use. Containers that have been opened must be carefully
	resealed and kept upright to prevent leakage. Do not store in unlabeled containers.
	Use appropriate containment to avoid environmental contamination. See Section 10 for
	incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Kaolin	1332-58-7	ACGIH TLV (United States, 1/2023). TWA: 2 mg/m ³ 8 hours. Form: Respirable fraction NIOSH REL (United States, 10/2020). TWA: 5 mg/m ³ 10 hours. Form: Respirable fraction TWA: 10 mg/m ³ 10 hours. Form: Total OSHA PEL (United States, 5/2018). TWA: 5 mg/m ³ 8 hours. Form: Respirable fraction TWA: 15 mg/m ³ 8 hours. Form: Total dust
Cristobalite, respirable powder	14464-46-1	 OSHA PEL Z3 (United States, 6/2016). TWA: 250 mppcf / 2 x (%SiO2+5) 8 hours. Form: Respirable TWA: 10 mg/m³ / 2 x (%SiO2+2) 8 hours. Form: Respirable TWA: 30 mg/m³ / 2 x (%SiO2+2) 8 hours. Form: Total dust OSHA PEL (United States, 5/2018). [Silica, crystalline] TWA: 50 μg/m³ 8 hours. Form: Respirable dust ACGIH TLV (United States, 1/2023). [Silica, crystalline] TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction NIOSH REL (United States, 10/2020). [SILICA, CRYSTALLINE (AS RESPIRABLE DUST)] TWA: 0.05 mg/m³ 10 hours. Form: respirable dust

Occupational exposure limits (Canada)

Ingredient	name		CAS #	Exposure lim	its		
Kaolin			1332-58-7	8 hrs OEL: 2 Respirable CA Quebec P TWAEV: 2 m dust. CA Ontario P	rovincial (Canad mg/m ³ 8 hours. rovincial (Cana g/m ³ 8 hours. Fo rovincial (Cana n ³ 8 hours. Form tter.	Form: I da, 6/202 orm: Res Ida, 6/201	22). pirable 9).
Date of issue/Date	ate of revision	: 4/19/2024	Date of previous issue	: 2/4/2024	Version	: 10.01	5/13
557221	HGTV HOME™ by \$ Base C	Sherwin-Williams OVATI	ON® Plus Interior Semi-Gloss		SHW-85	-NA-GHS-U	S

Section 8. Exposure controls/personal protection

		CA Saskatchewan Provincial (Canada,
		7/2013).
		STEL: 4 mg/m ³ 15 minutes. Form: respirable
		fraction
		TWA: 2 mg/m ³ 8 hours. Form: respirable
		fraction
		CA British Columbia Provincial (Canada,
		6/2022). Notes: the value is for particulate
		matter containing no asbestos and less
		than 1% crystalline silica.
		TWA: 2 mg/m ³ 8 hours. Form: Respirable
Cristobalite	14464-46-1	CA British Columbia Provincial (Canada,
		6/2022). [Silica, Crystalline - alpha quartz
		and Cristobalite Respirable]
		TWA: 0.025 mg/m ³ 8 hours. Form:
		Respirable
		CA Quebec Provincial (Canada, 6/2022).
		TWAEV: 0.05 mg/m ³ 8 hours. Form:
		Respirable dust.
		CA Alberta Provincial (Canada, 6/2018).
		8 hrs OEL: 0.025 mg/m ³ 8 hours. Form:
		Respirable particulate
		CA Ontario Provincial (Canada, 6/2019).
		TWA: 0.05 mg/m ³ 8 hours. Form: Respirable
		particulate matter.
		CA Saskatchewan Provincial (Canada,
		7/2013).
		TWA: 0.05 mg/m ³ 8 hours. Form: respirable
		fraction

Occupational exposure limits (Mexico)

	CAS #	Exposure limits
None.		

Biological exposure indices (United States)

No exposure indices known.

Biological exposure indices (Canada)

No exposure indices known.

Biological exposure indices (Mexico)

No exposure indices known.

Appropriate engineering controls		If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Date of issue/Date	of revision	: 4/19/2024	Date of previous issue	: 2/4/2024
2557221	HGTV HOME™ by Sherwin Base C	n-Williams OVATIO	N® Plus Interior Semi-Gloss	

Section 8. Exposure controls/personal protection

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	: Liquid.
Color	: Clear.
Odor	: Not available.
Odor threshold	: Not available.
рН	: 9.3
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: 100°C (212°F)
Flash point	: Closed cup: Not applicable.
Evaporation rate	: 0.09 (butyl acetate = 1)
Flammability	: Not available.
Lower and upper explosion limit/flammability limit	: Not available.
Vapor pressure	: 2.3 kPa (17.5 mm Hg)
Relative vapor density	: 1 [Air = 1]
Relative density	: 1.09
Solubility(ies)	:

Section 9. Physical and chemical properties

	Media		Result
	cold water		Partially soluble
Partition coefficient: n- : Not octanol/water		:	Not applicable.
A	Auto-ignition temperature : Not		Not available.
D	Decomposition temperature : Not		Not available.
V	scosity	1	Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)
Molecular weight : Not		1	Not applicable.
	Heat of combustion : 0.29		0.294 kJ/g

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Not available.

Irritation/Corrosion

Not available.

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Cristobalite, respirable powder	+	1	Known to be a human carcinogen.

Reproductive toxicity

Not available.

Date of issue/Date	e of revision	: 4/19/2024	Date of previous issue	: 2/4/2024	Version : 10.0	01 8/13
2557221	HGTV HOME™ by Sherw Base C	in-Williams OVATI	ON® Plus Interior Semi-Gloss		SHW-85-NA-GI	HS-US

Section 11. Toxicological information

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Kaolin	Category 1		lungs
Cristobalite, respirable powder	Category 1		respiratory tract

Aspiration hazard

Not available.

Information on the likely routes of exposure	:	Not available.				
Potential acute health effe	cts					
Eye contact	1	No known significant effects or critical hazards.				
Inhalation	1	No known significant effects or critical hazards.				
Skin contact	1	No known significant effects or critical hazards.				
Ingestion	1	No known significant effects or critical hazards.				
Symptoms related to the p	ohy	sical, chemical and toxicological characteristics				
Eye contact	1	No specific data.				
Inhalation	:	No specific data.				
Skin contact	1	No specific data.				
Ingestion	:	No specific data.				
	fec	ts and also chronic effects from short and long term exposure				
Short term exposure Potential immediate effects	:	Not available.				
Potential delayed effects	:	Not available.				
Long term exposure						
Potential immediate effects	:	Not available.				
Potential delayed effects	:	Not available.				
Potential chronic health effects						
Not available.						
General	:	Causes damage to organs through prolonged or repeated exposure.				
Carcinogenicity	:	May cause cancer. Risk of cancer depends on duration and level of exposure.				
Mutagenicity	:	No known significant effects or critical hazards.				
Teratogenicity	:	No known significant effects or critical hazards.				
Developmental effects	:	No known significant effects or critical hazards.				
Fertility effects	:	No known significant effects or critical hazards.				

Numerical measures of toxicity

Date of issue/Date	e of revision	: 4/19/2024	Date of previous issue	: 2/4/2024	Version :	10.01	9/13
2557221 HGTV HOME™ by Sherwin-Williams OVATION® Plus Interior Semi-Gloss Base C					SHW-85-NA	A-GHS-US	

Section 11. Toxicological information

Section 12. Ecological information

Acute toxicity estimates

Not available.

Toxicity

Persistence and de Not available.	<u>gradability</u>				
<mark>Bioaccumulative po</mark> Not available.	<u>ptential</u>				
<u>Mobility in soil</u> Soil/water partition coefficient (K _{oc})	n : Not av	ailable.			
Other adverse effec	ts : No kno	own significant effects	or critical hazards.		
Section 13. I	Disposal cor	nsiderations			
	the sev Waste when r safe w cleane Avoid and se		liant with the required recycled. Incineration e. This material and aken when handling ty containers or liners	ments of all author on or landfill should l its container must emptied containers s may retain some	ities with jurisdiction. d only be considered be disposed of in a that have not been product residues.
Section 14.	i ransport in	Tormation			
Section 14.	DOT	TDG	Mexico	ΙΑΤΑ	IMDG
Section 14.	•		Mexico Classification Not regulated.	IATA Not regulated.	IMDG Not regulated.
	DOT Classification	TDG Classification	Classification		
UN number UN proper	DOT Classification	TDG Classification	Classification		
UN proper shipping name Transport	DOT Classification Not regulated.	TDG Classification	Classification		

Additional - information	-	-	-	-
Special precautions for use				
ransport in bulk according	consider contain mode of transpo suitably for that to shipment, and of the person off dangerous good and on all action	her sizes. The presence ort (sea, air, etc.), does mode of transport. All p	e of a shipping descrip not indicate that the p packaging must be rev applicable regulations i ansport. People loadir Il of the risks deriving	roduct is packaged riewed for suitability prior is the sole responsibility ng and unloading

Section 15. Regulatory information

TSCA 5(a)2 proposed significant new use rules: 2-Methyl-4-isothiazolin-3-one; reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet, where applicable.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists

Australia inventory (AIIC): Not determined.
 China inventory (IECSC): Not determined.
 Japan inventory (CSCL): Not determined.
 Japan inventory (ISHL): Not determined.
 Korea inventory (KECI): Not determined.
 New Zealand Inventory of Chemicals (NZIoC): Not determined.
 Philippines inventory (PICCS): Not determined.
 Taiwan Chemical Substances Inventory (TCSI): Not determined.
 Thailand inventory: Not determined.
 Turkey inventory: Not determined.
 Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

	Classification	Justification	
CARCINOGENICITY - Category 1A Calculation method SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 Calculation method			
<u>History</u>			
Date of printing	: 4/19/2024		
Date of issue/Date of revision	: 4/19/2024		
Date of previous issue	: 2/4/2024		
Version	: 10.01		
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification a IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coeff MARPOL = International Convention for the Preventior as modified by the Protocol of 1978. ("Marpol" = marine N/A = Not available SGG = Segregation Group UN = United Nations	icient of Pollution From Ships, 1973	

Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs

Date of issue/Date	of revision	: 4/19/2024	Date of previous issue	: 2/4/2024	Version	:10.01	12/13
2557221	HGTV HOME™ by Sherwin Base C	-Williams OVATIO	DN® Plus Interior Semi-Gloss		SHW-85	-NA-GHS-US	

Section 16. Other information

obtained from any other source.

: 2/4/2024