



HGTV HOME™ BY SHERWIN-WILLIAMS

Interior/Exterior Acrylic Latex High Gloss GL003700 Series Series

<u>CHARACTERISTICS</u>	<u>SPECIFICATIONS</u>	<u>SURFACE PREPARATION</u>
<p>HGTV HOME™ by Sherwin-Williams High Gloss is a stain resistant paint & primer in one with a durable glass-like enamel finish.</p> <p>This HGTV HOME by Sherwin-Williams product is recommended for use on properly prepared interior and exterior trim, molding, cabinets, doors, windows and walls of drywall, plaster, masonry, wood and primed metal. Ideal for kitchens, bathrooms, laundry rooms and high traffic areas.</p> <p>Color: Most colors, Black Coverage: 400 sq ft/gal @ 4 mils wet; 1.6 mils dry Drying Time, @77°F, 50% RH: Touch: 1 hour Recoat: 4 hours <small>Drying and recoat times are temperature, humidity, and film thickness dependent</small> Finish: >70 units @ 60° Flash Point: N/A Vehicle Type: Acrylic GL003700 VOC (less exempt solvents): <50 g/L; <0.42 lb/gal <small>As per 40 CFR 59.406 and SOR/2009-264, s.12</small> Volume Solids: 34 ± 2% Weight Solids: 44 ± 2% Weight per Gallon: 9.79 lb</p> <p>Mildew Resistant This coating contains agents which inhibit the growth of mildew on the surface of this coating film.</p>	<p>Drywall, Plaster, Wood, Composition board 1 ct. HGTV HOME™ by Sherwin-Williams High Gloss or 1 ct. Of an appropriate primer 1 ct. HGTV HOME™ by Sherwin-Williams High Gloss</p> <p>Masonry, Concrete, Cement, Block (Can be filled to provide a smooth surface or primed if the substrate has a high pH) 1 ct. Of an appropriate primer or filler 2 cts. HGTV HOME™ by Sherwin-Williams High Gloss</p> <p>HGTV HOME™ by Sherwin-Williams High Gloss can be used directly over existing coatings, or bare drywall, plaster and masonry (both with a cured pH of less than 9) and non-bleeding wood.</p> <p>When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.</p>	<p>WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p> <p>Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or damaged paint to a sound surface. Sand glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with the appropriate primer/sealer. Caulk around windows, doors, and other openings after spot priming bare surfaces with HGTV HOME™ by Sherwin-Williams High Gloss.</p> <p>Drywall Fill cracks and holes with patching paste/spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.</p> <p>Plaster Base plaster must be cured and hard. Textured, soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon water. Repeat until the surface is hard, rinse with clear water and allow to dry.</p> <p>Wood Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.</p>



HGTV HOME™ BY SHERWIN-WILLIAMS

Interior/Exterior Acrylic Latex High Gloss GL003700 Series

SURFACE PREPARATION

Masonry, Concrete, Cement, Block

All new surfaces must be cured according to the suppliers recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with an appropriate primer. For extremely porous surfaces, a coat of block filler may be required to achieve a pinhole free film.

Caulking

Gaps between windows, doors, trim, and other through-wall openings can be filled with the appropriate caulk after priming the surface.

SURFACE PREPARATION

Mildew

Clean Mildew from the Surface: Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

APPLICATION

Apply at temperatures above 35°F.

No reduction necessary.

Brush

Use a nylon/polyester brush.

Roller

Use a 3/8" nap synthetic cover. **Spray—**

Airless

Pressure..... 2000 psi

Tip..... .013"-.017"

CLEANUP INFORMATION

Clean spills, spatters, hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with mineral spirits to prevent rusting of the equipment.

Follow manufacturer's instructions when using mineral spirits.

Do not pour unused contents down the drain. Consult with local authorities for proper methods of disposal and recycling.

CAUTIONS

Protect from freezing.

Non-photochemically reactive.

LABEL CAUTIONS

CAUTION contains CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**
16(1/10)

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.