



# Ovation® Plus Interior Paint & Primer

Interior Acrylic Latex  
Semi-Gloss

<u>CHARACTERISTICS</u>	<u>SPECIFICATIONS</u>	<u>SURFACE PREPARATION</u>								
<p><b>Ovation® Plus Interior Paint &amp; Primer</b> delivers beautiful coverage and a lasting finish all while having zero VOC's. This formula provides an easy, uniform application that confidently withstands scrubbing and stains.</p> <p><b>Color:</b> Most Colors</p> <p><b>Coverage:</b> Up to 400 sq ft/gal @ 4 mils wet; 1.5 mils dry</p> <p><b>Drying Time, @77°F, 50% RH:</b></p> <p>Touch: 1 Hour</p> <p>Recoat: 2-4 hours</p> <p><small>Drying and recoat times are temperature, humidity, and film thickness dependent</small></p> <p><b>Finish:</b> 40-50 units @ 85°</p> <p><b>Flash Point:</b> N/A</p> <p><b>Tinting with HydroChroma™ :</b></p> <table border="0"> <tr> <td>Base</td> <td>oz/gal</td> </tr> <tr> <td>Ultra White</td> <td>0-6</td> </tr> <tr> <td>Base B</td> <td>6-10</td> </tr> <tr> <td>Base C</td> <td>14</td> </tr> </table> <p><b>Vehicle Type:</b> Acrylic</p> <p><b>VOC (less exempt solvents):</b> &lt;50 g/L; &lt;0.42 lb/gal <small>As per 40 CFR 59.406 and SOR/2009-264, s.12</small></p> <p><b>Volume Solids:</b> 39%</p> <p><b>Weight Solids:</b> 52%</p> <p><b>Weight per Gallon:</b> 10.63 lb./gal.</p> <p><b>Mildew Resistant</b> This coating contains agents which inhibit the growth of mildew on the surface of this coating film.</p>	Base	oz/gal	Ultra White	0-6	Base B	6-10	Base C	14	<p><b>Previously Painted Drywall, Plaster</b> 1 ct. Ovation® Plus Interior Paint &amp; Primer</p> <p><b>New Drywall, Plaster<sup>1</sup></b> 1 ct. Ovation® Plus Interior Paint &amp; Primer</p> <p><sup>1</sup> Porous surfaces, such as uncoated drywall, will absorb paint making the finish blotchy or dull. For best results on these surfaces, sealing the surface with a primer first will result in a smooth, uniform paint finish.</p> <p><b>Composition Board, Masonry, Block, Metal</b> 1 ct. Ovation® Plus Interior Paint &amp; Primer</p> <p><b>Wood (Cedar, Redwood)<sup>2</sup></b> 1 ct. Ovation® Plus Interior Paint &amp; Primer</p> <p><sup>2</sup> Knots and some woods, such as red-wood and cedar, contain a high amount of tannin, a colored wood extract. If applied to these woods, tannins must be "locked in" by spot priming to prevent bleeding through the paint.</p> <p>When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.</p>	<p><b>WARNING!</b> Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p> <p>Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or damaged paint to a sound surface. Sand glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with the appropriate primer/sealer. Caulk around windows, doors, and other openings after spot priming bare surfaces with Ovation® Plus paint.</p> <p><b>Drywall</b> Fill cracks and holes with patching paste/spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.</p> <p><b>Plaster</b> Base plaster must be cured and hard. Textured, soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon water. Repeat until the surface is hard, rinse with clear water and allow to dry.</p> <p><b>Wood</b> Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.</p>
Base	oz/gal									
Ultra White	0-6									
Base B	6-10									
Base C	14									



# Ovation® Plus Interior Paint & Primer

Interior Acrylic Latex  
Semi-Gloss

<p><b><u>SURFACE PREPARATION</u></b></p> <p><b>Masonry, Concrete, Cement, Block</b> All new surfaces must be cured according to the suppliers recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with an appropriate primer.</p> <p><b>Caulking</b> Gaps between windows, doors, trim, and other through-wall openings can be filled with the appropriate caulk after priming the surface.</p> <p><b>MAINTENANCE:</b> For touching-up, reduce the product by one pint per gallon with water. To ensure maximum washability and durability, wait at least 14 days before washing Ovation® Plus paint. When removing stains, dirt and marks, use a soft cloth or sponge with water. Stubborn stains may require the use of a general purpose household cleaner for total removal. Do not use an abrasive cleaner or scrub brush to remove stains.</p>	<p><b><u>SURFACE PREPARATION</u></b></p> <p><b>Clean Mildew from the Surface:</b> Mildew is a fungus that looks like dirt, but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.</p> <p><b><u>APPLICATION</u></b></p> <p>Apply at temperatures above 50°F. Thinning not required.</p> <p><b>Brush</b> Use a premium-quality synthetic brush.</p> <p><b>Roller</b> Use a 1/4" - 3/4" nap soft woven or synthetic roller is preferred.</p> <p><b>Spray—Airless</b> Pressure..... 2000 psi Tip..... .015"-019"</p> <p><b><u>CLEANUP INFORMATION</u></b></p> <p><b>Cleanup/Disposal:</b> Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.</p>	<p><b><u>CAUTIONS</u></b></p> <p>For interior use only. Protect from freezing.</p> <p><b>LABEL CAUTIONS</b> <b>CONTAINS CRYSTALLINE SILICA.</b> Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (<b>NIOSH</b> approved) or leave the area. Adequate venti-lation required when sanding or abrading dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (<b>NIOSH</b> approved) . Follow respirator manufacturer's directions for respi-rator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. <b>FIRST AID:</b> In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physi-cian immediately. <b>DELAYED FFECTS FROM LONG TERM OVEREXPOSURE.</b> Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. <b>WARNING:</b> This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. <b>DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.</b> 16 (1/10)</p> <p>The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.</p>
--	---	---