



Infinity®
Interior Acrylic Latex
Semi-Gloss
IN4025001 Series

CHARACTERISTICS

Infinity® Interior Advanced Performance Paint & Primer delivers our Gold Standard™ that repels stains, resists scuff marks and scratches with one-coat perfection™. Our most durable paint blocks out existing stains with its stain blocking capabilities and allows for common household stains to be washed away with ease. This HGTV HOME® by Sherwin-Williams product is the perfect choice for customers that want the best. Ideal for properly prepared interior walls, trim and ceilings, previously painted or bare drywall, plaster, masonry and primed metal.

Color: Most Colors
Coverage: 400 sq. ft./gal
@ 4 mils wet; 1.5 mils dry

Drying Time, @ 77°F, 50% RH:
Touch: 1 Hour
Recoat: 2-4 Hours

Drying and recoat times are temperature, humidity, and film thickness dependent

Finish: 40 - 50 units @ 60°
Flash Point: N/A
Tinting with HydroChroma™:

Base	oz/gal	Strength
Ultra White	0-6	100%
Base B	6-10	100%
Base C	18	100%
Vehicle Type:	100% Acrylic	

VOC (less exempt solvents):
<50 g/L; <0.42 lb./gal
As per 40 CFR 59.406 and SOR/2009-264, s.12

Volume Solids: 42 ± 2%
Weight Solids: 54 ± 2%
Weight per Gallon: 10.79 lbs.

Mildew Resistant

This coating contains agents which inhibit the growth of mildew on the surface of this coating film.

SPECIFICATIONS

Previously Painted Drywall. Plaster:
1 ct. Infinity® Interior Paint & Primer

New Drywall, Plaster¹:
1 ct. Infinity® Interior Paint & Primer

¹Porous surfaces, such as uncoated drywall, will absorb paint making the finish blotchy or dull. For best results on these surfaces, sealing the surface with a primer first will result in a smooth, uniform paint finish.

Composition Board, Masonry, Block, Metal:
1 ct. Infinity® Interior Paint & Primer

Wood (Cedar, Redwood)²:
1 ct. Infinity® Interior Paint & Primer

² Knots and some woods, such as redwood and cedar, contain a high amount of tannin, a colored wood extract. If applied to these woods, tannins must be "locked in" by spot priming to prevent bleeding through the paint.

When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or damaged paint to a sound surface. Sand glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with the appropriate primer/sealer. Caulk around windows, doors, and other openings after spot priming bare surfaces with Infinity® paint.

Drywall

Fill cracks and holes patching paste/spackle and sand smooth. Joint compounds must be cured and sanded smooth. Remove all sanding dust.

Plaster

Base plaster must be cured and hard. Textured, soft, porous, or powdery plaster should be treated with a solution of 1 pint household vinegar to 1 gallon water. Repeat until the surface is hard, rinse with clear water and allow to dry.

Wood

Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth.



Infinity®
Interior Acrylic Latex
Semi-Gloss
IN4025001 Series

SURFACE PREPARATION

Masonry, Concrete, Cement, Block

All new surfaces must be cured according to the supplier's recommendations – usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with an appropriate primer.

Caulking

Gaps between windows, doors, trim, and other through-wall openings can be filled with the appropriate caulk after priming the surface.

Mildew

Remove before painting by washing with a solution of 1-part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.

MAINTENANCE:

For touching-up, reduce the product by one pint per gallon with water. To ensure maximum washability and durability, wait at least 14 days before washing Infinity® coating. When removing stains, dirt and marks, use a soft cloth or sponge with water. Stubborn stains may require the use of a general-purpose household cleaner for total removal. Do not use an abrasive cleaner or scrub brush to remove stains.

APPLICATION

Apply at temperatures above 50°F.

Thinning not required.

Brush

Use a premium-quality synthetic brush.

Roller

Use a 1/4" - 3/4" nap soft woven or synthetic roller

Spray—Airless

Pressure: 2000 psi

Tip Size: .015"-.019"

CLEAN UP INFORMATION

Clean spills, spatters, hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with compliant clean up solvent to prevent rusting of the equipment.

Follow manufacturer's safety recommendations when using solvents.

Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

CAUTIONS

For interior use only.
Protect from freezing.

LABEL CAUTIONS

CONTAINS CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (**NIOSH** approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (**NIOSH** approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.

Document Code: HGTVSWINFINTSG