



# EVERLAST®

## Exterior Acrylic Latex Enamel Semi Gloss EV002500 Series

CHARACTERISTICS	SPECIFICATIONS	SURFACE PREPARATION
<p><b>EVERLAST® Exterior Complete One Coat Paint &amp; Primer</b></p> <p>Everlast™ Exterior Paint &amp; Primer gives extreme all-weather protection in just one coat. Ever strong, ever beautiful, come sun, snow, rain or ice! Self Cleaning Technology - rinses away dirt and residue with rain showers or a garden hose. The enhanced fade-resistant technology protects against harmful UV rays, while its durable, 100% acrylic enamel provides a mildew- and algae- resistant finish. Not for use on floors.</p> <p><b>Color:</b> Most Colors  <b>Coverage:</b> 250-400 sq ft/gal  @ 4 mils wet; 1.5 mils dry  <b>Drying Time, @77°F, 50% RH:</b>  Touch: 1 Hour  Recoat: 4 hours  <b>Drying Time, @35-45°F, 50% RH:</b>  Touch: 2 Hours  Recoat: 24-48 hours  <small>Drying and recoat times are temperature, humidity, and film thickness dependent</small>  <b>Finish:</b> 15-30 units @ 60°  <b>Flash Point:</b> 499°F</p> <p><b>Vehicle Type:</b> Acrylic  <b>EV0014001</b>  <b>VOC (less exempt solvents):</b>  &lt;50 g/L; &lt;0.42 lb/gal  <small>As per 40 CFR 59.406 and SOR/2009-264, s.12</small>  <b>Volume Solids:</b> 37 ± 2%  <b>Weight Solids:</b> 48 ± 2%  <b>Weight per Gallon:</b> 10.08 lb</p> <p><b>Mildew Resistant</b>  This coating contains agents which inhibit the growth of mildew on the surface of this coating film.</p>	<p><b>Aluminum &amp; Aluminum Siding, Galvanized Steel, Steel, Vinyl Siding, Concrete Block, Wood, Plywood/Composition Board</b>  1 ct. EVERLAST® Exterior Paint &amp; Primer</p> <p><b>Brick, CMU, Cement Composition Siding/Panels, Stucco, Cement, Concrete</b>  1 ct. EVERLAST® Exterior Paint &amp; Primer</p> <p><b>Wood (Cedar, Redwood)<sup>1</sup></b>  1 ct. EVERLAST® Exterior Paint &amp; Primer</p> <p><sup>1</sup> Knots and some woods, such as redwood and cedar, contain a high amount of tannin, a colored wood extract. If applied to these woods, tannins must be "locked in" by spot priming to prevent bleeding through the paint.</p> <p>When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.</p>	<p><b>WARNING!</b> Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.</p> <p>Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or damaged paint to a sound surface. Sand glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with the appropriate primer/sealer. Caulk around windows, doors, and other openings after spot priming bare surfaces with EVERLAST® paint.</p> <p><b>Aluminum and Galvanized Steel</b>  Wash to remove any oil, grease, or other surface contamination. All corrosion must be removed with sandpaper, steel wool, or other abrading method.</p> <p><b>Cement Composition Siding/Panels</b>  Remove all dirt, dust, grease, oil, loose particles, laitance, foreign material, and peeling or defective coatings. Allow the surface to dry thoroughly. If the surface is new, test it for pH, if the pH is higher than 8, prime with an appropriate primer.</p> <p><b>Wood, Plywood, Composition Board</b>  Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. All patched areas must be primed.</p>



# EVERLAST®

## Exterior Acrylic Latex Enamel

### Semi Gloss

### EV002500 Series

#### SURFACE PREPARATION

Remove surface contaminants with an appropriate cleaner, rinse thoroughly and allow to dry. Remove peeled or damaged paint. Sand glossy surfaces dull. Seal stains with the appropriate primer. Caulk around windows, doors and other openings after spot priming bare surfaces.

**Concrete, Stucco, Masonry, Block, Cement Composition Siding:** All new surfaces must be cured. Remove all form release and curing agents. If the pH is higher than 8, prime with a masonry primer. Rough surfaces may be smoothed with block filler. Cracks, voids and other holes should be repaired with an elastomeric patch or sealant. For drastic color changes or deep, vivid colors, prime with this product or an appropriate tintable primer for your optimal color accuracy and coverage.

#### **Steel**

Rust and mill scale must be removed using sandpaper, steel wool, or other abrading method. Bare steel must be primed the same day as cleaned.

#### **Vinyl**

Clean the surface thoroughly by scrubbing with warm, soapy water. Rinse thoroughly. Repaint vinyl siding with a color similar to the original color to avoid excess heat absorption to prevent buckling or warping.

#### **Caulking**

Gaps between windows, doors, trim, and other through-wall openings can be filled with the appropriate caulk after priming the surface.

#### **Clean Mildew from the Surface**

Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.

#### SURFACE PREPARATION

(Cont'd) Knots and some woods, such as redwood and cedar, contain a high amount of tannin, a colored wood extract. If applied to these unpainted woods, the first coat of paint may show some staining, but it will be trapped in the first coat. A second coat will uniform the appearance. If staining persists, spot prime severe areas with a stain-blocking primer.

#### APPLICATION

Stir paint thoroughly. Intermix containers for uniformity. When air temperature is 35°F, substrates may be colder; prior to painting, check to be sure the air, surface and material temperatures are above 35°F and at least 5°F above the dew point. Avoid using if rain or snow is expected within 1 hour. Do not apply when air or surface temperatures may drop below 35°F within 48 hours. On large expanses of metal siding, the air, surface and material temperatures must be 50°F or higher. No reduction necessary. Apply with a premium-quality brush, a synthetic roller cover or airless spray (2000 PSI, .015"-.019" tip). Some deep or bright colors, surface conditions and application techniques may impact coverage and require more than one coat to achieve your optimal coverage. For additional application tips go to [hgtvhomebysherwinwilliams.com](http://hgtvhomebysherwinwilliams.com).

**Brush:** Use a premium-quality synthetic brush.

**Roller:** Use a 3/8" - 3/4" nap synthetic roller

**Spray—Airless:**

Pressure..... 2000 psi

Tip ..... .015"-.019"

#### CLEANUP INFORMATION

Clean spills, splatters, hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with compliant clean up solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

#### CAUTIONS

For exterior use only.  
Protect from freezing.

#### LABEL CAUTIONS

#### **CONTAINS CRYSTALLINE SILICA.**

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (**NIOSH** approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (**NIOSH** approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS**

#### **FROM LONG TERM OVEREXPOSURE.**

Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.