



Spec Right® Interior Paint & Primer

Interior Acrylic Latex
Eggshell

<u>CHARACTERISTICS</u>	<u>APPLICATION</u>	<u>SURFACE PREPARATION</u>
<p>Spec Right® Interior Paint & Primer is an acrylic latex formula with zero VOC. It's easy to apply and delivers excellent hide & coverage. With exceptional touch-up and a mold- & mildew-resistant finish, this product can be recoated quickly and cleaned up easily with soap and water.</p> <p>Color: Most Colors Coverage: Up to 400 sq ft/gal @ 4 mils wet; 1.7 mils dry Drying Time, @77°F, 50% RH: Touch: 1 Hour Recoat: 2-4 hours Drying and recoat times are temperature, humidity, and film thickness dependent Finish: 15-25 units @ 85° Flash Point: N/A Tinting with Novo™ : Base oz/gal Ultra White 0-6 Base B 6-10 Base C 14 Vehicle Type: Acrylic Latex</p> <p>VOC (less exempt solvents): <50 g/L; <0.42 lb/gal As per 40 CFR 59.406 and SOR/2009-264, s.12 Volume Solids: 43% Weight Solids: 56% Weight per Gallon: 11.08 lb./gal.</p> <p>Mildew Resistant This coating contains agents which inhibit the growth of mildew on the surface of this coating film.</p>	<p>Stir paint thoroughly. Intermix containers for uniformity. Apply product when surface, air and product temperatures are between 50-90°F. Apply with a premium-quality brush, a synthetic roller cover or airless spray (2000 PSI, .015"-.019" tip). Thinning not required. Some deep or bright colors, surface conditions and application techniques may impact coverage and require multiple coats to achieve your optimal coverage.</p> <p>For additional application tips, go to hgtvhomebysherwinwilliams.com.</p> <p>Brush Use a premium-quality synthetic brush. Roller Use a 1/4" - 3/4" nap soft woven or synthetic roller is preferred. Spray—Airless Pressure 2000 psi Tip015"-.019"</p>	<p>WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.</p> <p>Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull.</p> <p>Drywall Fill cracks and holes with patching paste and sand smooth.</p> <p>Plaster, Masonry, Block New surfaces must cure at least 30 days. Fill rough surfaces if desired.</p> <p>Wood Sand to a fresh surface. Patch imperfections with wood filler.</p> <p>Priming This product can be used to prime patched areas, unpainted surfaces and lightly stained areas before applying it as the finish coat.</p> <p>For best results on heavily stained areas, use a coat of an appropriate stain-blocking primer.</p> <p>For drastic color changes or deep, vivid colors, prime with this product or an appropriate tintable primer for your optimal color accuracy and coverage.</p>



Spec Right® Interior Paint & Primer

Interior Acrylic Latex
Eggshell

<p><u>SURFACE PREPARATION</u></p> <p>Masonry, Concrete, Cement, Block All new surfaces must be cured according to the suppliers recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with an appropriate primer.</p> <p>Caulking Gaps between windows, doors, trim, and other through-wall openings can be filled with the appropriate caulk after priming the surface.</p> <p>MAINTENANCE: For touching-up, reduce the product by one pint per gallon with water. To ensure maximum washability and durability, wait at least 14 days before washing Spec Right® paint. When removing stains, dirt and marks, use a soft cloth or sponge with water. Stubborn stains may require the use of a general purpose household cleaner for total removal. Do not use an abrasive cleaner or scrub brush to remove stains.</p>	<p><u>SURFACE PREPARATION</u></p> <p>Clean Mildew from the Surface: Mildew is a fungus that looks like dirt, but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.</p> <p><u>CLEANUP INFORMATION</u></p> <p>Cleanup/Disposal: Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.</p>	<p><u>CAUTIONS</u></p> <p>For interior use only. Protect from freezing.</p> <p>LABEL CAUTIONS CONTAINS CRYSTALLINE SILICA. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. 16 (1/10)</p> <p>The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.</p>
--	--	---