



Cabinet, Door & Trim Primer

Interior/Exterior Latex

CHARACTERISTICS

Cabinet, Door & Trim Primer is a high-quality latex primer offering excellent stain-blocking properties and promotes a durable, uniform finish. Designed to adhere to glossy surfaces, this primer assures adhesion with minimal surface prep.

- Recoat in 1 hour
- Works with all paint sheens
- Blocks tannin stains
- May be used as packaged or tinted
- Ideal for kitchen cabinets, varnished woodwork, vinyl, fiberglass/steel/metal/aluminum doors and previously painted surfaces
- Helps resist corrosion

Coverage: Up to 500 sq ft/gal depending on surface texture and porosity.

Drying Time, @77°F, 50% RH:

Touch: 30 minutes

Recoat: 1 hour

Drying and recoat times are temperature, humidity, and film thickness dependent

Finish: 0-10 units @ 60°

Flash Point: N/A

Vehicle Type: Urethane Modified Acrylic

VOC (less exempt solvents):

<100 g/L

As per 40 CFR 59.406 and SOR/2009-264, s.12

Volume Solids: 32%

Weight Solids: 47%

Weight per Gallon: 10.76 lbs./gal.

Tintable up to 2oz of colorant.

WHERE TO USE

Properly prepared interior and exterior surfaces, including wood, vinyl, metal, and previously painted surfaces.

CHARACTERISTICS

Freight Classification:

Paint or paint related material. Protect from freezing.

Packaging:

5474410 Quart – 4 per carton
5474409 Gallon – 4 per carton

COMPOSITION

Base and Fill Levels

(oz./gal.)

White 126

APPLICATION

Stir primer thoroughly before and during use. Apply with a premium-quality polyester brush, roller or airless sprayer. If applying by sprayer, back-roll or back-brush to work primer into the surface. Apply a liberal coat of primer uniformly, working well into the surface. Apply at temperatures above 35° F. Prior to painting, check to be sure the air, surface and material temperatures are above 35° F and at least 5° F above the dew point. Avoid using if rain or snow is expected within 2-3 hours. Air and surface temperatures must not drop below 35° F for 48 hours after application.

For additional application tips, go to hgtvhomebysherwinwilliams.com.

Brush

Use a premium-quality synthetic brush.

Roller

Use a 1/4" - 3/4" nap soft woven or synthetic roller is preferred.

Spray—Airless

Pressure: 2000 psi

Tip: 015"-.021"

STORAGE & DISPOSAL

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.

SURFACE PREPARATION

General:

Surfaces must be clean, dry and dull prior to application. Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull. All dust should be removed.

Wood:

Sand to a fresh surface. Patch imperfections with wood filler.

Metal:

New galvanized surfaces should be allowed to age 6 months before painting. Wash to remove any oil, grease or other surface contamination using a water-based cleaner-degreaser. Do not use hydrocarbon solvents for cleaning. Remove all corrosion with sandpaper, steel wool or other abrading method.

Vinyl/Fiberglass/Previously Painted Surfaces:

Thoroughly clean the surface and allow to dry. All dust and loose peeling paint should be removed.

Clean Mildew from the Surface:

Mildew is a fungus that looks like dirt but won't wash off. Mildew must be removed before painting, or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover following manufacturer's safety instructions.



Cabinet, Door & Trim Primer

Interior/Exterior Latex

CLEANUP INFORMATION

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARRANTY

SATISFACTION GUARANTEE - LIMITED WARRANTY: If this product, when applied and maintained according to product application and maintenance instructions to a properly prepared surface, fails to perform to your complete satisfaction, manufacturer shall, upon presentation of proof-of-purchase to the store where the product was purchased, either replace an equivalent quantity of product free of charge or refund the original purchase price. This warranty shall not apply to any defect or damage resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate or improper application or maintenance of the product. This is your sole remedy under this warranty. **THIS WARRANTY EXCLUDES (1) LABOR OR COSTS ASSOCIATED WITH LABOR FOR THE APPLICATION OR REMOVAL OF ANY PRODUCT, AND (2) ANY INCIDENTAL, CONSEQUENTIAL, SPECIAL, EXEMPLARY, PUNITIVE, OR INDIRECT DAMAGES. ALL IMPLIED WARRANTIES, INCLUDING OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, SHALL HAVE THE SAME DURATION AS THE ABOVE EXPRESS WARRANTY.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state. Sherwin-Williams.com/1-800-4-SHERWIN

CAUTIONS

CONTAINS CRYSTALLINE SILICA

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

FIRST AID:

In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.

Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure.

WARNING:

This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Sheet.