



LINE-UP[®] WATER-BASED ATHLETIC FIELD STRIPING PAINT

K5213

Krylon[®] Industrial Line-Up[®] Athletic Field Striping Paints provide a professional-looking job quickly and easily. These highly pigmented water-based paints produce sharp, durable stripes in one pass.

COLORS

Can be diluted up to 1:1 water to paint

CONCENTRATES

Can be diluted up to 3:1 water to paint

- ✓ Highly pigmented formulas
- ✓ Won't harm grass or stunt its growth
- ✓ Won't stain uniforms
- ✓ Safe alternative to lime
- ✓ Fast drying

INDUSTRIAL USE ONLY!

AS OF 01/01/2017 COMPLIES WITH:

- | | |
|--|---|
| <input checked="" type="checkbox"/> OTC | <input checked="" type="checkbox"/> CARB |
| <input checked="" type="checkbox"/> EC | <input checked="" type="checkbox"/> LADCO |
| <input checked="" type="checkbox"/> SCAQMD | <input checked="" type="checkbox"/> UTAH |

krylonindustrial.com

1-800-247-3266

Revised January 2017

SURFACE PREPARATION

Surface should be clean and dry. Grass should be cut to a low level on the first application to permit the paint to reach the ground. Make sure the ground is dry before painting. Muddy areas must be filled with sand to control runoff. Other athletic surfaces should have all debris removed before painting and they should be allowed to dry prior to application.

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority. Remove all surface contamination by washing with a Concentrated Cleaner or other appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or checked paint to a sound surface. Sand glossy surfaces dull.

APPLICATION

Stir paint thoroughly before use. Dry time will be extended when applied below 50 F or in high humidity. (Protect from freezing). Can be thinned with water up to 1 quart per gallon. For brush application, no reduction is necessary.

Brush: Use a nylon/polyester brush. For roller application, no reduction is necessary.

Roller: Use appropriate synthetic nap size roller cover. For airless spray reduce with up to 1 pint of water per gallon if necessary. Use .017 - .021 Tip, 80 mesh filter and 2,000 psi fluid pressure.

Spray: For conventional spray reduce with up to pint water per gallon if necessary. Use a 704 cap, E Tip, 40 psi atomization pressure and 15-20 psi fluid pressure.

TECHNICAL DATA

Finish:	Flat
Sizes:	5 gal
Drying Time:	(@77 F & 50% R.H.) To Touch: 30 minutes To Recoat: 1-2 hours
Rec. Spread Rate:	(calculated) 15 gals. Per mile of standard 4" strip or 350 lineal ft. of standard 4" strip per gal. (700 – 1,000 lineal ft. per gal.)
Volume Solids:	32% ± 2%, may vary by color
Weight Solids:	49% ± 2%, may vary by color
Weight per Gallon:	11.5 lbs
Vehicle Type:	Modified Acrylic Latex
Flash Point:	499 F PM Closed Cup
VOC:	<97 g/L, 0.81 lb/gal
Clean Up:	Soap and Water

CAUTION

Thoroughly review product label and SDS for safety and cautions prior to using this product. Please direct any questions or comments to your local Krylon Industrial Representative.

Note: The information, rating, and opinions stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application which are not known or under our control, Krylon Products Group cannot make any warranties as to the end result. Please direct any questions or comments to 1-800-247-3266.



krylonindustrial.com
1-800-247-3266

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of Krylon Industrial. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Krylon Industrial dealer or representative to obtain the most recent Product Data Sheet.