SAFETY DATA SHEET

K000Z6842

Section 1. Identifi	cation
Product name	: KRYLON® Acrylic Waterborne DTM Gloss Deep Base 2
Product code	: K000Z6842
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of t	the substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: Krylon Products Group 101 Prospect Avenue NW Cleveland, OH 44115
Emergency telephone number of the company	: US/Canada: (800) 424-9300 Mexico: CHEMTREC Mexico 800-681-9531. Available 24 hours and 365 days per year
Product Information Telephone Number	: US/Canada: (800) 247-3266 Mexico: Not Available
Transportation Emergency Telephone Number	: US/Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year
Section 2. Hazard	s identification
OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 1.2% (oral), 1.2% (dermal), 1.2% (inhalation)
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	: May cause an allergic skin reaction. Suspected of causing cancer.
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid breathing vapor. Contaminated work clothing must not be allowed out of the workplace.
Response	: IF exposed or concerned: Get medical advice or attention. Wash contaminated clothing

IF exposed or concerned: Get medical advice or attention. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention.

Storage : Store locked up.

Date of issue/Dat	te of revision	: 4/19/2024	Date of previous issue	: 2/4/2024	Version : 19.01	1/12
K000Z6842	KRYLON® Acrylic Deep Base 2	Waterborne DTM	Gloss		SHW-85-NA-GHS-US	

Section 2. Hazards identification

Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY.
	This product contains a TSCA regulated chemical. See Section 15 of the US SDS for details.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Titanium Dioxide	≤10	13463-67-7
Polypropylene glycol alkyl phenyl ether	≤3	9064-13-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first	aid measures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Date of issue/Date	of revision	: 4/19/2024	Date of previous issue	: 2/4/2024	Version : 19.	.01 2/12
K000Z6842	KRYLON® Acrylic Wa Deep Base 2	aterborne DTM (Gloss		SHW-85-NA-G	HS-US

Section 4. First aid measures

Potential acute health effe	<u>cts</u>			
Eye contact	: No known significant effects or critical hazards.			
Inhalation	: No known significant effects or critical hazards.			
Skin contact	: May cause an allergic skin reaction.			
Ingestion	: No known significant effects or critical hazards.			
Over-exposure signs/symp	<u>otoms</u>			
Eye contact	: No specific data.			
Inhalation	: No specific data.			
Skin contact	: Adverse symptoms may include the following: irritation redness			
Ingestion	: No specific data.			
Indication of immediate me	dical attention and special treatment needed, if necessary			
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. 			
Specific treatments	: No specific treatment.			
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.			

See toxicological information (Section 11)

Section 5. Fire-fighting measures

-	-
Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protect	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	This product contains a TSCA regulated chemical. See Section 15 of the US SDS for details.
		Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	nt	ainment and cleaning up
Small spill	1	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

disposal contractor.

place in an appropriate waste disposal container. Dispose of via a licensed waste

Section 7. Handling and storage

Deep Base 2

Precautions for safe handling	3			
Protective measures	history of sl this product handle until or on skin o use the ma wear appro made from	kin sensitization problems t is used. Avoid exposure I all safety precautions ha or clothing. Do not ingest terial presents a respirato priate respirator. Keep ir	s should not be emple - obtain special ins we been read and ur . Avoid breathing va bry hazard, use only the original contain ept tightly closed whe	ection 8). Persons with a oyed in any process in which tructions before use. Do not nderstood. Do not get in eyes por or mist. If during normal with adequate ventilation or er or an approved alternative en not in use. Empty containers use container.
Advice on general occupational hygiene	handled, sto drinking an		rkers should wash h taminated clothing a	ands and face before eating, nd protective equipment before
Conditions for safe storage, including any incompatibilities	direct sunlig (see Sectio and sealed resealed ar Use approp	ght in a dry, cool and well in 10) and food and drink until ready for use. Cont nd kept upright to prevent	-ventilated area, awa Store locked up. K ainers that have bee leakage. Do not sto d environmental con	nal container protected from ay from incompatible materials ieep container tightly closed n opened must be carefully ore in unlabeled containers. tamination. See Section 10 for
Date of issue/Date of revision	: 4/19/2024	Date of previous issue	: 2/4/2024	Version : 19.01 4/12
K000Z6842 KRYLON® Acrylic	Waterborne DTM	Gloss		SHW-85-NA-GHS-US

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Titanium Dioxide	13463-67-7	OSHA PEL (United States, 5/2018). TWA: 15 mg/m ³ 8 hours. Form: Total dust ACGIH TLV (United States, 1/2023). TWA: 2.5 mg/m ³ 8 hours. Form: respirable fraction, finescale particles
Polypropylene glycol alkyl phenyl ether	9064-13-5	None.

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
None.		

Occupational exposure limits (Mexico)

	CAS #	Exposure limits
None.		

Biological exposure indices (United States)

No exposure indices known.

Biological exposure indices (Canada)

No exposure indices known.

Biological exposure indices (Mexico)

No exposure indices known.

Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	This product contains a TSCA regulated chemical. See Section 15 of the US SDS for details.
		Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measur	<u>es</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection		

Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	: Liqu	uid.		
Color	: Wh	ite.		
Odor	: Not	available.		
Odor threshold	: Not	available.		
рН	: 9			
Melting point/freezing point	: Not	available.		
Boiling point, initial boiling point, and boiling range	: 100)°C (212°F)		
Flash point	: Clo	sed cup: Not applicable.		
Evaporation rate	: 0.09	9 (butyl acetate = 1)		
Flammability	: Not	: Not available.		
Lower and upper explosion limit/flammability limit	: Not available.			
Vapor pressure	: 2.3 kPa (17.5 mm Hg)			
Relative vapor density	: 1 [A	Air = 1]		
Relative density	: 1.08	8		
Solubility(ies)	:			
Media		Result		
cold water		Partially soluble		
Partition coefficient: n- octanol/water	: Not	applicable.		
Auto-ignition temperature	• Not	available		

Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)
Molecular weight	: Not applicable.
Heat of combustion	: 0.564 kJ/g

Date of issue/Date	of revision	: 4/19/2024	Date of previous issue	: 2/4/2024	Version : 19.01	6/12
K000Z6842	KRYLON® Acrylic Wa Deep Base 2	terborne DTM (Gloss		SHW-85-NA-GHS-US	

Section 10. Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients.
: The product is stable.
: Under normal conditions of storage and use, hazardous reactions will not occur.
: No specific data.
: No specific data.
: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300	-
				ug l	

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure) Not available.

Aspiration hazard

Not available.

Section 11. Toxicological information

Information on the likely routes of exposure	: Not available.
Potential acute health effe	<u>cts</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the p	hysical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
Delayed and immediate eff	fects and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health ef	ifects
Not available.	
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
N	

Numerical measures of toxicity Acute toxicity estimates Not available.

: 2/4/2024

Section 12. Ecological information

<u>Toxicity</u>

Product/ingredient name	Result	Species	Exposure
Titanium Dioxide	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods: This product contains a TSCA regulated chemical. See Section 15 of the US SDS
for details.
The generation of waste should be avoided or minimized wherever possible. Disposal
of this product, solutions and any by-products should at all times comply with the
requirements of environmental protection and waste disposal legislation and any
regional local authority requirements. Dispose of surplus and non-recyclable products
via a licensed waste disposal contractor. Waste should not be disposed of untreated to
the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Waste packaging should be recycled. Incineration or landfill should only be considered
when recycling is not feasible. This material and its containers that have not been
cleaned or rinsed out. Empty containers or liners may retain some product residues.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains
and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Date of issue/Date of rev 00026842 KRYI	vision : 4/19/2 _ON® Acrylic Waterborne I		issue : 2/4/2024		<mark>sion</mark> : 19.01 9/ W-85-NA-GHS-US

-	-	-	-
consider container sizes. T mode of transport (sea, air suitably for that mode of tra to shipment, and complian of the person offering the dangerous goods must be	he presence of a shi , etc.), does not indic ansport. All packaging ce with the applicable product for transport. trained on all of the r	pping description for ate that the product g must be reviewed f regulations is the so People loading and u isks deriving from the	a particular s packaged for suitability prior ble responsibility unloading
Not available.			
	: Not available.		
	consider container sizes. T mode of transport (sea, air suitably for that mode of tra to shipment, and complian of the person offering the p dangerous goods must be	consider container sizes. The presence of a shi mode of transport (sea, air, etc.), does not indic suitably for that mode of transport. All packaging to shipment, and compliance with the applicable of the person offering the product for transport. dangerous goods must be trained on all of the r and on all actions in case of emergency situatio	consider container sizes. The presence of a shipping description for mode of transport (sea, air, etc.), does not indicate that the product is suitably for that mode of transport. All packaging must be reviewed f to shipment, and compliance with the applicable regulations is the se of the person offering the product for transport. People loading and u dangerous goods must be trained on all of the risks deriving from the and on all actions in case of emergency situations.

U.S. Federal regulations : TSCA 5(a)2 proposed significant new use rules: reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1); 2-Methyl-4-isothiazolin-3-one TSCA 5(a)2 final significant new use rules: Sodium Nitrite List name Chemical name Notes United States - TSCA 5(a) Sodium Nitrite 40 CFR 721.4740 2 - Final significant new use rules **SARA 313**

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet, where applicable.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists

: Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined. Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Justification	
 culation method	

<u>History</u>	
Date of printing	: 4/19/2024
Date of issue/Date of revision	: 4/19/2024
Date of previous issue	: 2/4/2024
Version	: 19.01
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs

Date of issue/Date	of revision	: 4/19/2024	Date of previous issue	: 2/4/2024	Version	:19.01	11/12
K000Z6842	KRYLON® Acrylic Wate Deep Base 2	erborne DTM Gl	oss		SHW-85-	NA-GHS-US	

Section 16. Other information

obtained from any other source.