



# ACRYLI-QUIK™

Krylon® Industrial Acryli-Quik™ is specifically formulated for industrial maintenance and touch-up applications. Performance is exceptional, and the broad selection includes interior/exterior acrylic lacquers, primers and specialty paints. Acryli-Quik™ provides a high-solids, fast-drying formula. No Runs, No Drips, No Errors!™

- ✓ No recoat window, recoat anytime
- ✓ Dries to a touch in 12 minutes
- ✓ Hard, protective, durable finish
- ✓ High-Gloss finish

**INDUSTRIAL USE ONLY!**

[krylonindustrial.com](http://krylonindustrial.com)  
1-800-247-3266

## RECOMMENDED USES

- Metal
- Wood
- Motors
- Tools
- Pipelines
- Conduit
- Ducts
- Drums
- Cabinets
- Furniture
- Color coding steel and lumber

## SURFACE PREPARATION

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** For more information, contact your local health authority. Remove dirt, grease, wax, moisture, rust and loose paint from surface. Scuff-sand rusted, glossy or hard surfaces. Sand metal, wood or plastic with #220 grit sandpaper. Use a primer on new wood and on new or rusted metal to smooth uneven surfaces, or when dramatically changing color. For best results, use with Krylon Industrial White (K01315), Gray (K01318) or Ruddy Brown (K01317) Primers. Allow primer to dry for at least 30 minutes before lightly sanding and top coating with Krylon Industrial Acryli-Quik™ paints.

## CLEAN-UP

Use lacquer thinner to remove. Clean spray valve immediately after use by turning can upside-down and spraying until only clear gas comes out. Dispose of in accordance with local, state or federal regulations.

## TECHNICAL DATA

<b>Vehicle</b>	Acrylic Lacquer
<b>Finish</b>	Flat (Primer), High (Gloss)
<b>Flash Point</b>	-20°
<b>Weight/Gallon</b>	6.07 lb/gal
<b>VOC/MIR</b>	1.29
<b>Spread Rate</b>	15-20 sq. feet
<b>Shelf Life</b>	60 months
<b>Drying Time</b>	To Touch: 12 minutes To Recoat: Anytime To Handle: 30 minutes
<b>Dry Heat Resistance</b>	<150°
<b>Gas Resistance</b>	Film Softens after 15 mins
<b>Oil Resistance</b>	Film Softens after 15 mins
<b>Clean Up</b>	Lacquer Thinner
<b>Net Weight/Can Size</b>	12 oz. / 16 oz.

## APPLICATION

### APPLICATION CONDITIONS

Use at 70°F for best operation. Shake can until ball rattles for 1 minute. Test spray on inconspicuous area or scrap piece to check compatibility. Hold container upright 10-12 inches from surface. Do not apply with a continuous spray. To avoid runs apply several thin coats. Dries to touch in 12 minutes. Can be recoated at anytime.

## CAUTIONS

**FOR INDUSTRIAL USE ONLY.** Thoroughly review product label and SDS for safety and cautions prior to using this product. Please direct any questions or comments to your local Krylon Industrial Representative.

**Note:** The information, rating, and opinions stated here pertain to the material currently offered and represent the results of tests believed to be reliable. However, due to variations in customer handling and methods of application which are not known or under our control, Krylon Products Group cannot make any warranties as to the end result. Please direct any questions or comments to 1-800-247-3266.

The information and recommendations set forth in the Product Data Sheet are based upon tests conducted by or on behalf of Krylon® Industrial. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Krylon® Industrial dealer or representative to obtain the most recent Product Data Sheet.