



# KRYLON® FUSION ALL-IN-ONE™

Gloss, Flat, Satin, Matte

| PRODUCT DESCRIPTION   | APPLICATION  | CAUTIONS  |
|---|--|---|
| <p><b>FUSION ALL-IN-ONE® provides 5X stronger adhesion and bonds to tough surfaces, offers a no sand, no prime application with maximum rust protection and ultimate strength.</b></p>  | <p>Shake can until ball inside begins to rattle, then shake for an additional 2 minutes. Test spray in an inconspicuous area for compatibility. Hold can 8" to 10" from surface. Spray in a sweeping motion, side-to-side, with slight overlap. Surfaces can be sprayed at any angle. Apply multiple thin coats. Wait 1 minute between each coat.</p>  | <p><b>CONTAINS ACETONE, PROPANE, N-BUTYL ACETATE, LT. ALIPHATIC HYDROCARBON SOLVENT, BUTANE, ETHYL 3-ETHOXYPROPIONATE, XYLENE, TITANIUM DIOXIDE, ETHYLBENZENE. DANGER! EXTREMELY FLAMMABLE.</b> Keep away from heat, sparks and open flame. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are gone. <b>DO NOT SMOKE</b> — Extinguish all flames, pilot lights and heaters — Turn off stoves, electric tools and appliances, and any other sources of ignition. <b>CONTENTS UNDER PRESSURE.</b> Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120°F. Keep upright in a cool, dry place. Do not discard empty can in trash compactor. <b>VAPOR HARMFUL.</b> Use with adequate ventilation. Avoid continuous breathing of vapor and spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. <b>FIRST AID:</b> In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. <b>DELAYED EFFECTS FROM LONG-TERM OVEREXPOSURE.</b> Contains solvents that can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. <b>WARNING:</b> This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. <b>DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. CONFORMS TO ASTM D-4236.</b> Contact a physician for more health information. <b>DANGER:</b> Rags, steel wool, other waste soaked with this product and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.</p> |
| PAINTING CONDITIONS   | CHARACTERISTICS  |   |
| <p>Spray outdoors or in a well-ventilated area. Protect surrounding areas. Best results when temperature is 55°F (12°C) to 75°F (24°C) and humidity is below 60%. <b>NOTE:</b> Applying outside of this range may impact finish.</p>  | <p><b>Available Sheens:</b> Gloss, Flat, Satin, Matte</p> <p><b>Coverage:</b> Estimated 25 Square Feet</p> <p><b>Drying Time, @ 77°F, 50% RH:</b><br/><i>Drying time and recoat times are temperature, humidity, and film thickness dependent.</i></p> <p><b>Touch:</b> 20 Minutes<br/><b>To Handle:</b> 1 Hour</p> <p><b>Recoat:</b> Within 6 Hours; After 24 Hours</p> <p><b>Substrates:</b> All metals, wood, plastics, laminates, masonry, concrete, wicker, ceramic, glass, plaster and hard-to-adhere surfaces.</p> <p><b>Vehicle Type:</b> Modified Alkyd</p> |   |
| SURFACE PREPARATION   |  |   |
| <p><b>WARNING!</b> If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to <a href="http://www.epa.gov/lead">www.epa.gov/lead</a>. Surface should be clean, dull and dry. Remove loose rust and paint with wire brush or sandpaper.</p> |  |   |
|   | <p><b>Finishes:</b> Gloss, Flat, Satin, Matte</p> <p><b>Net Wt.:</b> 12 oz. / 340g</p> <p><b>Volume Solids:</b> 5-14%</p> <p><b>Weight Solids:</b> 7 - 25%</p>   | PERFORMANCE TESTING   |
|   |  | <p>Technical data furnished herein is accurate and true to the best of our knowledge. However, no guarantee of accuracy is expressed or implied. We assume no responsibility or liability as a result of purchase, coverage, application or injuries resulting in misuse. To contact us call 1-800-247-3268 or <a href="mailto:ask@krylon.com">ask@krylon.com</a>.</p>  |