



KRYLON® SPECIALTY METALLIC PAINT
 Product Numbers: 1701,1708, 1709

PRODUCT DESCRIPTION	APPLICATION	CAUTIONS
<p>Krylon® Specialty Metallic Paint provides a bright, polished metallic finish on a variety of projects. Not for use on craft foam. Ideal for furniture, decor & crafts. For use on wood, metal, wicker, glass, plaster & ceramic.</p>	<p>Shake until ball inside begins to rattle, then shake for an additional 2 minutes. Test spray in an inconspicuous area for compatibility. Hold can 10" to 12" from surface. Spray in sweeping motion side-to-side, with slight overlap. Apply multiple thin coats to avoid runs and drips. Dries to touch in 15 minutes or less. Handle after 1 hour. Recoat anytime. Clear valve by holding can upside down and spraying until only clear gas comes out. If spray button becomes clogged, wear eye protection, wipe off the button opening with lacquer thinner - DO NOT stick pin in dial opening. Clean overspray with paint or lacquer thinner, following solvent manufacturer's instructions. Wash hands after using. Recycle empty can and cap per local regulations.</p>	<p>CONTAINS ETHYBENZENE, ACETONE, PROPANE AND BUTANE. DANGER! EXTREMELY FLAMMABLE. Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are gone. DO NOT SMOKE - Extinguish all flames, pilot lights and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. CONTENTS UNDER PRESSURE. Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120°F. Keep upright in a cool, dry place. Do not discard empty can in trash compactor. VAPOR HARMFUL. Use with adequate ventilation. Avoid continuous breathing of vapor and spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY, KEEP OUT OF THE REACH OF CHILDREN. CONFORMS TO ASTM D-4236. Contact a physician for more health information.</p>
<p>PAINTING CONDITIONS</p> <p>Spray outdoors or in a well-ventilated area. Protect surrounding areas. Best results when temperature is 55°F (12°C) to 75°F (24°C) and humidity is below 60%.NOTE: Applying outside of this range may impact finish.</p>	<p>Colors: 6 colors</p> <p>Coverage: Up to 15 square feet</p> <p>Drying Time, @ 77 °F, 50% RH: <i>Drying time and recoat times are temperature, humidity and film thickness dependent.</i></p> <p>Touch: 15 minutes or less</p> <p>To Handle: 1 hours</p> <p>Recoat: Anytime</p> <p>Vehicle Type: Acrylic</p>	
<p>SURFACE PREPARATION</p> <p>WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log onto www.epa.gov/lead. Surface should be clean, dull & dry. Remove loose paint, rust dirt, grease and oil. To improve adhesion, sand glossy or rough surfaces until smooth.</p>	<p>Finish: Metallic</p> <p>Volume Solids: 4 - 11.50%</p> <p>Weight Solids: 8 - 20.5%</p>	<p>PERFORMANCE TESTING</p> <p>Technical data furnished herein is accurate and true to the best of our knowledge. However, no guarantee of accuracy is expressed or implied. We assume no responsibility or liability as a result of purchase, coverage, application or injuries resulting in misuse. To contact us call 1-800-247-3268 or ask@krylon.com.</p>