ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

51 00 [2594]

Date of Preparation Sep 15, 2024

PRODUCT NUMBER

C14512 PRODUCT NAME KRYSTAL® High Solids Conversion Varnish, Dull MANUFACTURER'S NAME M. L. CAMPBELL

101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED and rely on information provided to us by our raw material suppliers. Our suppliers often provide an estimated value or range less than a certain upper limit. We calculate MAXIMUM THEORETICAL VALUES using defined values, if provided, or the upper limit reported by our supplier. Additionally, the suppliers' information may include amounts present in the product as unintentional byproducts or impurities. Variations may occur in individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

C14512 = | Acute | Chronic | Fire |

Product Weight	Spe	ecific Gravity		FL/	ASH POINT	
8.20 lb/gal		0.99			60 °F PMCC	
Volatile Ingredients						
Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethylbenzene 100-41-4	Ν	Υ	Y	Y	0.3	0.4
Xylene 1330-20-7	Ν	Y	Υ	Y	2	2
Ethanol 64-17-5	Ν	Ν	N	N	7	9
1-Butanol 71-36-3	N	Y	Y	N	5	6
1-Methoxy-2-propanol 107-98-2	N	Ν	N	N	3	3
2-Methyl-1-propanol 78-83-1	N	Y	N	N	2	3
Methyl n-Amyl Ketone 110-43-0	N	N	N	N	3	4
Ethyl Acetate 141-78-6	N	Y	N	N	2	2
dimethyl carbonate 616-38-6	N	N	N	N	1	1
n-Butyl Acetate 123-86-4	Ν	Y	N	N	30	33

Volatile Organic Compounds - U.S. EPA / Canada

	C14512	
	LB/Gal	g/L
Coating Density	8.20	982
	By wt	By vol
Total Volatiles	56.9%	65.4%
Federally exempt solvents		
Water	0.0%	0.0%
Dimethyl carbonate	1.4%	1.3%
Organic Volatiles	55.6%	64.1%
Percent Non-Volatile	43.1%	34.6%
VOC Content	LB/Gal	g/L
Total	4.55	545
Less exempt solvents	4.61	552
Of solids	13.14	1575
Of solids	1.29 lb/lb	1.29 kg/kg
	By wt	
By wt LVP-VOC	55.3%	

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) 0.93

Volatile Organic Compounds - California

	C14512		
	LB/Gal	g/L	
Coating Density	8.20	982	
	By wt	By vol	
Total Volatiles	56.9%	65.4%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	56.9%	65.4%	
Percent Non-Volatile	43.1%	34.6%	
VOC Content	LB/Gal	g/L	
Total	4.66	559	
Less exempt solvents	4.66	559	
Of solids	13.47	1614	
Of solids	1.32 lb/lb	1.32 kg/kg	
	By wt		
By wt LVP-VOC	56.7%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) 0.86

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	C14512		
	LB/Gal	g/L	
Coating Density	8.20	982	
	By wt	By vol	
Total Volatiles	56.9%	65.4%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	56.9%	65.4%	
Percent Non-Volatile	43.1%	34.6%	
VOC Content	LB/Gal	g/L	
Total	4.66	559	
Less exempt solvents	4.66	559	
Of solids	13.47	1614	
Of solids	1.32 lb/lb	1.32 kg/kg	

Volatile Organic Compounds - EU Directive 2004/42/EC

	C14512	
	By wt	By vol
Total Volatiles	56.9%	65.4%
VOC Content	LB/Gal	g/L
Total	4.66	559

Volatile Organic Compounds - EU Directive 2010/75/EU

	C14512	
	By wt	By vol
Total Volatiles	56.9%	65.4%
VOC Content	LB/Gal	g/L
Total	4.66	559

Volatile Organic Compounds - Mexico

	C14512		
	LB/Gal	g/L	
Coating Density	8.20	982	
	By wt	By vol	
Total Volatiles	56.9%	65.4%	
Exempt solvents			
Water	0.0%	0.0%	
Organic Volatiles	56.9%	65.4%	
Percent Non-Volatile	43.1%	34.6%	
VOC Content	LB/Gal	g/L	
Total	4.66	559	
Less exempt solvents	4.66	559	
Of solids	13.47	1614	
Of solids	1.32 lb/lb	1.32 kg/kg	

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	C14512		
	LB/Gal	kg/L	
Volatile HAPS	0.16	0.019	
Of solids	0.47	0.056	
Of solids	0.04 lb/lb	0.04 kg/kg	

Air Quality Data

Density of Organic Solvent Blend 7.15 lb/gal Photochemically Reactive No

Waste Disposal

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

The addition of any material to this product can change the composition, hazards and risks of the product and may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.