

# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : FBS6-E0001 PE/P BT 65GL BLACK RAL 9005 RR33

**Product code** : 83835

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Material uses** : Paint or paint related material.

: Industrial use only.

### 1.3 Details of the supplier of the safety data sheet

Inver S.p.A. con Unico Socio

Via di Corticella 205 - Bologna

Phone: +39 051 6380411

**e-mail address of person responsible for this SDS** : minerbio.regulatory@sherwin.com

### 1.4 Emergency telephone number

#### National advisory body/Poison Centre

**Telephone number** : 111 (general public) /0344 892 111 (Medical professional (NHS) only)

#### Supplier

**Telephone number** : +39 051 6606811

**Hours of operation** : 08:30 - 17:30

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Signal word** : No signal word.

**Hazard statements** : No known significant effects or critical hazards.

#### Precautionary statements

**Prevention** : Not applicable.

**Response** : Not applicable.

**Storage** : Not applicable.

**Disposal** : Not applicable.

**Supplemental label elements** : Contains Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine.  
May produce an allergic reaction.

Safety data sheet available on request. FOR INDUSTRIAL USE ONLY

#### Special packaging requirements

**SECTION 2: Hazards identification**

Not applicable.

**2.3 Other hazards**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**Other hazards which do not result in classification** : May form combustible dust concentrations in air.

**SECTION 3: Composition/information on ingredients****3.2 Mixture**

:

| Product/ingredient name                                                | Identifiers                                                       | %         | Classification                                                                                                                    | Specific Conc. Limits, M-factors and ATEs | Type |
|------------------------------------------------------------------------|-------------------------------------------------------------------|-----------|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|------|
| Barium Sulfate                                                         | EC: 231-784-4<br>CAS: 7727-43-7                                   | ≥10 - ≤25 | Not classified.                                                                                                                   | -                                         | [2]  |
| Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine | REACH #:<br>01-2119979085-27<br>EC: 309-629-8<br>CAS: 100545-48-0 | ≤0.3      | Skin Sens. 1B, H317<br>Aquatic Chronic 3, H412<br><br><b>See Section 16 for the full text of the H statements declared above.</b> | -                                         | [1]  |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

**Type**

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

**4.2 Most important symptoms and effects, both acute and delayed**

**SECTION 4: First aid measures**

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localised skin irritation in folds of the skin or under tight clothing.

**4.3 Indication of any immediate medical attention and special treatment needed**

**Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

See toxicological information (Section 11)

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

**Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub> blanket, water spray or mist.

**Unsuitable extinguishing media** : Do not use water jet.  
Do not use inert gas under high pressure (e.g. CO<sub>2</sub>).

**5.2 Special hazards arising from the substance or mixture**

**Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

**Hazardous combustion products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

**5.3 Advice for firefighters**

**Special protective actions for fire-fighters** : Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.

**Special protective equipment for fire-fighters** : Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel** : Exclude sources of ignition and ventilate the area. Avoid breathing dust. Refer to protective measures listed in sections 7 and 8.

Keep unnecessary and unprotected personnel from entering.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**6.2 Environmental precautions**

: Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

**6.3 Methods and material for containment and cleaning up**

: Contain and collect spillage with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Do not use a dry brush as dust clouds or static can be created.

## SECTION 6: Accidental release measures

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**Advice should be taken from a competent occupational health practitioner on the assessment of employees with skin or respiratory complaints before the individual is exposed to the uncured product.**

- 7.1 Precautions for safe handling** : Precautions should be taken to prevent the formation of dusts in concentrations above flammable, explosive or occupational exposure limits.  
Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources.  
Mixture may charge electrostatically: always use earthing leads when transferring from one container to another.  
Operators should wear antistatic footwear and clothing and floors should be of the conducting type.  
Keep away from heat, sparks and flame.  
Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.  
Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.  
Put on appropriate personal protective equipment (see Section 8).  
Always keep in containers made from the same material as the original one.  
Comply with the health and safety at work laws.  
Do not allow to enter drains or watercourses.

- 7.2 Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations.  
**Additional information on storage conditions**  
Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight.  
Keep container tightly closed.  
Keep away from sources of ignition. No smoking. Prevent unauthorised access.  
Containers that have been opened must be carefully resealed and kept upright to prevent leakage.  
Contaminated absorbent material may pose the same hazard as the spilt product.

### 7.3 Specific end use(s)

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

Good housekeeping standards, regular safe removal of waste materials and regular maintenance of spray booth filters will minimise the risks of spontaneous combustion and other fire hazards.

**Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations.**

**SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**8.1 Control parameters****Occupational exposure limits**

| Product/ingredient name | Exposure limit values                                                                                                                                                      |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Barium Sulfate          | <b>EH40/2005 WELs (United Kingdom (UK), 1/2020).</b><br>TWA: 4 mg/m <sup>3</sup> 8 hours. Form: respirable dust<br>TWA: 10 mg/m <sup>3</sup> 8 hours. Form: inhalable dust |

**Biological exposure indices**

No exposure indices known.

- Recommended monitoring procedures** :
- Reference should be made to monitoring standards, such as the following:  
European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
  - Regular monitoring of all work areas should be carried out at all times, including areas that may not be equally ventilated.

**DNELs/DMELs**

| Product/ingredient name                                                | Type | Exposure             | Value                   | Population | Effects  |
|------------------------------------------------------------------------|------|----------------------|-------------------------|------------|----------|
| Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine | DNEL | Long term Inhalation | 0.308 mg/m <sup>3</sup> | Workers    | Systemic |

**PNECs**

No PNECs available

**8.2 Exposure controls**

- Appropriate engineering controls** :
- Avoid breathing dust. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain exposure to dusts below the OEL, suitable respiratory protection must be worn.
  - Users are advised to consider national Occupational Exposure Limits or other equivalent values.

**Individual protection measures**

- Hygiene measures** :
- Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** :
- Safety eyewear should be used when there is a likelihood of exposure.
- Skin protection**
- Hand protection** :
- Wear suitable gloves tested to EN374.
- Gloves** :
- Gloves for short term exposure or repeated or prolonged exposure (480 min): Wear any rubber glove such as Nitrile or Neoprene gloves.  
Due to many conditions (e.g. temperature, abrasion) the practical usage of a chemical protective glove in practice may be much shorter than the permeation time determined through testing.

**SECTION 8: Exposure controls/personal protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.  
The breakthrough time must be greater than the end use time of the product.  
The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.  
Gloves should be replaced regularly and if there is any sign of damage to the glove material.  
Always ensure that gloves are free from defects and that they are stored and used correctly.  
The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.  
Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.  
The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

- Body protection** : Personnel should wear protective clothing. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at the neck and wrists through contact with the powder are avoided.
- : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Recommended: particulate filter, P2-P3 (EN14387). Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Environmental exposure controls** : Do not allow to enter drains or watercourses.

**Before use of this material please refer to the Exposure Scenario(s) if attached for the specific end use, control measures and additional PPE considerations. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.**

**SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

**9.1 Information on basic physical and chemical properties****Appearance**

- Physical state** : Solid.
- Colour** : Black.
- Odour** : None
- Odour threshold** : Not applicable.
- pH** : Not relevant/applicable due to nature of the product.  
insoluble in water.
- Melting point/freezing point** : 60 to 120°C
- Initial boiling point and boiling range** : Not relevant/applicable due to nature of the product.
- Flash point** : Closed cup: Not applicable.
- Evaporation rate** : Not relevant/applicable due to nature of the product.
- Flammability** : Not relevant/applicable due to nature of the product.

**SECTION 9: Physical and chemical properties**

**Lower and upper explosion limit** : Not relevant/applicable due to nature of the product.

**Vapour pressure** : Not relevant/applicable due to nature of the product.

**Relative vapour density** : Not applicable.

**Relative density** : 1.51

**Solubility(ies)** :

| Media      | Result      |
|------------|-------------|
| cold water | Not soluble |

**Partition coefficient: n-octanol/ water** : Not relevant/applicable due to nature of the product.

**Auto-ignition temperature** : Not relevant/applicable due to nature of the product.

**Decomposition temperature** : Not relevant/applicable due to nature of the product.

**Viscosity** : Kinematic (40°C): >20.5 mm<sup>2</sup>/s

**Explosive properties** : Under normal conditions of storage and use, hazardous reactions will not occur.

**Oxidising properties** : Under normal conditions of storage and use, hazardous reactions will not occur.

**Particle characteristics**

**Median particle size** : Not relevant/applicable due to nature of the product.

**9.2 Other information**

**Heat of combustion** : 1.573 kJ/g

**SECTION 10: Stability and reactivity**

**10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : When exposed to high temperatures may produce hazardous decomposition products.

**10.5 Incompatible materials** : Not applicable.

**10.6 Hazardous decomposition products** : Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

**Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.**

**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

There are no data available on the mixture itself. Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. Coating powders can cause localised skin irritation in folds of the skin or under tight clothing.

**Acute toxicity**

No data available

**SECTION 11: Toxicological information****Acute toxicity estimates**

No data available

**Irritation/Corrosion**

No data available

**Conclusion/Summary** : Not available.**Sensitisation**

No data available

**Conclusion/Summary** : Not available.**Mutagenicity**

No data available

**Carcinogenicity**

No data available

**Reproductive toxicity**

No data available

**Teratogenicity**

No data available

**Specific target organ toxicity (single exposure)**

No data available

**Specific target organ toxicity (repeated exposure)**

No data available

**Aspiration hazard**

No data available

**11.2 Information on other hazards****11.2.1 Endocrine disrupting properties**

Not available.

**11.2.2 Other information**

Not available.

**SECTION 12: Ecological information****12.1 Toxicity**

There are no data available on the mixture itself.

Coating powder residues should not be allowed to enter drains or watercourses or be deposited where they could affect ground or surface waters.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]. See Sections 2 and 3 for details.

**12.2 Persistence and degradability**

| Product/ingredient name | Test | Result | Dose | Inoculum |
|-------------------------|------|--------|------|----------|
| No data available       |      |        |      |          |

**Conclusion/Summary** : Not available.

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| No data available       |                   |            |                  |

## SECTION 12: Ecological information

### 12.3 Bioaccumulative potential

| Product/ingredient name | LogP <sub>ow</sub> | BCF | Potential |
|-------------------------|--------------------|-----|-----------|
| No data available       |                    |     |           |

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### 12.6 Endocrine disrupting properties

Not available.

### 12.7 Other adverse effects

No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : No.

**European waste catalogue (EWC)** : 08 01 12 - waste paint and varnish other than those mentioned in 08 01 11

**Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

**European waste catalogue (EWC)** : Plastic articles 15 01 02 - metallic packaging 15 01 04 - mixed packaging 15 01 06.

**Special precautions** : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

|                                           | ADR/RID        | IMDG           | IATA           |
|-------------------------------------------|----------------|----------------|----------------|
| 14.1 UN number or ID number               | Not regulated. | Not regulated. | Not regulated. |
| 14.2 UN proper shipping name              | -              | -              | -              |
| 14.3 Transport Hazard Class(es)/ Label(s) | -              | -              | -              |
| 14.4 Packing group                        | -              | -              | -              |
| 14.5 Environmental hazards                | No.            | No.            | No.            |
| Additional information                    | -              | -              | -              |

*This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).*

14.6 Special precautions for user

: **Transport within user’s premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

: Not applicable.

*Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.*

SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU Regulation (EC) No. 1907/2006 (REACH)**

**Annex XIV - List of substances subject to authorisation**

**Annex XIV**

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles**

No listed substance

**Other EU regulations**

VOC content (2010/75/EU)

: 0 w/w

0 g/l

Explosive precursors

: Not applicable.

**Seveso Directive**

This product is not controlled under the Seveso Directive.

## SECTION 15: Regulatory information

### National regulations

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 DMEL = Derived Minimal Effect Level  
 DNEL = Derived No Effect Level  
 EUH statement = CLP-specific Hazard statement  
 PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number  
 vPvB = Very Persistent and Very Bioaccumulative  
 N/A = Not available

**Key literature references and sources for data** : Regulation (EC) No. 1272/2008 [CLP]  
 ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
 IATA = International Air Transport Association  
 IMDG = International Maritime Dangerous Goods  
 Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878  
 Directive 2012/18/EU, and relative amendments & additions  
 Directive 2008/98/EC, and relative amendments & additions  
 Directive 2009/161/EU, and relative amendments & additions  
 CEPE Guidelines

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

| Classification  | Justification |
|-----------------|---------------|
| Not classified. |               |

**Full text of abbreviated H statements** : H317 May cause an allergic skin reaction.  
 H412 Harmful to aquatic life with long lasting effects.

**Full text of classifications [CLP/GHS]** : Aquatic Chronic 3 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3  
 Skin Sens. 1B SKIN SENSITISATION - Category 1B

**Date of printing** : 31, May, 2024.

**Date of issue/ Date of revision** : 31, May, 2024

**Date of previous issue** : 11, Sep, 2023  
 : If there is no previous validation date please contact your supplier for more information.

**Version** : 5

### Notice to reader

*In accordance with Regulation (EC) 1907/2006, REACH Regulation, Articles 31, 37, any required hazard-related information on the use of substances received as downstream user will be sent forward. Consequently, the safety data sheets for some products will contain a SUMI - Safe Use of Mixture Information - attached to the safety data sheet.*

**Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II**

**FBS6-E0001 PE/P BT 65GL BLACK RAL 9005 RR33**

**83835**

## **SECTION 16: Other information**

**SUMI(s) will be added to the SDS for products if both the following conditions are met:**

- **The product is classified as hazardous for health**
- **The product contains one or more REACH-registered substances for which extended safety data sheets (exposure scenarios) have been provided**

**It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become make themselves aware of and understand the data contained in this SDS and any hazards that may be associated with the product. This information is provided in good faith and believed to be accurate as of the effective date mentioned herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can may change later the composition, hazards and risks of the product. Products shall should not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to, the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for the use of the product are not under the manufacturer's control of the manufacturer; the customer/buyer/user is responsible to for determine determining the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS, without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be held responsible for SDSs obtained from any other source.**

# SUMI

## Safe Use of Mixtures

### Information for end-users

**Title** : Industrial spray painting, walk-in booth

*This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet, Technical Data sheet and labels.*

## General description of the process covered

Paint application on industrial line with walk-in spray booth

## Operational conditions

**Place of use** : Indoor use

## Risk management measures (RMM)

| Contributing activity                                                       | Process category (ies) | Maximum duration  | Ventilation                            |                                       |
|-----------------------------------------------------------------------------|------------------------|-------------------|----------------------------------------|---------------------------------------|
|                                                                             |                        |                   | Type                                   | ach (air changes per hour)            |
| Preparation of material for application                                     | PROC05                 | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                |
| Loading of application equipment and handling of coated parts before curing | PROC08b                | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                |
| Industrial application of coatings and inks by spraying                     | PROC07                 | More than 4 hours | Local exhaust ventilation              | Refer to relevant technical standards |
| Film formation - force drying, stoving and other technologies               | PROC04                 | More than 4 hours | Local exhaust ventilation              | Refer to relevant technical standards |
| Cleaning                                                                    | PROC05                 | More than 4 hours | Local exhaust ventilation              | Refer to relevant technical standards |
| Application equipment cleaning outside booth                                | PROC05                 | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                |
| Waste management                                                            | PROC08b                | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                |

| Contributing activity                                                       | Process category (ies) | Respiratory                                                                                       | Eye                                     | Hands                                 |
|-----------------------------------------------------------------------------|------------------------|---------------------------------------------------------------------------------------------------|-----------------------------------------|---------------------------------------|
| Preparation of material for application                                     | PROC05                 | None                                                                                              | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Loading of application equipment and handling of coated parts before curing | PROC08b                | None                                                                                              | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Industrial application of coatings and inks by spraying                     | PROC07                 | Compressed-air breathing apparatus to EN 14594 with an assigned protection factor of at least 20. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Film formation - force drying, stoving and other technologies               | PROC04                 | None                                                                                              | None                                    | None                                  |
| Cleaning                                                                    | PROC05                 | None                                                                                              | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Application equipment                                                       | PROC05                 | None                                                                                              | Use eye protection                      | Wear suitable gloves                  |

**Date of issue/Date of revision** : 12, Sep, 2022

**Date of previous issue** : No previous validation **Version** 1

13/18

|                        |         |      |                                         |                                       |
|------------------------|---------|------|-----------------------------------------|---------------------------------------|
| cleaning outside booth |         |      | according to EN 166.                    | tested to EN374.                      |
| Waste management       | PROC08b | None | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |

See chapter 8 of this Safety Data Sheet for specifications.



## Disclaimer

The information in this Safe Use of Mixture Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product.

No liability is accepted for any damage, no matter of what kind, which is direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

# SUMI

## Safe Use of Mixtures

### Information for end-users

**Title** : Industrial spray painting, enclosed

*This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet, Technical Data sheet and labels.*

## General description of the process covered

Paint application on industrial line with fully-enclosed spraying

## Operational conditions

**Place of use** : Indoor use

## Risk management measures (RMM)

| Contributing activity                                                       | Process category (ies) | Maximum duration  | Ventilation                            |                                       |
|-----------------------------------------------------------------------------|------------------------|-------------------|----------------------------------------|---------------------------------------|
|                                                                             |                        |                   | Type                                   | ach (air changes per hour)            |
| Preparation of material for application                                     | PROC05                 | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                |
| Loading of application equipment and handling of coated parts before curing | PROC08b                | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                |
| Industrial application of coatings and inks by spraying                     | PROC07                 | More than 4 hours | Full containment/extraction            | 100 or equivalent                     |
| Film formation - force drying, stoving and other technologies               | PROC02                 | More than 4 hours | Local exhaust ventilation              | Refer to relevant technical standards |
| Cleaning                                                                    | PROC05                 | More than 4 hours | Local exhaust ventilation              | Refer to relevant technical standards |
| Application equipment cleaning outside booth                                | PROC05                 | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                |
| Waste management                                                            | PROC08b                | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                |

| Contributing activity                                                       | Process category (ies) | Respiratory | Eye                                     | Hands                                 |
|-----------------------------------------------------------------------------|------------------------|-------------|-----------------------------------------|---------------------------------------|
| Preparation of material for application                                     | PROC05                 | None        | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Loading of application equipment and handling of coated parts before curing | PROC08b                | None        | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Industrial application of coatings and inks by spraying                     | PROC07                 | None        | None                                    | None                                  |
| Film formation - force drying, stoving and other technologies               | PROC02                 | None        | None                                    | None                                  |
| Cleaning                                                                    | PROC05                 | None        | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Application equipment cleaning outside booth                                | PROC05                 | None        | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |

|                  |         |      |                                         |                                       |
|------------------|---------|------|-----------------------------------------|---------------------------------------|
| Waste management | PROC08b | None | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
|------------------|---------|------|-----------------------------------------|---------------------------------------|

See chapter 8 of this Safety Data Sheet for specifications.



## Disclaimer

The information in this Safe Use of Mixture Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product.

No liability is accepted for any damage, no matter of what kind, which is direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.

# SUMI

## Safe Use of Mixtures

### Information for end-users

**Title** : Industrial spray painting, no booth

*This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet, Technical Data sheet and labels.*

## General description of the process covered

Paint application on industrial line with no enclosure (only local exhaust ventilation)

## Operational conditions

**Place of use** : Indoor use

## Risk management measures (RMM)

| Contributing activity                                                       | Process category (ies) | Maximum duration  | Ventilation                            |                                       |
|-----------------------------------------------------------------------------|------------------------|-------------------|----------------------------------------|---------------------------------------|
|                                                                             |                        |                   | Type                                   | ach (air changes per hour)            |
| Preparation of material for application                                     | PROC05                 | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                |
| Loading of application equipment and handling of coated parts before curing | PROC08b                | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                |
| Industrial application of coatings and inks by spraying                     | PROC07                 | More than 4 hours | Local exhaust ventilation              | Refer to relevant technical standards |
| Film formation - force drying, stoving and other technologies               | PROC04                 | More than 4 hours | Local exhaust ventilation              | Refer to relevant technical standards |
| Cleaning                                                                    | PROC05                 | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                |
| Waste management                                                            | PROC08b                | More than 4 hours | Enhanced (mechanical) room ventilation | 5 - 10                                |

| Contributing activity                                                       | Process category (ies) | Respiratory                                                                              | Eye                                     | Hands                                 |
|-----------------------------------------------------------------------------|------------------------|------------------------------------------------------------------------------------------|-----------------------------------------|---------------------------------------|
| Preparation of material for application                                     | PROC05                 | None                                                                                     | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Loading of application equipment and handling of coated parts before curing | PROC08b                | None                                                                                     | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Industrial application of coatings and inks by spraying                     | PROC07                 | Wear a respirator conforming to EN140 with an assigned protection factor of at least 10. | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Film formation - force drying, stoving and other technologies               | PROC04                 | None                                                                                     | None                                    | None                                  |
| Cleaning                                                                    | PROC05                 | None                                                                                     | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |
| Waste management                                                            | PROC08b                | None                                                                                     | Use eye protection according to EN 166. | Wear suitable gloves tested to EN374. |

See chapter 8 of this Safety Data Sheet for specifications.



## Disclaimer

The information in this Safe Use of Mixture Information sheet is based on the data provided by the substance supplier for the substances in the product for which a chemical safety assessment has been carried out at the time of issue. It does not guarantee safe use of the product and does not replace any occupational risk assessment required by legislation. When developing workplace instructions for employees, SUMI sheets should always be considered in combination with the SDS and the label of the product.

No liability is accepted for any damage, no matter of what kind, which is direct or indirect consequence of acts and/or decisions (partly) based on the contents of this document.