SAFETY DATA SHEET

93301

Section 1. Identification

Product name	: THOMPSON'S® US Signature Series Color Wood Sealer Chestnut Brown
Product code	: 93301
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of the	he substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: THE THOMPSON'S COMPANY 101 W. Prospect Ave. Cleveland, OH 44115
Emergency telephone number of the company	: US/Canada: (216) 566-2917 Mexico: CHEMTREC Mexico 800-681-9531. Available 24 hours and 365 days per year
Product Information Telephone Number	: US / Canada: (800) 367-6297 Mexico: 800-717-3123 / 55-5333-1501
Transportation Emergency Telephone Number	: US/Canada: (800) 424-9300 Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year
Section 2. Hazards	s identification

ection 2. Hazarus identification

Chestnut Brown

	US Signature Series Color Wood Sealer SHW-85-NA-GHS-US				
Supplemental label elements Date of issue/Date of revision	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. : 4/16/2024 Version : 5.02 1/11				
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.				
Storage	: Store locked up.				
Response	: IF exposed or concerned: Get medical advice or attention.				
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection.				
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.				
Precautionary statements					
Hazard statements	: Suspected of causing cancer.				
Signal word	: Warning				
Hazard pictograms					
GHS label elements					
Classification of the substance or mixture	CARCINOGENICITY - Category 2				
OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).				

Section 2. Hazards identification

Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.

Hazards not otherwise classified

: DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.

identification

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Fumed Amorphous Silica	≤3	112945-52-5
Titanium Dioxide	≤1	13463-67-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health	<u>n effects</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

Date of issue/Date	e of revision	: 4/16/2024	Date of previous issue	: 2/23/2024	Version	: 5.02	2/11
93301	THOMPSON'S® US S Chestnut Brown	ignature Series	Color Wood Sealer		SHW-85-	NA-GHS-US	

Section 4. First aid measures

Over-exposure signs/symp	<u>otoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediate med	dical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	 No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protec	<u>tiv</u>	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Date of issue/Date	e of revision	: 4/16/2024	Date of previous issue	: 2/23/2024	Version : 5.02	3/11
93301	THOMPSON'S® US S Chestnut Brown	Signature Series	Color Wood Sealer		SHW-85-NA-GHS-US	

Section 6. Accidental release measures

Methods and materia	Is for containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Fumed Amorphous Silica	112945-52-5	NIOSH REL (United States, 10/2020). [SILICA, AMORPHOUS] TWA: 6 mg/m ³ 10 hours.
Titanium Dioxide	13463-67-7	OSHA PEL (United States, 5/2018). TWA: 15 mg/m ³ 8 hours. Form: Total dust ACGIH TLV (United States, 1/2023). TWA: 2.5 mg/m ³ 8 hours. Form: respirable fraction, finescale particles

Occupational exposure limits (Canada)

Date of issue/Date	of revision	: 4/16/2024	Date of previous issue	: 2/23/2024	Version	: 5.02	4/11
93301	THOMPSON'S® US Sig Chestnut Brown	nature Series (Color Wood Sealer		SHW-85-	NA-GHS-US	

Section 8. Exposure controls/personal protection

Ingredient name			CAS #	Exposure limits		
None.						
Occupational exposure lin	nits (<u>Mexico)</u>				
			CAS #	Exposure limits		
None.						
Biological exposure indice	s (U	nited States)				
No exposure indices known						
Biological exposure indice	s (C	anada)				
No exposure indices known						
Biological exposure indice	s (M	exico)				
No exposure indices known						
Appropriate engineering	:			, gas, vapor or mist, use process enclosures,		
controls				eering controls to keep worker exposure to nmended or statutory limits.		
Environmental exposure	:			ess equipment should be checked to ensure		
controls		5 1 5		nvironmental protection legislation. In some ering modifications to the process equipment		
		will be necessary to re				
Individual protection meas	<u>ures</u>					
Hygiene measures	Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.					
	Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safe					
		showers are close to t				
Eye/face protection	:			oved standard should be used when a risk		
				to avoid exposure to liquid splashes, mists, he following protection should be worn, unless		
	ee of protection: safety glasses with side-					
Skin protection		shields.				
Hand protection	:	Chemical-resistant, im	pervious gloves o	complying with an approved standard should be		
		worn at all times when	handling chemic	al products if a risk assessment indicates this is		
		during use that the glo	ves are still retair	s specified by the glove manufacturer, check ning their protective properties. It should be		
				any glove material may be different for different xtures, consisting of several substances, the		
		protection time of the				
Body protection	:			ody should be selected based on the task being		
		handling this product.	s involved and si	nould be approved by a specialist before		
Other skin protection	:	Appropriate footwear a		l skin protection measures should be selected		
		based on the task beir specialist before hand		the risks involved and should be approved by a		
Respiratory protection	:	Based on the hazard a	and potential for e	xposure, select a respirator that meets the		
				espirators must be used according to a e proper fitting, training, and other important		
		aspects of use.	program to enour	a propor many, training, and other important		

Date of issue/Date	of revision	: 4/16/2024	Date of previous issue	: 2/23/2024	Version	: 5.02	5/11
93301	THOMPSON'S® US Sig Chestnut Brown	gnature Series (Color Wood Sealer		SHW-85-	NA-GHS-US	

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Brown.
Odor	: Not available.
Odor threshold	: Not available.
рН	: 9
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: 100°C (212°F)
Flash point	: Closed cup: Not applicable.
Flash point Evaporation rate	Closed cup: Not applicable.0.09 (butyl acetate = 1)
Evaporation rate	: 0.09 (butyl acetate = 1)
Evaporation rate Flammability Lower and upper explosion	0.09 (butyl acetate = 1)Not available.
Evaporation rate Flammability Lower and upper explosion limit/flammability limit	 0.09 (butyl acetate = 1) Not available. Not available.
Evaporation rate Flammability Lower and upper explosion limit/flammability limit Vapor pressure	 0.09 (butyl acetate = 1) Not available. Not available. 2.3 kPa (17.5 mm Hg)

Media		Result
cold water		Partially soluble
	:	Not applicable.
uto-ignition temperature	:	Not available.
ecomposition temperature	:	Not available.
scosity	:	Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)
olecular weight	:	Not applicable.
leat of combustion	:	0.477 kJ/g
	Media cold water artition coefficient: n- ctanol/water uto-ignition temperature ecomposition temperature scosity olecular weight Heat of combustion	cold waterartition coefficient: n-artition coefficient: n-ctanol/wateruto-ignition temperatureacomposition temperaturescositycolecular weight

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Date of issue/Date of re-	vision : 4/16/2024	Date of previous issue	: 2/23/2024	Version : 5.02	6/11
	MPSON'S® US Signature Series tnut Brown	s Color Wood Sealer		SHW-85-NA-GHS-L	JS

 \checkmark

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Fumed Amorphous Silica	LD50 Oral	Rat	3160 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300	-
				ug l	

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Fumed Amorphous Silica Titanium Dioxide	-	3 2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely : Not available. routes of exposure

Chestnut Brown

Potential acute health effects

Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the	physical, chemical and toxicological characteristics	
Eye contact		
Inhalation		
Skin contact	: No specific data.	
Ingestion	: No specific data.	
Date of issue/Date of revision	: 4/16/2024 Date of previous issue : 2/23/2024	Version : 5.02 7/11
93301 THOMPSON'S	SHW-85-NA-GHS-US	

Section 11. Toxicological information

Delayed and immediate ef	fects and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health e	ffects
Not available.	
General	: No known significant effects or critical hazards.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Numerical measures of to	xicity

Numerical measures of toxicity Acute toxicity estimates Not available.

Section 12. Ecological information

Toxicity			
Product/ingredient name	Result	Species	Exposure
Titanium Dioxide	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

<u>Mobility in soil</u>

Soil/water partition: Not available.coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

Date of issue/Date of revision		: 4/16/2024	Date of previous issue	: 2/23/2024	Version : 5.02	8/11
93301	THOMPSON'S® US Signature Series Chestnut Brown		Color Wood Sealer		SHW-85-NA-GHS-US	

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-
Special precautions	conside mode o suitably to shipn of the p dangero and on	l odal shipping descrip or container sizes. Th f transport (sea, air, for that mode of tran nent, and compliance erson offering the pr pus goods must be tr all actions in case of	e presence of a ship etc.), does not indic nsport. All packaging e with the applicable oduct for transport. I rained on all of the ri	pping description for ate that the product g must be reviewed f regulations is the so People loading and u sks deriving from the	a particular is packaged for suitability prior ble responsibility unloading
ransport in bulk ac o IMO instruments	cording : Not avail	able.			

Proper shipping name : Not a

: Not available.

Section 15. Regulatory information

TSCA 5(a)2 proposed significant new use rules: Nonylphenoxypoly(ethoxy)ethanol; reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

<u>SARA 313</u>

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet, where applicable.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

Montreal Protocol

Not listed.


Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists : Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined. Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification					Justification		
CARCINOGENICITY - Category 2					Calculation method		
History							
Date of printir	ng	:	4/16/2024				
Date of issue/ revision	Date of	:	4/16/2024				
Date of previo	us issue	:	2/23/2024				
Version		:	5.02				
Date of issue/Date	of revision		: 4/16/2024	Date of previous issue	: 2/23/2024	Version : 5.02	10/11
3301 THOMPSON'S® US Signature Series Color Wood Sealer Chestnut Brown				SHW-85-NA-GHS-U	S		

Section 16. Other information

Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group
_	UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.