



Cabot® Solid Color Acrylic Siding Stain

#800 Series

DESCRIPTION

Enjoy durable, richly colored weather protection that keeps itself cleaner with innovative Rainwash Technology™. Everyday dirt and dust just rinse away each time it rains ... or you can rinse it off yourself with a garden hose. Its matte finish highlights wood texture and its 100% acrylic formula offers serious protection that lasts and lasts on wood siding, shingles and fences. Tint to any of 100 colors. Each one creates a mold-, mildew- and algae-resistant finish. Every home should look this good!

PRODUCT FEATURES

- Water repellent
- 100% Acrylic formula
- Low temp application
- Maximum pigment for superior coverage and UV protection

FOR USE ON

New or reconditioned wood siding and shingles, cement siding, manufactured hardboards, previously painted surfaces, aluminum and pre-primed ferrous metal, masonry, stucco and plywood-panel siding.

TINTING

White, Medium, Deep and Neutral Bases may be tinted with compatible universal colorants.

COVERAGE

On smooth surfaces approximately 300–400 sq. ft. (27–37 m²) per gallon. On rough surfaces, 200–300 sq. ft. (18–27 m²) per gallon.

Square feet can be calculated by multiplying length and width; e.g., 10' W x 25' L = 250 sq. ft. Requires a 2-coat application.

DRYING TIME

Approximately 4–6 hours depending on temperature and humidity.

SURFACE PREPARATION

In order to be effective, a stain must be able to adhere and penetrate. Surfaces must be sound and absolutely dry. Be sure surface is free of all dirt, mildew stains, loose wood fibers and other foreign matter. Old, loose stain should be scraped off and the edges sanded smooth for proper adhesion. New treated wood should be tested for porosity prior to application. Prepare previously stained or weathered surfaces with Cabot® Wood Cleaner to remove dirt and mildew stains, or Cabot® Wood Brightener to revive extremely weathered surfaces. Scrubbing with a stiff bristle brush is required to completely remove all dirt and debris. Sanding may be required to completely remove all loose wood fibers. Let the surface dry 24–48 hours after cleaning to ensure dry wood. Mildew: Any mildew stains present on the surface prior to application should be removed with Cabot® Wood Cleaner. Mildew stains are not caused by the coating, nor do they represent coating failure. This product contains agents that inhibit the growth of mildew on the coating's film.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

Apply with a natural-bristle brush or professional spray equipment. When spraying, always back-brush immediately. To ensure desired appearance and proper drying time, always finish a small test area before proceeding. Shake and stir thoroughly before and during use. If project requires more than 1 container, blend all containers together to ensure uniformity. Apply to small sections at a time (1–3 boards); start at one edge and follow through to the end of the boards to avoid lap marks. One thick coat application may be used on new wood: 2 coats for worn or weathered surfaces and for optimum performance.

RESTRICTIONS

Do not apply in direct sunlight, to hot surfaces or when air or surface temperature is below 35 °F (2 °C) or may fall below 35 °F (2 °C) for 48 hours after application. Do not apply over wet or damp surfaces or when rain is imminent. Do not intermix with any other products. Do not thin. Protect containers from freezing. For exterior use only.

NOTE TO USER

To ensure desired appearance and proper drying time, always finish a small test area before proceeding.

MAINTENANCE

UV rays (sunlight) and moisture (rain/snow/dew) are wood's natural enemies, so minimize exposure. Evaluate finish each spring and maintain as needed. Finish durability depends upon weather, wear and other local conditions, but finish typically lasts 10–20 years on siding and fences.



Cabot® Solid Color Acrylic Siding Stain

#800 Series

TECHNICAL DATA

Vehicle Type: Acrylic resin

Pigment Type: May contain titanium dioxide, iron oxide pigments, light-fast organic pigments and silica depending on color.

Viscosity: 100–110 Krebs Units

Flash Point: N/A

Sheen: 0–5 Units @ 85° (untinted)

V.O.C. Content: < 100 g/L

Solids Weight: 34%

Solids Volume: 25%

Density: 9.4 lbs./gal.

Recommended Film Thickness:

4.5 mil Wet 2.1 mil Dry

Application Temperature: 35–90 °F (2–32 °C)

*Data reported is typical of the Neutral Base and will vary by color and batch.

CLEANUP AND DISPOSAL

Clean up with soap and water. Do not freeze. Keep container closed when not in use. Do not transfer to other containers for storage or disposal. In case of spillage, absorb with inert material. Dispose in accordance with local, state and federal regulations.

WARRANTY

***SATISFACTION GUARANTEE LIFETIME LIMITED WARRANTY:** For complete warranty terms, visit cabotstain.com/warranty or contact customer service at 1-800-US-STAIN to request a written copy

CAUTIONS

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN**

PACKAGING

Available in quart, gallon and 5 gallon sizes. Ready mixes colors available in gallons.

BASE AND FILL LEVELS

	(oz./gal.)
White Base (801)	124
Neutral Base (806)	116
Medium Base (808)	120
Ultra White (812)	128
New Cedar (816)	128
Cordovan Brown (837)	128
Redwood (880)	128

Cabot
Cleveland, Ohio 44115
1-800-US-STAIN
cabotstain.com
Revision: 3/30/2023

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. CABOT assumes no obligation or liability for use of this information. **UNLESS CABOT AGREES OTHERWISE IN WRITING, CABOT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. CABOT WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.