



Cabot® Solid Color Oil Stain

#1600 Series

DESCRIPTION

Cabot® Solid Color Oil Stain combines maximum color and UV protection with a tough alkyd resin. The results are a completely opaque finish that imparts lasting beauty and is formulated to withstand foot traffic and wear.

PRODUCT FEATURES

- Water-repellent
- Superior durability
- Scuff resistant
- Penetrating oil to withstand heavy foot traffic

FOR USE ON

Exterior wood decks, railings, and outdoor furniture.

TINTING

White, Medium, Deep and Neutral Bases may be tinted with compatible universal colorants.

COVERAGE

On smooth surfaces approximately 400–500 sq. ft. (37–46 m²) per gallon. On rough surfaces, 200–300 sq. ft. (18–27 m²) per gallon. **Square feet can be calculated by multiplying length and width; e.g., 10' W x 25' L = 250 sq. ft. A 1-coat application is recommended; 2 coats may result in a higher sheen.**

DRYING TIME

Approximately 24 hours depending on temperature and humidity. When applied to decking covered by a canopy or roof structure, the drying time will be extended.

NOTE TO USER

To ensure desired appearance and proper drying time, always finish a small test area before proceeding.

SURFACE PREPARATION

Be sure surface is free of all dirt, mildew stains, loose wood fibers and other foreign matter. In order to be effective, a stain must be able to penetrate. Surfaces must be sound and absolutely dry. (Moisture content must be below 15% or wood must be exposed to dry weather a minimum of 3 to 5 days.) Prepare previously stained or weathered surfaces with Cabot® Wood Cleaner, Wood Brightener or Wood Strippers. On untreated weathered surfaces, scrubbing with a stiff bristle brush or sanding may be required to completely remove all loose wood fibers.

Mildew: Any mildew stains present on the surface prior to application should be removed with Cabot® Wood Cleaner. Mildew stains are not caused by the coating, nor do they represent coating failure. This product contains agents that inhibit the growth of mildew on the coating's film.

Extractive Bleeding: Extractive bleeding is not caused by the coating, nor is it a coating failure. To remove discoloration caused by extractive bleeding, use Cabot® Wood Brightener. Follow directions on label.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

Apply with a natural-bristle brush, stain pad or professional spray equipment. When spraying, always back-brush immediately. Do not overapply. Shake and stir thoroughly before and during use. If project requires more than 1 container, blend all containers together to ensure uniformity. Apply to small sections at a time (1–3 boards); start at one edge and follow through to the end of the boards to avoid lap marks. A 1-coat application is recommended; 2 coats may result in a higher sheen.

RESTRICTIONS

Overapplication of this product may result in a glossy appearance, poor drying or sagging. Do not apply in direct sunlight, to hot surfaces, or when air or surface temperature is below 50 °F (10 °C) or may fall below 50 °F (10 °C) for 48 hours after application. Do not apply over wet or damp surfaces or when rain is imminent. **Do not intermix with any other products. Do not thin.** Do not apply over previously painted or sealed surfaces. **For exterior use only.**

MAINTENANCE

UV rays (sunlight) and moisture (rain/snow/dew) are wood's natural enemies, so minimize exposure. Evaluate finish each spring and maintain as needed. Finish durability depends upon weather, wear and other local conditions, but finish typically lasts 5–10 years on decks.



Cabot® Solid Color Oil Stain

#1600 Series

TECHNICAL DATA

Pigment Type: May contain titanium-dioxide, iron-oxide pigments, light-fast organic pigments and silica depending on color

Vehicle Type: Specially-blended Alkyd Resins

Solvent Type: Aliphatic petroleum distillates

Viscosity: 65–75 Krebs Units

Flash Point: over 100°F

V.O.C. Content: < 350 g/L

Solids Weight: 72%

Solids Volume: 58%

Density: 9.7 lbs./gal.

Film Thickness: 2–3 mil dry

Water Repellent: Yes

Mildew Resistant: Yes

*Data reported is typical of the Neutral Base and will vary by color and batch.

CLEANUP AND DISPOSAL

Clean brushes and tools with a regionally compliant cleaner following manufacturer's safety instructions. Wash hands with soap and water.

DANGER: Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed, water-filled metal container. Dispose of according to local regulations.

WARRANTY

***SATISFACTION GUARANTEE LIFETIME**

LIMITED WARRANTY: For complete warranty terms, visit cabotstain.com/warranty or contact customer service at 1-800-US-STAIN to request a written copy

CAUTIONS

DANGER! HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE! VAPOR HARMFUL. IRRITATES EYES, SKIN AND RESPIRATORY TRACT. CONTAINS ALIPHATIC HYDROCARBONS. Contents are **COMBUSTIBLE**. Keep away from heat and open flame. **VAPOR HARMFUL.** Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (**NIOSH** approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. DANGER:** Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

PACKAGING

Available in gallons.

BASE AND FILL LEVELS

	(oz./gal.)
White Base (1601)	124
Neutral Base (1606)	116
Deep Base (1607)	116
Medium Base (1608)	120

Cleveland, OH 44115
1-800-US-STAIN
cabotstain.com
Revised:3/3/2023