



Cabot Wood Toned Stain + Sealer LOW VOC

#19200 Series

DESCRIPTION

Cabot® Wood Toned Stain + Sealer is specially formulated with a unique blend of resin and oil to provide a superior, natural finish for bare wood. Easy to apply, Cabot Wood Toned Stain slightly darkens wood when first applied, leaving a flat, translucent-toned finish, which weathers with time to a natural wood hue. For use on new or reconditioned exterior wood only, including decks, siding, fences and trim. Also suitable for use on shingles, shakes and log homes.

PRODUCT FEATURES

- Water repellent
- Deep-penetrating oil
- Fade resistant
- A translucent oil stain that highlights wood's natural beauty

FOR USE ON

New or reconditioned exterior wood only, including decks, siding, fences and trim. Also suitable for use on shingles and shakes.

TINTING

Do not tint this product.

COVERAGE

Approximately 250–350 sq. ft. (23–33 m²) per gallon. **Square feet can be calculated by multiplying length and width; e.g., 10' W x 25' L = 250 sq. ft. Requires a 1-coat application.**

DRYING TIME

Approximately 24 hours depending on temperature and humidity.

NOTE TO USER

The appearance of the finish will vary depending on the porosity and color of the wood surface. To ensure desired appearance and proper drying time, always finish a small test area before proceeding.

SURFACE PREPARATION

In order to be effective, a stain must be able to adhere and penetrate. Surfaces must be sound and absolutely dry. Be sure surface is free of all dirt, mildew stains, loose wood fibers and other foreign matter. Old, loose stain should be scraped off and the edges sanded smooth for proper adhesion. New treated wood should be tested for porosity prior to application. Prepare previously stained or weathered surfaces with Cabot® Wood Cleaner to remove dirt and mildew stains, or Cabot® Wood Brightener to revive extremely weathered surfaces. Scrubbing with a stiff bristle brush is required to completely remove all dirt and debris. Sanding may be required to completely remove all loose wood fibers. Let the surface dry 24-48 hours after cleaning to ensure dry wood. Mildew: Any mildew stains present on the surface prior to application should be removed with Cabot® Wood Cleaner. Mildew stains are not caused by the coating, nor do they represent coating

failure. This product contains agents that inhibit the growth of mildew on the coating's film.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

Apply with good-quality, nylon or polyester brushes, stain pads or professional spray equipment. When spraying, always back-brush immediately. To ensure desired appearance and proper drying time, always finish a small test area before proceeding. Do not overapply. Shake and stir thoroughly before and during use. If project requires more than 1 container, blend all containers together to ensure uniformity. Apply to small sections at a time (1-3 boards); start at one edge and follow through to the end of the boards to avoid lap marks. Apply 1 coat only. For wood substrates only.

RESTRICTIONS

Do not apply in direct sunlight, to hot surfaces or when air or surface temperature is below 50°F (10°C) or may fall below 50°F (10°C) for 48 hours after application. Do not apply over wet surfaces or when rain is imminent. Do not intermix with any other products. Do not thin. Protect containers from freezing. Do not apply over previously painted or sealed surfaces. For exterior use only.

MAINTENANCE

UV rays (sunlight) and moisture (rain/snow/dew) are wood's natural enemies, so minimize exposure. Evaluate finish each spring and maintain as needed. Finish durability depends upon weather, wear and other local conditions, but finish typically lasts 1–2 years on decks and 1–3 years on siding and fences.



Cabot Wood Toned Stain + Sealer LOW VOC

#19200 Series

TECHNICAL DATA

Vehicle Type: Long-oil alkyds, Tung oil and natural linseed oil
Solvent: Water; ester alcohol; ethylene glycol monopropyl
Viscosity: 25–50 Units Centipoise
Flash Point: N/A
V.O.C. Content: < 250 g/L
Solids Weight: 23%
Solids Volume: 22%
Density: 8.4 lbs./gal.
Film Thickness: Minimal because Cabot Semi-Transparent Stain penetrates deeply into wood.
Water Repellent: Yes
Mildew Resistant: Yes

*Data reported is typical of the Neutral Base and will vary by color and batch.

PACKAGING

4 ready mix colors available in quarts, gallon and five gallon.

BASE AND FILL LEVELS

	(oz./gal.)
Natural (19200)	128
Cedar (19202)	128
Heartwood (19204)	128
Pacific Redwood (19205)	128

CLEANUP AND DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.

WARRANTY

*SATISFACTION GUARANTEE LIFETIME LIMITED WARRANTY:

For complete warranty terms, visit cabotstain.com/warranty or contact customer service at 1-800-US-STAIN to request a written copy.

CAUTIONS

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.** **DANGER:** Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, waterfilled, metal container. Dispose of in accordance with local fire regulations.

Cleveland, OH
44115
1-800-US-STAIN
cabotstain.com
Revised:3/3/2023