



Cabot® Wood Cleaner

#8007

DESCRIPTION

Cabot® Wood Cleaner is specially formulated to remove stains caused by mold, mildew, and algae, as well as dirt and other foreign matter, from painted, stained, or weathered wood surfaces. Unlike other mildew stain cleaners, this easy-to-use Cabot product does not require the addition of bleach in order to be effective. Use for routine cleaning and for properly preparing all surfaces prior to staining or painting. Cabot Wood Cleaner is not a paint or stain remover. It will, however, remove paint or stain on an unsound surface.

PRODUCT FEATURES

- Ready-To-Use formula
- Removes dirt and mildew stains
- Ideal for cleaning decks, siding and fences prior to staining
- Removes dirt, algae stains and mildew stains

FOR USE ON

Exterior wood decks, siding, fences, railings, steps and most exterior surfaces including aluminum, vinyl, plastic and masonry.

COVERAGE

Approximately 200 sq. ft. per gallon (18 m² per 3.78 L).

PACKAGING

Available in Ready-to-Use gallons.

INGREDIENTS

VOC: < 0.5%

INGREDIENTS: Sodium Hypochlorite and Sodium Hydroxide. For more ingredient information, visit our website.

APPLICATION

Important — read before use. Test it: on a small, hidden area at recommended dilution to determine its effectiveness. Protect shrubs: wet down with water and cover with plastic. Hose off shrubs when job is done. Application: APPLY LIBERALLY to problem surfaces using a brush or pump sprayer. Do not apply to hot surfaces. To avoid non-uniform appearances on vertical surfaces, start at the bottom, doing a small section at a time and continue to the top, being sure to rinse thoroughly.

LET SET 15–20 MINUTES. Stubborn areas may require scrubbing with a stiff bristle brush. If surface begins to dry quickly, lightly mist with water. RINSE using a garden hose with nozzle at maximum pressure or a high-pressure power washer. Repeat procedure if necessary.

IMPORTANT: Allow cleaned surfaces to dry completely before staining or painting. Do not apply this product when temperatures are below 50 °F (10 °C).

IMPORTANT: Always wear safety goggles or a face shield, rubber gloves, protective clothing and footwear when spraying.

IMPORTANT: When applying and rinsing product, walking surfaces, ladders and scaffolding may become slippery. Rinse all such surfaces thoroughly to remove overspray.

Cleanup: Rinse equipment and overspray areas thoroughly with water.

Storage: Keep from freezing. Store at temperatures between 50 °F (10 °C) and 100 °F (38 °C).

CAUTIONS

DANGER! Contains Sodium Hypochlorite and Sodium Hydroxide. **KEEP OUT OF THE REACH OF CHILDREN.** Harmful if inhaled. Causes eye, skin and respiratory tract burns. **Use only with adequate ventilation.** Do not breathe spray mist. Avoid contact with eyes, skin and clothing. Wear protective equipment during application, including acid resistant rubber gloves, goggles, boots, dust mask and other appropriate clothing. Wash thoroughly after handling. **DO NOT TAKE INTERNALLY. Do not mix with other products or chemicals such as peroxides or alkalines, as this will release hazardous gases. First Aid: Eye Contact:** Flush thoroughly with water for at least 15 minutes. If irritation persists, get medical attention.* **Skin Contact:** Flush skin thoroughly with soap and water for at least 15 minutes. If irritation persists, get medical attention.* Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean contaminated shoes. **If Inhaled:** If affected by spray mist, move to fresh air. If breathing difficulty continues, get medical attention.* **If Swallowed:** Give large amounts of water immediately. Do not induce vomiting. Get medical attention immediately.*

*Call poison control center, hospital emergency room or physician immediately.

WARNING: This product contains chemicals known to the State of California to cause cancer.

Cleveland, OH 44115
1-800-US-STAIN
cabotstain.com
Revised:3/3/2023