



Cabot® Wood Brightener

#8008

DESCRIPTION

Cabot® Wood Brightener is formulated specifically to remove unsightly discoloration of wood caused by tannin bleed in extractive-prone wood types such as cedar and redwood. It also removes nail and metal rust stains. This product can be used on all painted, stained and unfinished wood surfaces. Plus, when used on weathered wood, Cabot Wood Brightener brings back the rich, new-wood look. Cabot Wood Brightener is not a paint or stain remover. It will, however, remove paint or stain on an unsound surface.

PRODUCT FEATURES

- Ready-To-Use formula
- Brightens and conditions exterior siding, fences and decks
- Removes extractive tannin bleed and rust stains

FOR USE ON

Exterior wood decks, siding, fences, railings, and steps. Can also be used to remove rust stains on all types of coated surfaces.

COVERAGE

Approximately 200 sq. ft. per gallon (18 m² per 3.78 L)

PACKAGING

Available in Ready-to-Use gallons.

INGREDIENTS

VOC: < 4%

INGREDIENTS: Water, Oxalic Acid. For more ingredient information, visit our website

APPLICATION

Important — read before use

Test it: on a small, hidden area at recommended dilution to determine its effectiveness. Protect shrubs: wet down with water and cover with plastic. Hose off shrubs when job is done.

PROTECT GLASS: Wet down with water or cover with plastic. Hose off glass frequently to prevent streaking.

Application: APPLY LIBERALLY to problem surfaces using a brush or pump sprayer. Do not apply to hot surfaces. To avoid non-uniform appearances on vertical surfaces, start at the bottom, doing a small section at a time and continue to the top, being sure to rinse thoroughly.

LET SET 15–20 MINUTES. Stubborn areas may require scrubbing with a stiff bristle brush. If surface begins to dry quickly, lightly mist with water. RINSE using a garden hose with nozzle at maximum pressure or a high-pressure power washer. Repeat procedure if necessary.

IMPORTANT: Allow cleaned surfaces to dry completely before staining or painting. Do not apply this product when temperatures are below 50 °F (10 °C).

IMPORTANT: Always wear safety goggles or a face shield, rubber gloves, protective clothing and footwear when spraying.

IMPORTANT: When applying and rinsing product, walking surfaces, ladders and scaffolding may become slippery. Rinse all such surfaces thoroughly to remove overspray.

Cleanup: Rinse equipment and overspray areas thoroughly with water.

Storage: Keep from freezing. Store at temperatures between 50 °F (10 °C) and 100 °F (38 °C).

CAUTIONS

DANGER! Contains Oxalic Acid. **KEEP OUT OF THE REACH OF CHILDREN.** Harmful if inhaled. Causes eye, skin and respiratory tract burns. **Use only with adequate ventilation.** Do not breathe spray mist. Avoid contact with eyes, skin and clothing. Wear protective equipment during application, including acid resistant rubber gloves, goggles, boots, dust mask and other appropriate clothing. Wash thoroughly after handling. **DO NOT TAKE INTERNALLY. Do not mix with other products or chemicals such as peroxides or alkalines, as this will release hazardous gases. First Aid: Eye Contact:** Flush thoroughly with water for at least 15 minutes and get medical attention.* **Skin Contact:** Flush skin thoroughly with soap and water for at least 15 minutes. If irritation persists, get medical attention.* Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean contaminated shoes. **If Inhaled:** If affected by spray mist, move to fresh air. If breathing difficulty continues, get medical attention.* **If Swallowed:** Give large amounts of water immediately. Do not induce vomiting. Get medical attention immediately.*

*Call poison control center, hospital emergency room or physician immediately.

Cleveland, OH 44115
1-800-US-STAIN
cabotstain.com
Revised:3/3/2023