SAFETY DATA SHEET

4666143

Section 1. Identification : Valspar Defense Exterior Satin **Product name** Base 2 **Product code** : 4666143 Other means of : Not available. identification **Product type** : Liquid. Relevant identified uses of the substance or mixture and uses advised against Paint or paint related material. Manufacturer : Valspar 101 W. Prospect Avenue Cleveland, OH 44115 **Emergency telephone** : (800) 424-9300 number of the company **Product Information** : 1-877-825-7727 **Telephone Number**

Section 2. Hazards identification

: (800) 424-9300

Transportation Emergency

Base 2

Telephone Number

| Date of issue/Date of revision4666143Valspar Defense | : 5/18/2024 Date of previous issue : 4/10/2024 Version : 8 1/ • Exterior Satin SHW-85-NA-GHS-US | |
|--|---|--|
| Response | : IF exposed or concerned: Get medical advice or attention. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. | |
| Prevention | : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid breathing vapor. Contaminated work clothing must not be allowed out of the workplace. | |
| <u>Precautionary statements</u> General | : Read label before use. Keep out of reach of children. If medical advice is needed, hav product container or label at hand. | |
| Hazard statements | : May cause an allergic skin reaction. May cause cancer. Suspected of damaging fertility or the unborn child. | |
| Signal word | : Danger | |
| <u>GHS label elements</u> Hazard pictograms | | |
| Classification of the substance or mixture | : SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A TOXIC TO REPRODUCTION - Category 2 | |
| OSHA/HCS status | : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). | |

Section 2. Hazards identification

| Storage | : Store locked up. |
|-------------------------------------|--|
| Disposal | : Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Supplemental label elements | WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure. |
| | Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage. |
| Hazards not otherwise classified | : None known. |

Section 3. Composition/information on ingredients

| Substance/mixture | : Mixture |
|-------------------|------------------|
| Other means of | : Not available. |
| identification | |

CAS number/other identifiers

| Ingredient name | % by weight | CAS number |
|--------------------------------------|-------------|------------|
| Titanium Dioxide | ≤10 | 13463-67-7 |
| Zinc Oxide | ≤5 | 1314-13-2 |
| Bis(pentamethyl-4-piperidyl)sebacate | ≤0.3 | 41556-26-7 |
| Cristobalite, respirable powder | ≤0.3 | 14464-46-1 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

| Eye contact | : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. |
|--------------|--|
| Inhalation | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
| Skin contact | : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse. |

Section 4. First aid measures

| Section 4. First a | |
|--------------------------------|---|
| Ingestion | : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
| Most important symptoms/ | effects, acute and delayed |
| Potential acute health effe | <u>cts</u> |
| Eye contact | : No known significant effects or critical hazards. |
| Inhalation | : No known significant effects or critical hazards. |
| Skin contact | : May cause an allergic skin reaction. |
| Ingestion | : No known significant effects or critical hazards. |
| <u>Over-exposure signs/sym</u> | otoms |
| Eye contact | : No specific data. |
| Inhalation | : Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations |
| Skin contact | : Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations |
| Ingestion | : Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations |
| Indication of immediate me | dical attention and special treatment needed, if necessary |
| Notes to physician | Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments | : No specific treatment. |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

See toxicological information (Section 11)

Section 5. Fire-fighting measures

| Extinguishing media | |
|--------------------------------|---|
| Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. |
| Unsuitable extinguishing media | : None known. |

| Date of issue/Date | e of revision | : 5/18/2024 | Date of previous issue | : 4/10/2024 | Version : 8 | 3/14 |
|--------------------|------------------------------|---------------|------------------------|-------------|------------------|------|
| 4666143 | Valspar Defense Ex Base 2 | cterior Satin | | | SHW-85-NA-GHS-US | |

Section 5. Fire-fighting measures

| • | |
|--|---|
| Specific hazards arising from the chemical | : In a fire or if heated, a pressure increase will occur and the container may burst. |
| Hazardous thermal decomposition products | : Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides |
| Special protective actions for fire-fighters | Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

| For non-emergency personnel | : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
|--------------------------------|--|
| For emergency responders | : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| Environmental precautions | : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). |
| Methods and materials for co | tainment and cleaning up |
| Small chill | Stop look if without rick. Move containers from spill area. Dilute with water and mon up |

| Small spill | : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
|-------------|---|
| Large spill | : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. |

Section 7. Handling and storage

Precautions for safe handling

| Protective measures | : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. |
|---------------------|---|
|---------------------|---|

| Date of issue/Date | of revision | : 5/18/2024 | Date of previous issue | : 4/10/2024 | Version : 8 | 4/14 |
|--------------------|---------------------------------|-------------|------------------------|-------------|------------------|------|
| 4666143 | Valspar Defense Exter Base 2 | or Satin | | | SHW-85-NA-GHS-US | |

Section 7. Handling and storage

| Advice on general occupational hygiene | Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |
|--|---|
| Conditions for safe storage, including any incompatibilities | Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. |

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

| Zinc Oxide 1314-13-2 1314-13- | Ingredient name | CAS # | Exposure limits |
|--|------------------|------------|---|
| Zinc Oxide1314-13-2NIOSH REL (United States, 10/2020). CEIL: 15 mg/m³ Form: Dust TWA: 5 mg/m³ 10 hours. Form: Dust TWA: 5 mg/m³ 15 minutes. Form: Dust mues STEL: 10 mg/m³ 15 minutes. Form: Fum OSHA PEL (United States, 5/2018). TWA: 5 mg/m³ 8 hours. Form: Respirable fraction TWA: 15 mg/m³ 8 hours. Form: Respirable fraction STEL: 10 mg/m³ 15 minutes. Form: Respirable fraction STEL: 10 mg/m³ 12 x (%SiO2+2) 8 hours Form: Respirable TWA: 30 mg/m³ / 2 x (%SiO2+2) 8 hours Form: Respirable TWA: 30 mg/m³ / 2 x (%SiO2+2) 8 hours Form: Total dust OSHA PEL (United States, 5/2018). [Sili crystalline] TWA: 50 µg/m³ 8 hours. Form: Respirable TWA: 50 µg/m³ 8 hours. Form: Respirable form: Total dust OSHA PEL (United States, 7/2023). [Sili crystalline] TWA: 50 µg/m³ 8 hours. Form: Respirable form Total dust OSHA PEL (United States, 7/2023). [Sili crystalline] TWA: 50 µg/m³ 8 hours. Form: Respirable form: Respirable form: Respirable form: Respirable for | Titanium Dioxide | 13463-67-7 | TWA: 15 mg/m ³ 8 hours. Form: Total dust ACGIH TLV (United States, 7/2023). TWA: 2.5 mg/m ³ 8 hours. Form: respirable |
| Cristobalite, respirable powder 14464-46-1 OSHA PEL Z3 (United States, 6/2016). TWA: 250 mppcf / 2 x (%SiO ₂ +5) 8 hours Form: Respirable TWA: 10 mg/m³ / 2 x (%SiO ₂ +2) 8 hours Form: Respirable TWA: 30 mg/m³ / 2 x (%SiO ₂ +2) 8 hours Form: Total dust OSHA PEL (United States, 5/2018). [Sili crystalline] TWA: 50 µg/m³ 8 hours. Form: Respirable dust ACGIH TLV (United States, 7/2023). [Sili crystalline] TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction | Zinc Oxide | 1314-13-2 | NIOSH REL (United States, 10/2020). CEIL: 15 mg/m ³ Form: Dust TWA: 5 mg/m ³ 10 hours. Form: Dust and fumes STEL: 10 mg/m ³ 15 minutes. Form: Fume OSHA PEL (United States, 5/2018). TWA: 5 mg/m ³ 8 hours. Form: Fume TWA: 5 mg/m ³ 8 hours. Form: Respirable fraction TWA: 15 mg/m ³ 8 hours. Form: Total dust ACGIH TLV (United States, 7/2023). TWA: 2 mg/m ³ 8 hours. Form: Respirable fraction STEL: 10 mg/m ³ 15 minutes. Form: |
| | | | OSHA PEL Z3 (United States, 6/2016). TWA: 250 mppcf / 2 x (%SiO₂+5) 8 hours. Form: Respirable TWA: 10 mg/m³ / 2 x (%SiO₂+2) 8 hours. Form: Respirable TWA: 30 mg/m³ / 2 x (%SiO₂+2) 8 hours. Form: Total dust OSHA PEL (United States, 5/2018). [Silica, crystalline] TWA: 50 μg/m³ 8 hours. Form: Respirable dust ACGIH TLV (United States, 7/2023). [Silica, crystalline] TWA: 0.025 mg/m³ 8 hours. Form: |

Section 8. Exposure controls/personal protection

| | [SILICA, CRYSTALLINE] TWA: 0.05 mg/m³ 10 hours. Form: respirable dust |
|--|---|
|--|---|

Occupational exposure limits (Canada)

| Ingredient name | CAS # | Exposure limits |
|-----------------|------------|---|
| Zinc Oxide | 1314-13-2 | CA Alberta Provincial (Canada, 3/2023). OEL: 2 mg/m ³ 8 hours. Form: Respirable OEL: 10 mg/m ³ 15 minutes. Form: Respirable CA British Columbia Provincial (Canada, 8/2023). TWA: 2 mg/m ³ 8 hours. Form: Respirable STEL: 10 mg/m ³ 15 minutes. Form: Respirable CA Quebec Provincial (Canada, 7/2023). TWAEV: 2 mg/m ³ 8 hours. Form: Respirable dust. STEV: 10 mg/m ³ 15 minutes. Form: Respirable dust. CA Ontario Provincial (Canada, 6/2019). TWA: 2 mg/m ³ 8 hours. Form: Respirable particulate matter. STEL: 10 mg/m ³ 15 minutes. Form: Respirable particulate matter. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 10 mg/m ³ 15 minutes. Form: respirable dust and fume TWA: 2 mg/m ³ 8 hours. Form: respirable dust and fume |
| Cristobalite | 14464-46-1 | CA British Columbia Provincial (Canada, 8/2023). [Silica, Crystalline - alpha quartz and Cristobalite] TWA: 0.025 mg/m³ 8 hours. Form: Respirable CA Quebec Provincial (Canada, 7/2023). TWAEV: 0.05 mg/m³ 8 hours. Form: Respirable dust. CA Alberta Provincial (Canada, 3/2023). OEL: 0.025 mg/m³ 8 hours. Form: Respirable particulate CA Ontario Provincial (Canada, 6/2019). TWA: 0.05 mg/m³ 8 hours. Form: Respirable particulate matter. CA Saskatchewan Provincial (Canada, 7/2013). TWA: 0.05 mg/m³ 8 hours. Form: respirable fraction |

Occupational exposure limits (Mexico)

| Date of issue | /Date of revision | : 5/18/2024 | Date of previous issue | : 4/10/2024 | Version : 8 | 6/14 |
|---------------|--|-------------|------------------------|-------------|------------------|------|
| 4666143 | 4666143 Valspar Defense Exterior Satin Base 2 | | | | SHW-85-NA-GHS-US | ; |

Section 8. Exposure controls/personal protection

| | | CAS # | Exposure limits | |
|---|--|--|--|--|
| Zinc Oxide | | 1314-13-2 | NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 2 mg/m ³ 8 hours. Form: Respirable fraction STEL: 10 mg/m ³ 15 minutes. Form: Respirable fraction | |
| Biological exposure indice | <u>s (United States)</u> | | | |
| No exposure indices known | | | | |
| Biological exposure indice No exposure indices known | | | | |
| Biological exposure indice | s (Mexico) | | | |
| No exposure indices known | | | | |
| | | | | |
| Appropriate engineering controls | local exhaust ver airborne contami | ntilation or other engi nants below any rec | es, gas, vapor or mist, use process enclosures, ineering controls to keep worker exposure to ommended or statutory limits. | |
| Environmental exposure controls | they comply with cases, fume scru | the requirements of been been been been been been been bee | ocess equipment should be checked to ensure environmental protection legislation. In some ineering modifications to the process equipment s to acceptable levels. | |
| ndividual protection measu | <u>ures</u> | | | |
| Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, the eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clor Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safet showers are close to the workstation location. | | | | |
| Eye/face protection | assessment indic gases or dusts. | cates this is necessa If contact is possible | proved standard should be used when a risk iry to avoid exposure to liquid splashes, mists, , the following protection should be worn, unless egree of protection: safety glasses with side- | |
| Skin protection | | | | |
| Hand protection | worn at all times necessary. Cons during use that th noted that the tim glove manufactur | when handling chem sidering the paramet ne gloves are still ret ne to breakthrough fo rers. In the case of r | s complying with an approved standard should b nical products if a risk assessment indicates this ers specified by the glove manufacturer, check aining their protective properties. It should be or any glove material may be different for differer mixtures, consisting of several substances, the be accurately estimated. | |
| Body protection | • | e risks involved and | e body should be selected based on the task beir I should be approved by a specialist before | |
| Other skin protection | based on the tas | | nal skin protection measures should be selected nd the risks involved and should be approved by .t. | |
| Respiratory protection | appropriate stand | dard or certification. | r exposure, select a respirator that meets the Respirators must be used according to a ure proper fitting, training, and other important | |

| Date of issue/Date of revision | | : 5/18/2024 | Date of previous issue | : 4/10/2024 | Version : 8 | 7/14 |
|--------------------------------|-----------------------------|---------------|------------------------|-------------|------------------|------|
| 4666143 | Valspar Defense E Base 2 | xterior Satin | | | SHW-85-NA-GHS-US | |

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

| Appearance | |
|---|-------------------------------|
| Physical state | : Liquid. |
| Color | : White. |
| Odor | : Not available. |
| Odor threshold | : Not available. |
| рН | : 9.6 |
| Melting point/freezing point | : Not available. |
| Boiling point, initial boiling point, and boiling range | : 100°C (212°F) |
| Flash point | : Closed cup: Not applicable. |
| Evaporation rate | : 0.09 (butyl acetate = 1) |
| Flammability | : Not available. |
| Lower and upper explosion limit/flammability limit | : Not available. |
| Vapor pressure | : 2.3 kPa (17.5 mm Hg) |
| Relative vapor density | : 1 [Air = 1] |
| Relative density | : 1.19 |
| Solubility(ies) | 4 |

| Media | | Result | |
|--|--------|--|--|
| cold water | | Partially soluble | |
| Partition coefficient: n- octanol/water | : Not | applicable. | |
| Auto-ignition temperature | : Not | available. | |
| Decomposition temperature | : Not | available. | |
| Viscosity | : Kin | ematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt) | |
| Molecular weight | : Not | applicable. | |
| Heat of combustion | : 0.81 | l2 kJ/g | |

Section 10. Stability and reactivity

| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
|------------------------------------|--|
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : No specific data. |
| Incompatible materials | : No specific data. |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

| Date of issue/Date | of revision | : 5/18/2024 | Date of previous issue | : 4/10/2024 | Version : 8 | 8/14 |
|--|-------------|-------------|------------------------|-------------|------------------|------|
| 4666143 Valspar Defense Exterior Satin Base 2 | | | | | SHW-85-NA-GHS-US | |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Not available.

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|----------------------|---------|-------|----------------------|-------------|
| Titanium Dioxide | Skin - Mild irritant | Human | - | 72 hours 300 ug l | - |
| Zinc Oxide | Eyes - Mild irritant | Rabbit | - | 24 hours 500 | - |
| | Skin - Mild irritant | Rabbit | - | 24 hours 500 mg | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|--|--------|---------|--------------------------------------|
| Titanium Dioxide Cristobalite, respirable powder | - + | 2B 1 | - Known to be a human carcinogen. |

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

| Name | | Route of exposure | Target organs |
|---------------------------------|------------|----------------------|-------------------|
| Cristobalite, respirable powder | Category 1 | inhalation | respiratory tract |

Aspiration hazard

Not available.

Information on the likely : Not available.

routes of exposure

Potential acute health effects

| Eye contact | : No known significant effects or critical hazards. |
|--------------|---|
| Inhalation | : No known significant effects or critical hazards. |
| Skin contact | : May cause an allergic skin reaction. |
| Ingestion | : No known significant effects or critical hazards. |

| Date of is | sue/Date of revision | : 5/18/2024 | Date of previous issue | : 4/10/2024 | Version : 8 | 9/14 |
|------------|------------------------------|---------------|------------------------|-------------|------------------|------|
| 4666143 | Valspar Defense Ex Base 2 | xterior Satin | | | SHW-85-NA-GHS-US | |

Section 11. Toxicological information

| Symptoms related to the ph | ysical, chemical and toxicological characteristics |
|----------------------------|--|
| Eye contact | : No specific data. |
| Inhalation | : Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations |
| Skin contact | : Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations |
| Ingestion | : Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations |

| Delayed and immediate ef | fects and also chronic effects from short and long term exposure |
|--------------------------------|---|
| Short term exposure | |
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| Long term exposure | |
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| Potential chronic health et | ffects |
| Not available. | |
| General | : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. |
| Carcinogenicity | : May cause cancer. Risk of cancer depends on duration and level of exposure. |
| Mutagenicity | : No known significant effects or critical hazards. |
| Teratogenicity | : No known significant effects or critical hazards. |
| Developmental effects | : No known significant effects or critical hazards. |
| Fertility effects | : Suspected of damaging fertility. |
| | |

Numerical measures of toxicity Acute toxicity estimates Not available.

Section 12. Ecological information

Toxicity

| Date of issue/Date | e of revision | : 5/18/2024 | Date of previous issue | : 4/10/2024 |
|--------------------|---------------------------------|-------------|------------------------|-------------|
| 4666143 | Valspar Defense Exter Base 2 | ior Satin | | |
| | Dase Z | | | |

Section 12. Ecological information

| L | | | - |
|--------------------------------|-----------------------------------|---|----------------------------------|
| Product/ingredient name | Result | Species | Exposure |
| Titanium Dioxide Zinc Oxide | Acute IC50 1.85 mg/l Marine water | Fish - <i>Fundulus heteroclitus</i> Algae - <i>Skeletonema costatum</i> Daphnia - <i>Daphnia magna</i> - Neonate | 96 hours 96 hours 48 hours |
| | Acute LC50 1.1 ppm Fresh water | Fish - Oncorhynchus mykiss | 96 hours |

Persistence and degradability

Not available.

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|-------|-----------|
| Zinc Oxide | - | 28960 | High |

Mobility in soil

| Soil/water partition | : Not available. |
|----------------------|------------------|
| coefficient (Koc) | |

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

- **Disposal methods**
- : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | DOT Classification | TDG Classification | Mexico Classification | ΙΑΤΑ | IMDG |
|---|--|-----------------------|--------------------------|--|--|
| UN number | Not regulated. | Not regulated. | Not regulated. | UN3082 | UN3082 |
| UN proper shipping name | - | - | - | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Zinc Pyrithione, Zinc Oxide) | ENVIRONMENTALL HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Zinc Pyrithione, Zinc Oxide). Marine pollutant (Zinc Pyrithione, Zinc Oxide) |
| Date of issue/Date of re 666143 Vals | vision : 5/18/20 par Defense Exterior Satin | 024 Date of previous | issue : 4/10/202 | | on : 8 11/1 -85-NA-GHS-US |

| 111 |
|--|
| Yes. |
| duct is lated as rous teen soluted in ≤5 L or soluted tagings agings be general this product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 1.1 and 1.1 and 4.1.1.8. Emergency schedules F-A, S F |
| national purposes and do not scription for a particular he product is packaged e reviewed for suitability prior ons is the sole responsibility bading and unloading ving from the substances |
| |

Section 15. Regulatory information

TSCA 5(a)2 proposed significant new use rules: 2-Methyl-4-isothiazolin-3-one; reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

<u>SARA 313</u>

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet, where applicable.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

| Date of issue/Dat | e of revision | : 5/18/2024 | Date of previous issue | : 4/10/2024 | Version : 8 | 12/14 |
|-------------------|---------------------------------|-------------|------------------------|-------------|------------------|-------|
| 4666143 | Valspar Defense Exter Base 2 | rior Satin | | | SHW-85-NA-GHS-US | |

Section 15. Regulatory information

International regulations

Montreal Protocol

Not listed.


Stockholm Convention on Persistent Organic Pollutants

Not listed.

| International lists | : Australia inventory (AIIC): Not determined. |
|---------------------|--|
| | China inventory (IECSC): Not determined. |
| | Japan inventory (CSCL): Not determined. |
| | Japan inventory (ISHL): Not determined. |
| | Korea inventory (KECI): Not determined. |
| | New Zealand Inventory of Chemicals (NZIoC): Not determined. |
| | Philippines inventory (PICCS): Not determined. |
| | Taiwan Chemical Substances Inventory (TCSI): Not determined. |
| | Thailand inventory: Not determined. |
| | Turkey inventory: Not determined. |
| | Vietnam inventory: Not determined. |

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Base 2

| | Classification | Justification | | |
|--|--|-------------------|--|--|
| SKIN SENSITIZATION - C CARCINOGENICITY - Cat TOXIC TO REPRODUCTI | Calculation method Calculation method Calculation method | | | |
| <u>History</u> | | | | |
| Date of printing | : 5/18/2024 | | | |
| Date of issue/Date of revision | : 5/18/2024 | | | |
| Date of previous issue | : 4/10/2024 | | | |
| Version | : 8 | | | |
| Key to abbreviations | : ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = Iogarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 | | | |
| Date of issue/Date of revision | : 5/18/2024 Date of previous issue : 4/10/2024 | Version : 8 13/14 | | |
| 666143 Valspar Defens | e Exterior Satin | SHW-85-NA-GHS-US | | |

Section 16. Other information

as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

✓ Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.