# **SAFETY DATA SHEET**

4666149

### Section 1. Identification **Product name** : Valspar Defense Exterior Satin Base 4 **Product code** : 4666149 Other means of : Not available. identification **Product type** : Liquid. Relevant identified uses of the substance or mixture and uses advised against Paint or paint related material. Manufacturer : Valspar 101 W. Prospect Avenue Cleveland, OH 44115 **Emergency telephone** : (800) 424-9300 number of the company **Product Information** : 1-877-825-7727 **Telephone Number Transportation Emergency** : (800) 424-9300 **Telephone Number** Section 2. Hazards identification **OSHA/HCS** status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). **Classification of the** : SKIN SENSITIZATION - Category 1 **CARCINOGENICITY - Category 1A** substance or mixture **TOXIC TO REPRODUCTION - Category 2 GHS** label elements Hazard pictograms Signal word : Danger **Hazard statements** : May cause an allergic skin reaction. May cause cancer. Suspected of damaging fertility or the unborn child. **Precautionary statements** General : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. **Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Avoid breathing vapor. Contaminated work clothing must not be allowed out of the workplace. : IF exposed or concerned: Get medical advice or attention. Wash contaminated clothing Response before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Date of issue/Date of revision : 5/18/2024 : 4/10/2024 1/12 Date of previous issue Version : 7 4666149 Valspar Defense Exterior Satin SHW-85-NA-GHS-US

Base 4

# Section 2. Hazards identification

Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise	: None known.

# Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

### **CAS number/other identifiers**

Ingredient name	% by weight	CAS number
Bis(pentamethyl-4-piperidyl)sebacate	≤0.3	41556-26-7
Cristobalite, respirable powder	≤0.3	14464-46-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

### Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	<ul> <li>Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.</li> </ul>
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing
Date of issue/Date of revision	: 5/18/2024 Date of previous issue : 4/10/2024 Version : 7 2/12

Dute of 1550c/Dute	orrevision	0,10,2021	Dute of previous issue	. 1/10/2021	
4666149	Valspar Defense Exteri Base 4	or Satin			SHW-85-NA-GHS-US

# Section 4. First aid measures

such as a collar, tie, belt or waistband.

Most important symptoms/eff	ects, acute and delayed
Potential acute health effects	<u>5</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sympto	oms
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide

Date of issue/Date	e of revision	: 5/18/2024	Date of previous issue	: 4/10/2024	Version : 7	3/12
4666149	Valspar Defense Exter	ior Satin			SHW-85-NA-GHS-US	
	Base 4					

# Section 5. Fire-fighting measures

Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

Personal precautions, protec	tive equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ntainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Date of issue/Date of revision : 5/18/2024		: 5/18/2024	Date of previous issue	: 4/10/2024	Version : 7	4/12
4666149 Valspar Defense Exterior Satin				SHW-85-NA-GHS-US		
	Base 4					

# Section 7. Handling and storage

Conditions for safe storage,	: Store in accordance with local regulations. Store in original container protected from
including any	direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials
incompatibilities	(see Section 10) and food and drink. Store locked up. Keep container tightly closed
	and sealed until ready for use. Containers that have been opened must be carefully
	resealed and kept upright to prevent leakage. Do not store in unlabeled containers.
	Use appropriate containment to avoid environmental contamination. See Section 10 for
	incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

### **Control parameters**

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Bis(pentamethyl-4-piperidyl)sebacate Cristobalite, respirable powder	41556-26-7 14464-46-1	None. OSHA PEL Z3 (United States, 6/2016). TWA: 250 mppcf / 2 x (%SiO <sub>2</sub> +5) 8 hours. Form: Respirable TWA: 10 mg/m <sup>3</sup> / 2 x (%SiO <sub>2</sub> +2) 8 hours. Form: Respirable TWA: 30 mg/m <sup>3</sup> / 2 x (%SiO <sub>2</sub> +2) 8 hours. Form: Total dust OSHA PEL (United States, 5/2018). [Silica, crystalline] TWA: 50 μg/m <sup>3</sup> 8 hours. Form: Respirable dust ACGIH TLV (United States, 7/2023). [Silica, crystalline] TWA: 0.025 mg/m <sup>3</sup> 8 hours. Form: Respirable fraction NIOSH REL (United States, 10/2020). [SILICA, CRYSTALLINE] TWA: 0.05 mg/m <sup>3</sup> 10 hours. Form: respirable dust

### Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
Cristobalite	14464-46-1	CA British Columbia Provincial (Canada, 8/2023). [Silica, Crystalline - alpha quartz and Cristobalite] TWA: 0.025 mg/m <sup>3</sup> 8 hours. Form: Respirable CA Quebec Provincial (Canada, 7/2023). TWAEV: 0.05 mg/m <sup>3</sup> 8 hours. Form: Respirable dust. CA Alberta Provincial (Canada, 3/2023). OEL: 0.025 mg/m <sup>3</sup> 8 hours. Form: Respirable particulate CA Ontario Provincial (Canada, 6/2019). TWA: 0.05 mg/m <sup>3</sup> 8 hours. Form: Respirable particulate matter. CA Saskatchewan Provincial (Canada, 7/2013). TWA: 0.05 mg/m <sup>3</sup> 8 hours. Form: respirable fraction

Occupational exposure limits (Mexico)

# Section 8. Exposure controls/personal protection

		CAS #	Exposure limits				
None.							
Biological exposure indices (United States) No exposure indices known.							
Biological exposure indices (Canada) No exposure indices known.							
Biological exposure indices (N	lexico)						
No exposure indices known.							
Appropriate engineering controls : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.							
Environmental exposure : controls	they comply with the re	equirements of en s, filters or engine	ess equipment should be checked to ensure vironmental protection legislation. In some ering modifications to the process equipment o acceptable levels.				
Individual protection measures	-						
Hygiene measures :	eating, smoking and u Appropriate technique Contaminated work clo	sing the lavatory a s should be used othing should not before reusing.	ghly after handling chemical products, before and at the end of the working period. to remove potentially contaminated clothing. be allowed out of the workplace. Wash Ensure that eyewash stations and safety cation.				
Eye/face protection :	assessment indicates gases or dusts. If co		oved standard should be used when a risk to avoid exposure to liquid splashes, mists, ne following protection should be worn, unless ee of protection: safety glasses with side-				
Skin protection							
Hand protection :	worn at all times when necessary. Considerin during use that the glo noted that the time to l	handling chemican ng the parameters wes are still retain breakthrough for a In the case of mix	complying with an approved standard should be al products if a risk assessment indicates this is a specified by the glove manufacturer, check ing their protective properties. It should be any glove material may be different for different ctures, consisting of several substances, the accurately estimated.				
Body protection :			ody should be selected based on the task being nould be approved by a specialist before				
Other skin protection :		ng performed and	skin protection measures should be selected the risks involved and should be approved by a				
Respiratory protection :	appropriate standard of	or certification. Re	xposure, select a respirator that meets the espirators must be used according to a e proper fitting, training, and other important				

# Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance	
Physical state	: Liquid.
Color	: Clear.
Odor	: Not available.
Odor threshold	: Not available.
рН	: 9.3
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: 100°C (212°F)
Flash point	: Closed cup: Not applicable.
Evaporation rate	: 0.09 (butyl acetate = 1)
Flammability	: Not available.
Lower and upper explosion limit/flammability limit	: Not available.
Vapor pressure	: 2.3 kPa (17.5 mm Hg)
Relative vapor density	: 1 [Air = 1]
Relative density	: 1.08
Solubility(ies)	:

Media		Result			
cold water		Partially soluble			
Partition coefficient: n- : Not octanol/water		applicable.			
Auto-ignition temperature : Not		available.			
Decomposition temperature : Not :		available.			
Viscosity : Kine		ematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)			
Molecular weight	: Not applicable.				
Heat of combustion : 0.94		2 kJ/g			

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Date of issue/Date of revision : 5/18/2024		Date of previous issue	: 4/10/2024	Version : 7	7/12	
4666149	Valspar Defense Exterior Satin Base 4				SHW-85-NA-GHS-US	

# Section 11. Toxicological information

### Information on toxicological effects

### Acute toxicity

Not available.

### Irritation/Corrosion

Not available.

### **Sensitization**

Not available.

### **Mutagenicity**

Not available.

### **Carcinogenicity**

Not available.

### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Cristobalite, respirable + 1 powder		1	Known to be a human carcinogen.

### Reproductive toxicity

Not available.

### **Teratogenicity**

Not available.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Cristobalite, respirable powder	Category 1	inhalation	respiratory tract

### Aspiration hazard

Not available.

# Information on the likely<br/>routes of exposure: Not available.Potential acute health effectsEye contact<br/>Inhalation: No known significant effects or critical hazards.Skin contact<br/>Ingestion: May cause an allergic skin reaction.Ingestion: No known significant effects or critical hazards.

Symptoms related to the p	hysical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Date of issue/Dat	e of revision	: 5/18/2024	Date of previous issue	: 4/10/2024	Version : 7	8/12
4666149	Valspar Defense I Base 4	Exterior Satin			SHW-85-NA-GHS-US	

# Section 11. Toxicological information

Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Delayed and immediate ef	fects and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health e	ffects
Not available.	
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: May cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: Suspected of damaging fertility.

### Numerical measures of toxicity Acute toxicity estimates Not available.

# Section 12. Ecological information

### **Toxicity**

Not available.

### Persistence and degradability

Not available.

### **Bioaccumulative potential**

Not available.

### Mobility in soil

Date of issue/Date of revision		: 5/18/2024	Date of previous issue	: 4/10/2024	Version : 7	9/12
4666149	666149 Valspar Defense Exterior Satin Base 4				SHW-85-NA-GHS-US	6

# Section 12. Ecological information

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

# Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according : Not available. to IMO instruments

Date of issue/Date of revision		: 5/18/2024	Date of previous issue	: 4/10/2024	Version : 7	10/12
4666149 Valspar Defense Exterior Satin Base 4		ior Satin			SHW-85-NA-GHS-L	IS

# Section 14. Transport information

Proper shipping name : No

: Not available.

# Section 15. Regulatory information

**TSCA 5(a)2 proposed significant new use rules**: 2-Methyl-4-isothiazolin-3-one; reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

### <u>SARA 313</u>

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet, where applicable.

### California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

### International regulations

### **Montreal Protocol**

Not listed.

### Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists : Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined. Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

# Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification	
SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A TOXIC TO REPRODUCTION - Category 2	Calculation method Calculation method Calculation method	
History		
Date of printing : 5/18/2024		

	5					
Date of issue/Date	of revision	: 5/18/2024	Date of previous issue	: 4/10/2024	Version : 7	11/12
4666149	Valspar Defense E Base 4	Exterior Satin			SHW-85-NA-GHS-L	IS

# Section 16. Other information

Date of issue/Date of revision	: 5/18/2024
Date of previous issue	: 4/10/2024
Version	: 7
Key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations</li> </ul>

✓ Indicates information that has changed from previously issued version.

### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.