



Valspar® Prep Step® Drywall Primer

No. 990 series

GENERAL DESCRIPTION

Valspar® Prep Step® Drywall primer will create an optimal appearance for your topcoat, improving sheen differences between porous and non-porous surfaces and allowing color uniformity.

PRODUCT FEATURES

- Ideal for drywall, plaster and repaints
- Seals porous walls and ceilings
- High hiding for drastic color changes
- Prepares surface for any topcoat
- Great for brush, roller and spray application

RECOMMENDED USES

- Drywall
- Plaster
- Previously painted surfaces

SHIPPING AND PACKAGING

Freight Classification: Paint or paint related material. Protect from freezing.

Packaging:

- Gallon – 4 per carton
- Quart – 4 per carton
- 5 Gallon Pail

COMPOSITION

Base and Fill Levels

(oz./gal.)

White 128

APPLICATION AND CLEANUP

Application: Stir thoroughly. Intermix containers to ensure uniform color. Apply with a premium-quality roller, premium quality synthetic brush or airless sprayer. If applying by spray, back-roll or back-brush to work paint into the surface. Apply a liberal coat of primer uniformly, working well into the surface. Surface conditions and application technique can also impact coverage.

Cleanup: Clean up with warm, soapy water.

Airless Spray:

Pressure: 2000 PSI

Tip: 0.015–0.019"

Brush: premium-quality nylon or polyester brush

Roller: premium quality synthetic, 3/8 – 1/2" nap

SYSTEM

RECOMMENDATIONS

Drywall:

1 Coat Valspar® Prep Step® Drywall

1-2 Coats Valspar® Paint

Plaster:

1 Coat Valspar® Prep Step® Drywall

1-2 Coats Valspar® Paint

Previously Painted Surfaces:

1 Coat Valspar® Prep Step® Drywall

1-2 Coats Valspar® Paint

PRODUCT SPECIFICATIONS

Vehicle Type: Vinyl Acetate Ethylene Copolymer

Pigment Type: Titanium dioxide

Viscosity: 95-105 Krebs Units

Sheen: 0–9 Units @ 85° angle

Flashpoint: N/A

VOC: < 50 g/L as per 40 CFR 59.406

Volume Solids: 19%

Weight Solids: 40%

Weight Per Gallon: 10.52 lbs./gal

Practical Coverage: up to 400 sq. ft. per gallon (37

m² per 3.78 L) depending on surface porosity.

Recommended Film Thickness:

4.0 mil Wet 8 mil Dry

Dry Time @ 77 °F and 50% Relative Humidity

To Touch: 1 hour

Recoat: 2 hours for latex

4 hours for oil

Washing Instructions: Wait at least 7 days before

washing with a mild detergent and soft sponge

Application Temperature: 50–90 °F (10–32 °C)

Storage Temperature: 40–90 °F (5–32 °C)

REGULATORY COMPLIANCE

Current as of: 12/21/2020

SCAQMD Yes

CARB 2000 SCM Yes

CARB 2007 SCM Yes

OTC/LADCO Yes

US National Yes

STORAGE AND DISPOSAL

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.

SURFACE PREPARATION

General:

Read the Lead Warning paragraph.

Surfaces must be clean, dry and dull prior to application. Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Scrape and sand peeled or damaged paint. Sand glossy surfaces dull. All dust should be removed. Heavily stained areas, including tannin stains on wood, may require an appropriate stain-blocking primer. Do not use on bare metal or over glazed or glossy surfaces.

New Drywall/Wallboard:

Tape joints should be sanded smooth and even with the drywall or wallboard. Using a damp cloth or sponge, wipe tape joints and all wallboard surfaces to remove all sanding dust. Be sure to remove all chalky residue before priming. Allow to dry, then prime.

Plaster:

Allow new plaster to fully cure and sand smooth. Soft and deteriorating plaster can be treated with 1-pint of household vinegar to 1-gallon of water, repeat until surface is hard. Rinse with water and allow to dry prior to priming.

Previously Painted Surfaces:

Remove all dirt, dust, grease and oils by using a non-residue cleaner to clean the surface. Scrape off any loose, cracked or peeling paint. Patch cracks and nail holes. Sand smooth, then prime entire surface or spot prime patches.

LEAD WARNING

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

WARRANTY

Satisfaction Guaranteed – Limited Warranty

This product is warranted to perform to your satisfaction at the time of application when applied to a properly prepared residential surface in accordance with the label directions and excludes failure due to deterioration of the underlying surface, structural defects or failure of previous product. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.

MILDEW

Mildew is a fungus that looks like dirt, but won't wash off. Mildew must be removed before painting or it will grow through any new coat of paint. To remove mildew or suspected mildew, scrub surface before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin and eyes. Protect skin and eyes by wearing rubber gloves and eye goggles when working with bleach solution.

CAUTIONS

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

15 (1/10)

First Aid: Eye Contact: Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention.* **If Inhaled:** If affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.* **If Swallowed:** Drink 2 glasses of water. Get medical attention immediately.*

*Call poison control center, hospital emergency room or physician immediately.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:

1-888-345-5732

101 W. Prospect Ave. Cleveland, OH
888.313.5569

valsparpaint.com

Revised: 12/21/200

Version: 990A