# **SAFETY DATA SHEET**

VL1028077

# Section 1. Identification

Product name	: Transparent Exterior Stain Canyon Brown
Product code	: VL1028077
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of th	e substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: Valspar 101 W. Prospect Avenue Cleveland, OH 44115

Emergency telephone number of the company	: (800) 424-9300
Product Information Telephone Number	: 1-877-825-7727
Transportation Emergency Telephone Number	: (800) 424-9300

# Section 2. Hazards identification

OSHA/HCS sta	atus :	This material is considered hazardous by the OSHA Hazard (29 CFR 1910.1200).	Communication Standard
Classification substance or I		SKIN SENSITIZATION - Category 1 GERM CELL MUTAGENICITY - Category 1	
		TOXIC TO REPRODUCTION - Category 1B	
GHS label eler	<u>nents</u>		
Hazard picto	grams :		
Signal word	:	Danger	
Hazard state	ments :	May cause an allergic skin reaction. May cause genetic defects. May damage fertility or the unborn child.	
<b>Precautionary</b>	statements		
General	:	Read label before use. Keep out of reach of children. If med product container or label at hand.	lical advice is needed, have
Prevention	:	Obtain special instructions before use. Do not handle until al been read and understood. Wear protective gloves, protective protection. Avoid breathing vapor. Contaminated work clothin of the workplace.	e clothing and eye or face
Response	:	IF exposed or concerned: Get medical advice or attention. We before reuse. IF ON SKIN: Wash with plenty of water. If skir Get medical advice or attention.	0
Date of issue/Date	e of revision	: 2/4/2024 Date of previous issue : 11/6/2023	Version : 18.01 1/13
VL1028077	Transparent Exterior Canyon Brown	Stain	SHW-85-NA-GHS-US

# Section 2. Hazards identification

Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

# Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

#### **CAS number/other identifiers**

Ingredient name	% by weight	CAS number
Propylene Glycol	≤3	57-55-6
Heavy Paraffinic Oil	≤1	64742-54-7
Bis(pentamethyl-4-piperidyl)sebacate	≤0.3	41556-26-7
Carbendazim	≤0.3	10605-21-7
UV Light Absorber	≤0.3	104810-48-2
Benzotriazole Hydroxyphenyl Polymer	≤0.3	104810-47-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

Description of	necessary first a	<u>id measures</u>	2			
Eye contact	:	eyelids. Ch	y flush eyes with plenty of w leck for and remove any co et medical attention.			
Inhalation	:	not breathir respiration aid to give r in recovery	tim to fresh air and keep at ng, if breathing is irregular of or oxygen by trained persor mouth-to-mouth resuscitation position and get medical at t clothing such as a collar,	r if respiratory arrean nel. It may be dan on. Get medical att tention immediately	st occurs, provide a gerous to the perso ention. If unconsci y. Maintain an oper	artificial on providing ous, place
Skin contact	:	contaminate Continue to complaints	plenty of soap and water. F ed clothing thoroughly with rinse for at least 10 minute or symptoms, avoid further bughly before reuse.	water before removes. Get medical atte	/ing it, or wear glov ention. In the even	es. t of any
Ingestion	:	and the exp exposed per unless direct kept low so anything by and get me	nouth with water. Remove posed person is conscious, erson feels sick as vomiting cted to do so by medical pe that vomit does not enter the mouth to an unconscious p dical attention immediately. ollar, tie, belt or waistband.	give small quantitie may be dangerous rsonnel. If vomiting he lungs. Get med person. If unconsci Maintain an open	es of water to drink. Do not induce vo g occurs, the head ical attention. Neve ious, place in recov	Stop if the miting should be er give rery position
Date of issue/Date	of revision	: 2/4/2024	Date of previous issue	: 11/6/2023	Version : 18.	01 2/13
VL1028077	Transparent Exterior S Canyon Brown	Stain			SHW-85-NA-G	HS-US

# Section 4. First aid measures

Most important sympt	oms/effects, acute and delayed
Potential acute health	<u>n effects</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: May cause an allergic skin reaction.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs	/symptoms
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediat	e medical attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large

Notes to physician	<ul> <li>I reat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide

Date of issue/D	ate of revision	: 2/4/2024	Date of previous issue	: 11/6/2023	Version : 18.01	3/13
VL1028077	Transparent Exter	rior Stain			SHW-85-NA-GHS-US	
	Canyon Brown					

# **Section 5. Fire-fighting measures**

Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

Personal precautions, protect	tive equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ntainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures

Date of issue/Date	e of revision	: 2/4/2024	Date of previous issue	: 11/6/2023	Version : 18.01	4/13
VL1028077	Transparent Exteri Canyon Brown	or Stain			SHW-85-NA-GHS-US	

# Section 7. Handling and storage

Conditions for safe storage,	: Store in accordance with local regulations. Store in original container protected from					
including any	direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials					
incompatibilities	(see Section 10) and food and drink. Store locked up. Keep container tightly closed					
-	and sealed until ready for use. Containers that have been opened must be carefully					
	resealed and kept upright to prevent leakage. Do not store in unlabeled containers.					
	Use appropriate containment to avoid environmental contamination. See Section 10 for					
	incompatible materials before handling or use.					

## Section 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits (OSHA United States)**

Ingredient name	CAS #	Exposure limits	
Propylene Glycol	57-55-6	OARS WEEL (United States, 4/2022). TWA: 10 mg/m <sup>3</sup> 8 hours.	
Heavy Paraffinic Oil	64742-54-7	OSHA PEL (United States, 5/2018). [Oil mist, mineral] TWA: 5 mg/m <sup>3</sup> 8 hours. ACGIH TLV (United States, 1/2023). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2020). [OIL MIST MINERAL] TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Mist	
Bis(pentamethyl-4-piperidyl)sebacate	41556-26-7	STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist None.	
Carbendazim	10605-21-7	None.	
UV Light Absorber	104810-48-2	None.	
Benzotriazole Hydroxyphenyl Polymer	104810-47-1	None.	

#### Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
Kaolin	1332-58-7	<ul> <li>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable</li> <li>CA Quebec Provincial (Canada, 6/2022). TWAEV: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable dust.</li> <li>CA Ontario Provincial (Canada, 6/2019). TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable particulate matter.</li> <li>CA Saskatchewan Provincial (Canada, 7/2013).</li> <li>STEL: 4 mg/m<sup>3</sup> 15 minutes. Form: respirable fraction</li> <li>TWA: 2 mg/m<sup>3</sup> 8 hours. Form: respirable fraction</li> <li>CA British Columbia Provincial (Canada, 6/2022). Notes: the value is for particulate matter containing no asbestos and less than 1% crystalline silica.</li> <li>TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable</li> </ul>

#### **Occupational exposure limits (Mexico)**

Date of issue/Date	of revision	: 2/4/2024	Date of previous issue	: 11/6/2023	Version	: 18.01	5/13
VL1028077	Transparent Exterior St Canyon Brown	ain			SHW-85-	NA-GHS-US	

# Section 8. Exposure controls/personal protection

				CAS #	Exposure limits				
No	ne.								
Bio	logical exposure indices	(U)	nited States)						
No	No exposure indices known.								
<u>Bio</u>	logical exposure indices	<u>(Ca</u>	anada)						
No	No exposure indices known.								
<u>Bio</u>	logical exposure indices	<u>(M</u>	<u>exico)</u>						
No	exposure indices known.								
cont	ropriate engineering trols ironmental exposure		local exhaust ventilational airborne contaminants	on or other engine below any recom	, gas, vapor or mist, use process enclosures, ering controls to keep worker exposure to mended or statutory limits. ess equipment should be checked to ensure				
cont	trols		they comply with the re	equirements of en s, filters or engine	vironmental protection legislation. In some ering modifications to the process equipment				
	vidual protection measur								
Hy	giene measures	<ul> <li>asures</li> <li>Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.</li> </ul>							
Eye	e/face protection	:	assessment indicates gases or dusts. If con	this is necessary tact is possible, the	oved standard should be used when a risk to avoid exposure to liquid splashes, mists, ne following protection should be worn, unless ee of protection: safety glasses with side-				
<u>Ski</u>	in protection								
H	and protection	:	worn at all times when necessary. Considerin during use that the glo noted that the time to b	handling chemica ng the parameters ves are still retain preakthrough for a In the case of mix	complying with an approved standard should be al products if a risk assessment indicates this is a specified by the glove manufacturer, check ing their protective properties. It should be any glove material may be different for different ctures, consisting of several substances, the accurately estimated.				
B	ody protection	:			ody should be selected based on the task being nould be approved by a specialist before				
0	ther skin protection	:		ng performed and	skin protection measures should be selected the risks involved and should be approved by a				
Re	spiratory protection	:	appropriate standard of	or certification. Re	xposure, select a respirator that meets the espirators must be used according to a e proper fitting, training, and other important				

# Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance	
Physical state	: Liquid.
Color	: Not available.
Odor	: Not available.
Odor threshold	: Not available.
рН	: 8.9
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: 100°C (212°F)
Flash point	: Closed cup: Not applicable.
Flash point Evaporation rate	<ul><li>Closed cup: Not applicable.</li><li>0.09 (butyl acetate = 1)</li></ul>
Evaporation rate	: 0.09 (butyl acetate = 1)
Evaporation rate Flammability Lower and upper explosion	<ul> <li>0.09 (butyl acetate = 1)</li> <li>Not available.</li> <li>Lower: 2.6%</li> </ul>
Evaporation rate Flammability Lower and upper explosion limit/flammability limit	<ul> <li>0.09 (butyl acetate = 1)</li> <li>Not available.</li> <li>Lower: 2.6% Upper: 12.5%</li> </ul>
Evaporation rate Flammability Lower and upper explosion limit/flammability limit Vapor pressure	<ul> <li>0.09 (butyl acetate = 1)</li> <li>Not available.</li> <li>Lower: 2.6% Upper: 12.5%</li> <li>2.3 kPa (17.5 mm Hg)</li> </ul>

	Result
	Partially soluble
: Not	applicable.
: Not	available.
: Not	available.
: Kin	ematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)
: Not	applicable.
: 1.75	59 kJ/g
	: Not : Not : Kin : Not

# Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Date of issue/Dat	te of revision	: 2/4/2024	Date of previous issue	: 11/6/2023	Version : 18.01	7/13
VL1028077	Transparent Exter Canyon Brown	ior Stain			SHW-85-NA-GHS-US	

# Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Propylene Glycol	LD50 Dermal	Rabbit	20800 mg/kg	-
	LD50 Oral	Rat	20 g/kg	-
Carbendazim	LD50 Dermal	Rabbit	8500 mg/kg	-
	LD50 Dermal	Rat	2 g/kg	-
	LD50 Oral	Rat	>5050 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Propylene Glycol	Eyes - Mild irritant	Rabbit	-	100 mg	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Skin - Mild irritant	Human	-	168 hours	-
				500 mg	
	Skin - Mild irritant	Woman	-	96 hours 30	-
				%	
	Skin - Moderate irritant	Child	-	96 hours 30	-
				% C	
	Skin - Moderate irritant	Human	-	72 hours 104	-
				mg l	

#### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Name	Result
Heavy Paraffinic Oil	ASPIRATION HAZARD - Category 1

# Information on the likely : Not available. routes of exposure

#### Potential acute health effects

Eye contact	1	No known significant effects or critical hazards.
Inhalation	÷	No known significant effects or critical hazards.

Skin contact : May cause an allergic skin reaction.

Date of issue/Dat	e of revision	: 2/4/2024	Date of previous issue	: 11/6/2023	Version	: 18.01	8/13
VL1028077	Transparent Exteri Canyon Brown	or Stain			SHW-85-	NA-GHS-US	

# Section 11. Toxicological information

Ingestion	: No known significant effects or critical hazards.
Symptoms related to the p	physical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Delayed and immediate ef	fects and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health e	ffects
Not available.	
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: May cause genetic defects.
Teratogenicity	: May damage the unborn child.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: May damage fertility.
-	

Numerical measures of toxicity Acute toxicity estimates Not available.

: 2/4/2024

: 11/6/2023

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Propylene Glycol	Acute EC50 >110 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 1020000 μg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 hours
	Acute LC50 710000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
Carbendazim	Acute EC50 19.0562 mg/l Fresh water	Algae - Scenedesmus acutus var. acutus	96 hours
	Acute EC50 20 µg/l Fresh water	Daphnia - <i>Daphnia magna</i>	48 hours
	Acute LC50 77 µg/l Fresh water	Crustaceans - <i>Gammarus pulex</i> - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 7 μg/l Fresh water	Fish - Ictalurus punctatus - Yolk- sac fry	96 hours
	Chronic EC10 10 µg/l Fresh water	Crustaceans - Gammarus pulex - Adult	21 days
	Chronic NOEC 3.1 ppb Fresh water	Daphnia - <i>Daphnia magna</i>	21 days

#### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Propylene Glycol	-	-	Readily

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Carbendazim	-	2.51	Low

<u>Mobility in soil</u>	
Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects

: No known significant effects or critical hazards.

## Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date	of revision	: 2/4/2024	Date of previous issue	: 11/6/2023	Version : 18.01	10/13
VL1028077	Transparent Exterior S	tain			SHW-85-NA-GHS-US	
	Canyon Brown					

### Section 14. Transport information

UN proper shipping nameTransport hazard class(es)Packing groupEnvironmental hazardsAdditional	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
shipping nameTransport hazard class(es)Packing groupEnvironmental hazardsAdditional	-	-	_		
hazard class(es)Packing groupEnvironmental hazardsAdditional				-	-
Environmental hazards Additional	-	-	-	-	-
hazards Additional	-	-	-	-	-
	No.	No.	No.	No.	No.
information	-	-	-	-	-
Special precautions f ransport in bulk acc o IMO instruments	conside mode of suitably to shipm of the pe dangero and on a	odal shipping descrip r container sizes. Th f transport (sea, air, for that mode of tran nent, and compliance erson offering the pro- ous goods must be tr all actions in case of able.	e presence of a ship etc.), does not indica isport. All packaging with the applicable oduct for transport. I ained on all of the ri	oping description for ate that the product g must be reviewed to regulations is the se People loading and sks deriving from th	a particular is packaged for suitability prior ple responsibility unloading

## Section 15. Regulatory information

**TSCA 5(a)2 proposed significant new use rules**: 2-Methyl-4-isothiazolin-3-one; reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

#### SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet, where applicable.

#### California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

#### International regulations

#### **Montreal Protocol**

Not listed.

Stockholm Convention on Persistent Organic Pollutants

: 2/4/2024

#### Not listed.

Date	of issue/Date of	revision


: 11/6/2023

## Section 15. Regulatory information

International lists	: Australia inventory (AIIC): Not determined.
	China inventory (IECSC): Not determined.
	Japan inventory (CSCL): Not determined.
	Japan inventory (ISHL): Not determined.
	Korea inventory (KECI): Not determined.
	New Zealand Inventory of Chemicals (NZIoC): Not determined.
	Philippines inventory (PICCS): Not determined.
	Taiwan Chemical Substances Inventory (TCSI): Not determined.
	Thailand inventory: Not determined.
	Turkey inventory: Not determined.
	Vietnam inventory: Not determined.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

#### Procedure used to derive the classification

Classification		Justification
SKIN SENSITIZATION - C GERM CELL MUTAGENIC TOXIC TO REPRODUCTI	Calculation method Calculation method Calculation method	
History		
Date of printing	: 2/4/2024	
Date of issue/Date of revision	: 2/4/2024	
Date of previous issue	: 11/6/2023	
Version	: 18.01	
Key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations</li> </ul>	

Indicates information that has changed from previously issued version.
<u>Notice to reader</u>

Date of issue/Date	e of revision	: 2/4/2024	Date of previous issue	: 11/6/2023	Version : 18.01	12/13
VL1028077 Transparent Exterior Stain Canyon Brown			SHW-85-NA-GHS-US			

# Section 16. Other information

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.