# **SAFETY DATA SHEET**

15359

### Section 1. Identification

Product name	: Interior/Exterior Door & Trim Enamel Semi-Gloss Base 4	
Product code	: 15359	
Other means of identification	: Not available.	
Product type	: Liquid.	
Relevant identified uses of	he substance or mixture and uses advised against	
Paint or paint related material		
Manufacturer	: Valspar 101 W. Prospect Avenue Cleveland, OH 44115	
Emergency telephone number of the company	: (800) 424-9300	

Emergency telephone number of the company	: (800) 424-9300
Product Information Telephone Number	: 1-877-825-7727
Transportation Emergency Telephone Number	: (800) 424-9300

# Section 2. Hazards identification

OSHA/HCS status	: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.
Classification of the substance or mixture	: Not classified.
GHS label elements	
Signal word	: No signal word.
Hazard statements	: No known significant effects or critical hazards.
Precautionary statements	
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Not applicable.
Response	: Not applicable.
Storage	: Not applicable.
Disposal	: Not applicable.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure.

Date of issue/Date	of revision	: 11/28/2023	Date of previous issue	: 9/21/2023	Version	:17	1/11
15359	Interior/Exterior Door & Base 4	Trim Enamel S	emi-Gloss		SHW-85-I	NA-GHS-US	

### Section 2. Hazards identification

	This product contains a TSCA regulated chemical. See Section 15 of the US SDS for details.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.
Section 3. Comp	osition/information on ingredients

#### Ai caicilla

#### Substance/mixture : Mixture Other means of

### identification

: Not available.

#### **CAS number/other identifiers**

Ingredient name	% by weight	CAS number
Silica gel, pptd., crystfree	≤3	112926-00-8
Heavy Paraffinic Oil	≤1	64742-65-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	<ul> <li>Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.</li> </ul>
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

#### Most important symptoms/effects, acute and delayed

Potential acute health effects				
Eye contact	: No known significant effects or critical hazards.			
Inhalation	: No known significant effects or critical hazards.			
Skin contact	: No known significant effects or critical hazards.			
Ingestion	: No known significant effects or critical hazards.			
Over-exposure signs/symptoms				
Eye contact	: No specific data.			
Inhalation	: No specific data.			
Skin contact	: No specific data.			
Ingestion	: No specific data.			

Date of issue/Date	of revision	: 11/28/2023	Date of previous issue	: 9/21/2023	Version	:17	2/11
15359	Interior/Exterior Door & Base 4	Trim Enamel S	emi-Gloss		SHW-85-	NA-GHS-US	

### Section 4. First aid measures

Indication of immediate med	lical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

### Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: metal oxide/oxides
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

Personal precautions, protec	<u>tiv</u>	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	•	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	This product contains a TSCA regulated chemical. See Section 15 of the US SDS for details.
		Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	nt	ainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

### Section 6. Accidental release measures

Large spill	: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers,
	water courses, basements or confined areas. Wash spillages into an effluent treatment
	plant or proceed as follows. Contain and collect spillage with non-combustible,
	absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in
	container for disposal according to local regulations (see Section 13). Dispose of via a
	licensed waste disposal contractor. Note: see Section 1 for emergency contact

### Section 7. Handling and storage

#### Precautions for safe handling

r reductions for sure numaring		
Protective measures	:	Put on appropriate personal protective equipment (see Section 8).
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

information and Section 13 for waste disposal.

### Section 8. Exposure controls/personal protection

### **Control parameters**

#### Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Silica gel, pptd., crystfree	112926-00-8	NIOSH REL (United States, 10/2020). [SILICA, AMORPHOUS] TWA: 6 mg/m <sup>3</sup> 10 hours.
Heavy Paraffinic Oil	64742-65-0	OSHA PEL (United States, 5/2018). [Oil mist, mineral] TWA: 5 mg/m <sup>3</sup> 8 hours. ACGIH TLV (United States, 1/2023). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2020). [OIL MIST MINERAL] TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Mist STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: Mist

### Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
None.		

### Occupational exposure limits (Mexico)

	CAS #	Exposure limits
None.		

Date of issue/Date of revision	: 11/28/2023	Date of previous issue	: 9/21/2023	Version : 17	4/11
15359 Interior/Exterior D Base 4	Interior/Exterior Door & Trim Enamel Semi-Gloss Base 4			SHW-85-NA-GHS-US	

### Section 8. Exposure controls/personal protection

### **Biological exposure indices (United States)**

No exposure indices known.

#### **Biological exposure indices (Canada)**

No exposure indices known.

#### **Biological exposure indices (Mexico)**

No exposure indices known.

15359

Base 4

Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Environmental exposure controls	This product contains a TSCA regulated chemical. See Section 15 of the US SDS for details.
	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Body protection	<ul> <li>Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

### Section 9. Physical and chemical properties

Interior/Exterior Door & Trim Enamel Semi-Gloss

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Date of issue/Date of revision	: 11/28/2023 Date of previous issue	: 9/21/2023	Version : 17	5/11
рН	: 9			
Odor threshold	: Not available.			
Odor	: Not available.			
Color	: Not available.			
Physical state	: Liquid.			
Appearance				

SHW-85-NA-GHS-US

### Section 9. Physical and chemical properties

Melting point/freezing point	: N	ot available.		
Boiling point, initial boiling point, and boiling range	: 10	00°C (212°F)		
Flash point	: C	losed cup: Not applicable.		
Evaporation rate	: 0.	: 0.09 (butyl acetate = 1)		
Flammability	: N	ot available.		
Lower and upper explosion limit/flammability limit	: N	ot available.		
Vapor pressure	: 2	3 kPa (17.5 mm Hg)		
Relative vapor density	: 1	[Air = 1]		
Relative density	: 1.	05		
Solubility(ies)	:			
Media		Result		
cold water		Partially soluble		
Partition coefficient: n- octanol/water	: N	ot applicable.		
Auto-ignition temperature	: N	ot available.		
Decomposition temperature	: N	ot available.		
Viscosity	: K	(inematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)		
Molecular weight	: N	lot applicable.		
Heat of combustion	: 1.	208 kJ/g		

### Section 10. Stability and reactivity

	· · · · · · · · · · · · · · · · · · ·
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Heavy Paraffinic Oil	LD50 Dermal LD50 Oral		>5000 mg/kg >5000 mg/kg	-

### Irritation/Corrosion

Not available.

Date of issue/Date	e of revision	: 11/28/2023	Date of previous issue	: 9/21/2023	Version : 17	6/11
15359	······································			SHW-85-NA-GHS-US	;	

### Section 11. Toxicological information

### Sensitization

Not available.

#### **Mutagenicity**

Not available.

### **Carcinogenicity**

Not available.

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Silica gel, pptd., crystfree	-	3	-

#### **Reproductive toxicity**

Not available.

#### Teratogenicity

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Base 4

Name	Result
Heavy Paraffinic Oil	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	: Not available.		
Potential acute health effe	<u>tts</u>		
Eye contact	: No known significant effects or critical hazards.		
Inhalation	: No known significant effects or critical hazards.		
Skin contact	: No known significant effects or critical hazards.		
Ingestion	: No known significant effects or critical hazards.		
Symptoms related to the p	hysical, chemical and toxicological characteristics		
Eye contact	: No specific data.		
Inhalation	: No specific data.		
Skin contact	: No specific data.		
Ingestion	: No specific data.		
Delayed and immediate ef	ects and also chronic effects from short and long term exposur	<u>re</u>	
Short term exposure			
Potential immediate effects	: Not available.		
Potential delayed effects	: Not available.		
Long term exposure			
Potential immediate effects	: Not available.		
Date of issue/Date of revision	: 11/28/2023 Date of previous issue : 9/21/2023	Version : 17	7/11
15359 Interior/Exterior	Door & Trim Enamel Semi-Gloss	SHW-85-NA-GHS-US	

### Section 11. Toxicological information

Potential delayed effects	: Not available.						
Potential chronic health e	Potential chronic health effects						
Not available.							
General	: No known significant effects or critical hazards.						
Carcinogenicity	: No known significant effects or critical hazards.						
Mutagenicity	: No known significant effects or critical hazards.						
Teratogenicity	: No known significant effects or critical hazards.						
Developmental effects	: No known significant effects or critical hazards.						
Fertility effects	: No known significant effects or critical hazards.						

Numerical measures of toxicity Acute toxicity estimates Not available.

### Section 12. Ecological information

#### **Toxicity**

Not available.

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

### Mobility in soil

Soil/water partition: Not available.coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

### Section 13. Disposal considerations

Disposal methods	: This product contains a TSCA regulated chemical. See Section 15 of the US SDS for details.
	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date	of revision	: 11/28/2023	Date of previous issue	: 9/21/2023	Version	:17	8/11
15359	Interior/Exterior Door & Base 4	Trim Enamel Se	emi-Gloss		SHW-85-	NA-GHS-US	

### Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-
Special precautions	consid mode suitabl to ship of the j dangei	nodal shipping descri er container sizes. Th of transport (sea, air, y for that mode of tra ment, and complianc person offering the pr rous goods must be t all actions in case of	he presence of a shi etc.), does not indic nsport. All packagin e with the applicable oduct for transport. rained on all of the r	pping description for ate that the produce g must be reviewed regulations is the People loading and isks deriving from t	or a particular t is packaged d for suitability prior sole responsibility d unloading
ransport in bulk ac o IMO instruments	cording : Not ava	lable.			
	Broper	shipping name	: Not available.		

U.S. Federal regulations : TSCA 5(a)2 proposed significant new use rules: 2-Methyl-4-isothiazolin-3-one; reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

### TSCA 5(a)2 final significant new use rules: Chlorodiazocarboxylate

<u>List name</u>	Chemical name	<u>Notes</u>
United States - TSCA 5(a) 2 - Final significant new use rules	Chlorodiazocarboxylate	40 CFR 721.10414

### <u>SARA 313</u>

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

### California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

### International regulations

### **Montreal Protocol**

Date of issue/Date	of revision	: 11/28/2023	Date of previous issue	: 9/21/2023	Version : 17	9/11
15359	Interior/Exterior Door 8 Base 4	& Trim Enamel S	Semi-Gloss		SHW-85-NA-GHS-US	

### Section 15. Regulatory information

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists	: Australia inventory (AIIC): Not determined.
	China inventory (IECSC): Not determined.
	Japan inventory (CSCL): Not determined.
	Japan inventory (ISHL): Not determined.
	Korea inventory (KECI): Not determined.
	New Zealand Inventory of Chemicals (NZIoC): Not determined.
	Philippines inventory (PICCS): Not determined.
	Taiwan Chemical Substances Inventory (TCSI): Not determined.
	Thailand inventory: Not determined.
	Turkey inventory: Not determined.
	Vietnam inventory: Not determined.

### Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Base 4

	Classification	Justification
Not classified.		
<u>History</u>		
Date of printing	: 11/28/2023	
Date of issue/Date of revision	: 11/28/2023	
Date of previous issue	: 9/21/2023	
Version	: 17	
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification an IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coeffic MARPOL = International Convention for the Prevention of as modified by the Protocol of 1978. ("Marpol" = marine N/A = Not available SGG = Segregation Group UN = United Nations	eient of Pollution From Ships, 1973
ate of issue/Date of revision	: 11/28/2023 Date of previous issue : 9/21/2023	Version : 17 10/11
5359 Interior/Exterior	Door & Trim Enamel Semi-Gloss	SHW-85-NA-GHS-US

### Section 16. Other information

### Indicates information that has changed from previously issued version.

#### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.