SAFETY DATA SHEET

5170

Section 1. Identification

Product name	: Supreme® Interior Eggshell Tint Base
Product code	: 5170
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of th	e substance or mixture and uses advised against
Paint or paint related material.	
Manufacturer	: Valspar 101 W. Prospect Avenue

Cleveland, OH 44115

Emergency telephone number of the company	: (800) 424-9300
Product Information Telephone Number	: 1-877-825-7727
Transportation Emergency Telephone Number	: (800) 424-9300

Section 2. Hazards identification

Supreme® Interior Eggshell

Tint Base

5170

Signal word	- Denger
Signal word Hazard statements	 Danger Suspected of causing cancer. Causes demage to organe through prolonged or repeated expecture. (lungs)
Hazard statements	-
-	: Suspected of causing cancer.
Hazard statements	 Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure. (lungs) Read label before use. Keep out of reach of children. If medical advice is needed, have
Hazard statements Precautionary statements General	 Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure. (lungs) Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Hazard statements Precautionary statements	 Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure. (lungs) Read label before use. Keep out of reach of children. If medical advice is needed, have
Hazard statements <u>Precautionary statements</u> General	 Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure. (lungs) Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Do not breathe vapor. Do not eat, drink or smoke when using this product.

SHW-85-NA-GHS-US

Section 2. Hazards identification

Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture Other means of

: Mixture

identification

: Not available.

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Titanium Dioxide	≤10	13463-67-7
Kaolin	≤10	1332-58-7
Heavy Paraffinic Oil	≤0.3	64742-54-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary	first aid measures
Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most impo	ortant symptoms	/effects, acute an	d delayed			
Potentia	acute health effe	<u>ects</u>				
Eye cor	ntact	: No known s	ignificant effects or critic	al hazards.		
Inhalati	on	: No known s	ignificant effects or critic	al hazards.		
Date of issue	e/Date of revision	: 9/21/2023	Date of previous issue	: 6/15/2023	Version : 15	2/12
5170	Supreme® Inte Tint Base	rior Eggshell			SHW-85-NA-GHS-L	JS

Section 4. First aid measures

Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/s	symptoms
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediate	medical attention and special treatment needed, if necessary
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protect	ve equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions :

Date of issue/Date	e of revision	: 9/21/2023	Date of previous issue	: 6/15/2023	Version : 15	3/12
5170	Supreme® Interior Eg	gshell			SHW-85-NA-GHS-US	
	Tint Base					

Section 6. Accidental release measures

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name		CAS #	Exposure limits OSHA PEL (United States, 5/2018). TWA: 15 mg/m³ 8 hours. Form: Total dust ACGIH TLV (United States, 1/2023). TWA: 2.5 mg/m³ 8 hours. Form: respirable fraction, finescale particles				
Titanium Dioxide		13463-67-7					
Kaolin			1332-58-7		(United States, /m³ 8 hours. For		
Date of issu	e/Date of revision	: 9/21/2023	Date of previous issue	: 6/15/2023	Version	:15	4/12
5170	Supreme® Interic Tint Base	r Eggshell			SHW-85-	NA-GHS-U	JS

Section 8. Exposure controls/personal protection

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
Kaolin	1332-58-7	 CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 2 mg/m³ 8 hours. Form: Respirable CA Quebec Provincial (Canada, 6/2022). TWAEV: 2 mg/m³ 8 hours. Form: Respirable dust. CA Ontario Provincial (Canada, 6/2019). TWA: 2 mg/m³ 8 hours. Form: Respirable particulate matter. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 4 mg/m³ 15 minutes. Form: respirable fraction TWA: 2 mg/m³ 8 hours. Form: respirable fraction CA British Columbia Provincial (Canada, 6/2022). Notes: the value is for particulate matter containing no asbestos and less than 1% crystalline silica. TWA: 2 mg/m³ 8 hours. Form: Respirable

Occupational exposure limits (Mexico)

	CAS #	Exposure limits
None.		
	•	

Date of previous issue

Biological exposure indices (United States)

No exposure indices known.

Biological exposure indices (Canada)

No exposure indices known.

Biological exposure indices (Mexico)

: 9/21/2023

Date	of	issue	/Date	of	revision

Section 8. Exposure controls/personal protection

No exposure indices known.

Appropriate engineering controls Environmental exposure controls	 If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measure	
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
O a attain O Dhuata	

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance	
Physical state	: Liquid.
Color	: Not available.
Odor	: Not available.
Odor threshold	: Not available.
рН	: 9
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: 100°C (212°F)
Flash point	: Closed cup: Not applicable.
Date of issue/Date of revision	: 9/21/2023 Date of previous issue

 Date of issue/Date of revision
 : 9/21/2023
 Date of previous issue
 : 6/15/2023
 Version
 : 15
 6/12

 5170
 Supreme® Interior Eggshell Tint Base
 SHW-85-NA-GHS-US
 SHW-85-NA-GHS-US

Section 9. Physical and chemical properties

Evaporation rate	: 0.0	09 (butyl acetate = 1)		
Flammability	: No	Not available.		
Lower and upper explosion limit/flammability limit	: No	Not available.		
Vapor pressure	: 2.3	3 kPa (17.5 mm Hg)		
Relative vapor density	: 1[Air = 1]		
Relative density	: 1.2	2		
Solubility(ies)	:			
Media		Result		
cold water		Partially soluble		
Partition coefficient: n- octanol/water	: No	ot applicable.		
Auto-ignition temperature	: No	ot available.		
Decomposition temperature	: No	ot available.		
Viscosity	: Ki	nematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)		
Molecular weight	: No	ot applicable.		
Heat of combustion	: 0.5	544 kJ/g		

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300	-
				ug l	

Sensitization

Not available.

Mutagenicity

Not available.

Date of issue/Date	of revision	: 9/21/2023	Date of previous issue	: 6/15/2023	Version : 15	7/12
5170	Supreme® Interior Egg Tint Base	shell			SHW-85-NA-GHS-US	

Section 11. Toxicological information

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Supreme® Interior Eggshell

. Tint Base . . .

.. . .

Name		Route of exposure	Target organs
Kaolin	Category 1	inhalation	lungs

Aspiration hazard

5170

Name	Result
Heavy Paraffinic Oil	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	:	Not available.							
Potential acute health effe	cts								
Eye contact	:	No known significant	effects or critical	hazards.					
Inhalation	1	No known significant	effects or critical	hazards.					
Skin contact	: No known significant effects or critical hazards.								
Ingestion	:	: No known significant effects or critical hazards.							
Symptoms related to the p	ohy	ical, chemical and t	toxicological cha	racteristics					
Eye contact	:	No specific data.							
Inhalation	:	No specific data.							
Skin contact	1	No specific data.							
Ingestion	:	No specific data.							
Delayed and immediate ef	fec	s and also chronic	effects from sho	rt and long term e	<u>xposure</u>				
Short term exposure				-					
Potential immediate effects	:	Not available.							
Potential delayed effects	:	Not available.							
Long term exposure									
Potential immediate effects	:	Not available.							
Potential delayed effects	:	Not available.							
Potential chronic health ef	ffec	t <u>s</u>							
Date of issue/Date of revision		: 9/21/2023 Date o	f previous issue	: 6/15/2023	Version	:15	8/12		

Section 11. Toxicological information

Not available.

General	: Causes damage to organs through prolonged or repeated exposure.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity Acute toxicity estimates Not available.

Section 12. Ecological information

ToxicityProduct/ingredient nameResultSpeciesExposureTitanium DioxideAcute LC50 >100000 µg/l Marine waterFish - Fundulus heteroclitus96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition	: Not available.
coefficient (Koc)	

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Date of issu	ue/Date of revision	: 9/21/2023	Date of previous issue	: 6/15/2023	Version : 15	9/12
5170	5170 Supreme® Interior Eggshell				SHW-85-NA-GHS-US	
	Tint Base					

Section 14. Transport information

UN proper shipping nameTransport hazard class(es)Packing groupEnvironmental hazardsAdditional	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
shipping nameTransport hazard class(es)Packing groupEnvironmental hazardsAdditional	-	-	_		
hazard class(es)Packing groupEnvironmental hazardsAdditional				-	-
Environmental hazards Additional	-	-	-	-	-
hazards Additional	-	-	-	-	-
	No.	No.	No.	No.	No.
information	-	-	-	-	-
Special precautions f ransport in bulk acc o IMO instruments	conside mode of suitably to shipm of the pe dangero and on a	odal shipping descrip r container sizes. Th f transport (sea, air, for that mode of tran nent, and compliance erson offering the pro- ous goods must be tr all actions in case of able.	e presence of a ship etc.), does not indica isport. All packaging with the applicable oduct for transport. I ained on all of the ri	oping description for ate that the product g must be reviewed to regulations is the se People loading and sks deriving from th	a particular is packaged for suitability prior ple responsibility unloading

Section 15. Regulatory information

TSCA 5(a)2 proposed significant new use rules: 2-Methyl-4-isothiazolin-3-one; reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Date of issu	e/Date of revision	: 9/2
5170	Supreme® Interior	Eggshell
	Tint Base	

: 6/15/2023

Section 15. Regulatory information

International lists	: Australia inventory (AIIC): Not determined.
	China inventory (IECSC): Not determined.
	Japan inventory (CSCL): Not determined.
	Japan inventory (ISHL): Not determined.
	Korea inventory (KECI): Not determined.
	New Zealand Inventory of Chemicals (NZIoC): Not determined.
	Philippines inventory (PICCS): Not determined.
	Taiwan Chemical Substances Inventory (TCSI): Not determined.
	Thailand inventory: Not determined.
	Turkey inventory: Not determined.
	Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

		Justification
CARCINOGENICITY - Catego SPECIFIC TARGET ORGAN	Calculation method Calculation method	
<u>History</u>		
Date of printing	: 9/21/2023	
Date of issue/Date of revision	: 9/21/2023	
Date of previous issue	: 6/15/2023	
Version	: 15	
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification a IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coeff MARPOL = International Convention for the Preventior as modified by the Protocol of 1978. ("Marpol" = marine N/A = Not available SGG = Segregation Group UN = United Nations	icient of Pollution From Ships, 1973

Indicates information that has changed from previously issued version.

Notice to reader

Date of issue/Date	of revision	: 9/21/2023	Date of previous issue	: 6/15/2023	Version	:15	11/12
5170	Supreme® Interior Egg Tint Base	shell			SHW-85-	NA-GHS-US	

Section 16. Other information

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

12/12