SAFETY DATA SHEET

6001-382

Section 1. Identification

Product name	: Integrity® Paint and Primer Satin Exterior Clear Base
Product code	: 6001-382
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of	the substance or mixture and uses advised against
Paint or paint related materia	I.
Manufacturer	: Valspar 101 W. Prospect Avenue Cleveland, OH 44115
Emergency telephone number of the company	: (800) 424-9300

Product Information Telephone Number	:	1-877-825-7727
Transportation Emergency Telephone Number	:	(800) 424-9300

Clear Base

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).				
Classification of the substance or mixture	: CARCINOGENICITY - Category 2				
GHS label elements					
Hazard pictograms					
Signal word	: Warning				
Hazard statements	: Suspected of causing cancer.				
Precautionary statements					
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.				
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection.				
Response	IF exposed or concerned: Get medical advice or attention.				
Storage	Store locked up.				
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations. 				
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.				
Date of issue/Date of revision 6001-382 Integrity® Pain	: 2/5/2024 Date of previous issue : 10/31/2023 Version : 13.02 1/11 : and Primer Satin Exterior SHW-85-NA-GHS-US SHW-85-NA-GHS-US 1/11				

Section 2. Hazards identification

Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.

Hazards not otherwise classified

Section 3. Composition/information on ingredients

: None known.

Substance/mixture	: Mixture
Other means of identification	: Not available.

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Titanium Dioxide	≤1	13463-67-7
Heavy Paraffinic Oil	≤1	64742-65-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health	<u>n effects</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/	/symptoms
Eye contact	: No specific data.

Date of issue/Date	of revision	: 2/5/2024	Date of previous issue	: 10/31/2023	Version	:13.02	2/11
6001-382 Integrity® Paint and Primer Satin Exterior Clear Base					SHW-85-	NA-GHS-US	

Section 4. First aid measures

Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediate mee	dical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Date of issue/Date	e of revision	: 2/5/2024	Date of previous issue	: 10/31/2023	Version : 13.0	02 3/11
6001-382 Integrity® Paint and Primer Satin Exterior Clear Base			erior		SHW-85-NA-GH	IS-US

Section 6. Accidental release measures

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredien	t name		CAS #	Exposure limits		
Titanium Dioxide			13463-67-7	OSHA PEL (United States, 5/2018). TWA: 15 mg/m ³ 8 hours. Form: Total dust ACGIH TLV (United States, 1/2023). TWA: 2.5 mg/m ³ 8 hours. Form: respirable fraction, finescale particles		
Heavy Par	raffinic Oil		64742-65-0	mist, mineral TWA: 5 mg/r ACGIH TLV (I [Mineral Oil,] refined]	-	
Date of issue/	Date of revision	: 2/5/2024	Date of previous issue	: 10/31/2023	Version : 13.02 4/11	
6001-382	Integrity® Paint a Clear Base	and Primer Satin Exte	erior		SHW-85-NA-GHS-US	

Section 8. Exposure controls/personal protection

	NIOSH REL (United States, 10/2020). [OIL MIST MINERAL] TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist
--	---

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
None.		

Occupational exposure limits (Mexico)

	CAS #	Exposure limits
None.		

Biological exposure indices (United States)

No exposure indices known.

Biological exposure indices (Canada)

No exposure indices known.

Biological exposure indices (Mexico)

No exposure indices known.

Appropriate engineering : If user of local ex

- : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Environmental exposure controls
 Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Date of issue/Dat	e of revision	: 2/5/2024	Date of previous issue	: 10/31/2023	Version : 1	13.02	5/11
6001-382 Integrity® Paint and Primer Satin Exter		erior		SHW-85-NA	-GHS-US		
	Clear Base						

Section 8. Exposure controls/personal protection

Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	:	Liqu	id.		
Color	:	: Not available.			
Odor	:	: Not available.			
Odor threshold	:	Not available.			
рН	:	9			
Melting point/freezing point	:	Not	available.		
Boiling point, initial boiling point, and boiling range	1	100°C (212°F)			
Flash point	:	Clos	ed cup: Not applicable.		
Evaporation rate	:	0.09	(butyl acetate = 1)		
Flammability	:	: Not available.			
Lower and upper explosion limit/flammability limit	1	: Lower: 0.6% Upper: 4.2%			
Vapor pressure	:	: 2.3 kPa (17.5 mm Hg)			
Relative vapor density	:	: 1 [Air = 1]			
Relative density	:	: 1.09			
Solubility(ies)	:				
Media			Result		
cold water			Partially soluble		
Partition coefficient: n- octanol/water	:	Not applicable.			
Auto-ignition temperature	: Not available.				
Decomposition temperature	: Not available.				
Viscosity	: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)				
Molecular weight	:	Not	applicable.		
Heat of combustion	:	1.46	8 kJ/g		

Section 10. Stability and reactivity

 Reactivity
 : No specific test data related to reactivity available for this product or its ingredients.

 Chemical stability
 : The product is stable.

 Possibility of hazardous reactions
 : Under normal conditions of storage and use, hazardous reactions will not occur.

Date of issue/Date	e of revision	: 2/5/2024	Date of previous issue	: 10/31/2023	Version : 13.0	02 6/11
6001-382	Integrity® Paint and P Clear Base	rimer Satin Exte	erior		SHW-85-NA-GI	HS-US

Section 10. Stability and reactivity			
Conditions to avoid	: No specific data.		
Incompatible materials	: No specific data.		
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.		

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Heavy Paraffinic Oil	LD50 Dermal LD50 Oral		>5000 mg/kg >5000 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human		72 hours 300 ug l	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Name	Result
Heavy Paraffinic Oil	ASPIRATION HAZARD - Category 1

Information on the likely : Not available.

routes of exposure

Potential acute health effects

Eye contact

: No known significant effects or critical hazards.

Date of issue/Date	of revision	: 2/5/2024	Date of previous issue	: 10/31/2023	Version	:13.02	7/11
6001-382	Integrity® Paint and P Clear Base	rimer Satin Ext	erior		SHW-85-	NA-GHS-US	

Section 11. Toxicological information

Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the p	physical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Delayed and immediate ef	fects and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health ef	ffects
Not available.	
General	: No known significant effects or critical hazards.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level or exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity Acute toxicity estimates Not available.

Section 12. Ecological information

<u>Toxicity</u>			
Product/ingredient name	Result	Species	Exposure
Titanium Dioxide	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Date of issue/Date	e of revision	: 2/5/2024	Date of previous issue	: 10/31/2023	Version : 13.02	8/11
6001-382 Integrity® Paint and Primer Satin Exterior Clear Base		erior		SHW-85-NA-GHS-US		

Section 12. Ecological information

Mobility in soil

Soil/water partition
coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods
 The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-
Special precautions	conside mode o suitably to shipn of the p dangero	l odal shipping descripter odal shipping descripter f container sizes. The f transport (sea, air, for that mode of transform for that mode of transform nent, and compliance erson offering the propus goods must be transform all actions in case of	ne presence of a shi etc.), does not indic nsport. All packaging e with the applicable oduct for transport. rained on all of the r	pping description for ate that the product g must be reviewed regulations is the s People loading and isks deriving from th	a particular is packaged for suitability prior ole responsibility unloading
	rity® Paint and Primer Satin		issue : 10/31/20		on : 13.02 9/ 1-85-NA-GHS-US

Section 14. Transport information

Transport in bulk according : Not available. to IMO instruments

Proper shipping name

: Not available.

Section 15. Regulatory information

TSCA 5(a)2 proposed significant new use rules: 2-Methyl-4-isothiazolin-3-one; reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet, where applicable.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists	: Australia inventory (AIIC): Not determined.
	China inventory (IECSC): Not determined.
	Japan inventory (CSCL): Not determined.
	Japan inventory (ISHL): Not determined.
	Korea inventory (KECI): Not determined.
	New Zealand Inventory of Chemicals (NZIoC): Not determined.
	Philippines inventory (PICCS): Not determined.
	Taiwan Chemical Substances Inventory (TCSI): Not determined.
	Thailand inventory: Not determined.
	Turkey inventory: Not determined.
	Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification
CARCINOGENICITY - Category 2	Calculation method

History

Date of issue/Date of revision		: 2/5/2024	Date of previous issue	: 10/31/2023	Version	:13.02	10/11
6001-382	Integrity® Paint and Pri Clear Base	mer Satin Exter	or		SHW-85-	NA-GHS-US	

Section 16. Other information

Date of printing	: 2/5/2024
Date of issue/Date of revision	: 2/5/2024
Date of previous issue	: 10/31/2023
Version	: 13.02
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations

Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.