SAFETY DATA SHEET

6004-287

Section 1. Identification

Product name	: Integrity® Paint and Primer Semi-Gloss Exterior Pastel Base
Product code	: 6004-287
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of	the substance or mixture and uses advised against
Paint or paint related materia	l.
Manufacturer	: Valspar 101 W. Prospect Avenue Cleveland, OH 44115
Emergency telephone number of the company	: (800) 424-9300

Product Information Telephone Number	1	1-877-825-7727
Transportation Emergency Telephone Number	;	(800) 424-9300

Pastel Base

Section 2. Hazards identification

Date of issue/Date of revision6004-287Integrity® Paint	: 2/5/2024 Date of previous issue : 11/1/2023 and Primer Semi-Gloss Exterior	Version : 16 1/13 SHW-85-NA-GHS-US
Storage	: Store locked up.	
Response	: IF exposed or concerned: Get medical advice or attentior	۱.
Prevention	: Obtain special instructions before use. Do not handle un been read and understood. Wear protective gloves, prote protection. Do not breathe vapor. Do not eat, drink or sn Wash thoroughly after handling.	ective clothing and eye or face noke when using this product.
General	: Read label before use. Keep out of reach of children. If product container or label at hand.	
Precautionary statements		
Hazard statements	: Suspected of causing cancer. Causes damage to organs through prolonged or repeated	d exposure. (lungs)
Signal word	: Danger	
Hazard pictograms		
GHS label elements	Percentage of the mixture consisting of ingredient(s) of u (oral), 3.1% (dermal), 3.1% (inhalation)	nknown acute toxicity: 3.1%
Classification of the substance or mixture	: CARCINOGENICITY - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED E)	, .
OSHA/HCS status	: This material is considered hazardous by the OSHA Haza (29 CFR 1910.1200).	ard Communication Standard

Section 2. Hazards identification

Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture Other means of

: Mixture

identification

: Not available.

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Titanium Dioxide	≥10 - ≤25	13463-67-7
Kaolin	≤5	1332-58-7
Heavy Paraffinic Oil	≤1	64742-65-0

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary f	rst aid measures
Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most importa	ant symptoms/	<u>effects, acute ar</u>	<u>nd delayed</u>			
Potential ac	ute health effe	<u>cts</u>				
Eye contac	ct	: No known s	significant effects or critic	al hazards.		
Inhalation		: No known s	significant effects or critic	al hazards.		
Date of issue/Da	te of revision	: 2/5/2024	Date of previous issue	: 11/1/2023	Version : 16	2/13
6004-287	Integrity® Paint Pastel Base	and Primer Semi-Glo	ss Exterior		SHW-85-NA-GHS-U	s

Section 4. First aid measures

Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
<u>Over-exposure signs/symp</u>	<u>otoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediate med	lical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Section 6. Accidental release measures

Personal precautions, protect	ve equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions :

Date of issue/Date	of revision	: 2/5/2024	Date of previous issue	: 11/1/2023	Version : 16	3/13
6004-287	Integrity® Paint and P Pastel Base	rimer Semi-Glo	ss Exterior		SHW-85-NA-GHS-US	

Section 6. Accidental release measures

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient	name		CAS #	Exposure lim	its	
Titanium D	ioxide		13463-67-7	TWA: 15 m ACGIH TLV TWA: 2.5 m	United States, 5/2018). g/m ³ 8 hours. Form: Total dus (United States, 1/2023). g/m ³ 8 hours. Form: respirab scale particles	
Kaolin			1332-58-7		(United States, 1/2023). /m³ 8 hours. Form: Respirable	э
Date of issue/D	ate of revision	: 2/5/2024	Date of previous issue	: 11/1/2023	Version : 16	4/13
6004-287	Integrity® Paint a Pastel Base	nd Primer Semi-Glo	ss Exterior		SHW-85-NA-GHS-US	

Section 8. Exposure controls/personal protection

TWA: 5 m fraction TWA: 10 r	
Heavy Paraffinic Oil Heavy Paraffinic Oil Heavy Paraffinic Oil Heavy Paraffinic Oil Heavy Paraffinic Oil 64742-65-0 OSHA PEL mist, mine TWA: 5 m ACGIH TLV [Mineral O refined] TWA: 5 m fraction NIOSH REI MIST MINE TWA: 5 m	g/m ³ 8 hours. 7 (United States, 1/2023). I, pure, highly and severely g/m ³ 8 hours. Form: Inhalable . (United States, 10/2020). [OIL

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits	
Kaolin	1332-58-7	 CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 2 mg/m³ 8 hours. Form: Respirable CA Quebec Provincial (Canada, 6/2022). TWAEV: 2 mg/m³ 8 hours. Form: Respirable dust. CA Ontario Provincial (Canada, 6/2019). TWA: 2 mg/m³ 8 hours. Form: Respirable particulate matter. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 4 mg/m³ 15 minutes. Form: respirable fraction TWA: 2 mg/m³ 8 hours. Form: respirable fraction CA British Columbia Provincial (Canada, 6/2022). Notes: the value is for particulate matter containing no asbestos and less than 1% crystalline silica. TWA: 2 mg/m³ 8 hours. Form: Respirable 	
diuron (ISO)	330-54-1	 CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 10 mg/m³ 8 hours. CA British Columbia Provincial (Canada, 6/2022). TWA: 10 mg/m³ 8 hours. CA Ontario Provincial (Canada, 6/2019). TWA: 10 mg/m³ 8 hours. CA Quebec Provincial (Canada, 6/2022). TWAEV: 10 mg/m³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 20 mg/m³ 15 minutes. TWA: 10 mg/m³ 8 hours. 	

6004-287 Integrity® Paint and Primer Semi-Gloss Exterior Pastel Base

SHW-85-NA-GHS-US

Section 8. Exposure controls/personal protection

Occupational exposure limits (Mexico)

		CAS #	Exposure limits	
diuron (ISO)		330-54-1	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 10 mg/m ³ 8 hours.	
Biological exposure indice	s (United States	<u>5)</u>		
No exposure indices known				
Biological exposure indice	s (Canada)			
No exposure indices known				
Biological exposure indice	s (Mexico)			
No exposure indices known				
··· ·· · · · · · · · · · · · · · · · ·				
Appropriate engineering controls	local exhau	st ventilation or other eng	nes, gas, vapor or mist, use process enclosures, gineering controls to keep worker exposure to commended or statutory limits.	
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.			
ndividual protection measu	ures			
Hygiene measures	eating, smo Appropriate Wash conta	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.		
Eye/face protection	assessmen gases or du	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.		
Skin protection				
Hand protection	worn at all t necessary. during use noted that t glove manu	Chemical-resistant, impervious gloves complying with an approved standard should b worn at all times when handling chemical products if a risk assessment indicates this necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for differen glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.		
Body protection	performed	Personal protective equipment for the body should be selected based on the task be performed and the risks involved and should be approved by a specialist before handling this product.		
Other skin protection	based on th		onal skin protection measures should be selected and the risks involved and should be approved by ct.	
Respiratory protection	appropriate	standard or certification. protection program to en	or exposure, select a respirator that meets the Respirators must be used according to a sure proper fitting, training, and other important	

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Not available.
Odor	: Not available.
Odor threshold	: Not available.
рН	: 9
Melting point/freezing point	: Not available.
Boiling point, initial boiling point, and boiling range	: 100°C (212°F)
Flash point	: Closed cup: Not applicable.
Flash point Evaporation rate	Closed cup: Not applicable.0.09 (butyl acetate = 1)
Evaporation rate	: 0.09 (butyl acetate = 1)
Evaporation rate Flammability Lower and upper explosion	0.09 (butyl acetate = 1)Not available.
Evaporation rate Flammability Lower and upper explosion limit/flammability limit	 0.09 (butyl acetate = 1) Not available. Not available.
Evaporation rate Flammability Lower and upper explosion limit/flammability limit Vapor pressure	 0.09 (butyl acetate = 1) Not available. Not available. 2.3 kPa (17.5 mm Hg)

Media		Result
cold water		Partially soluble
Partition coefficient: n- octanol/water	: Not	applicable.
Auto-ignition temperature	: Not available.	
Decomposition temperature	e : Not available.	
Viscosity	: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)	
Molecular weight	: Not applicable.	
Heat of combustion : 1.357 kJ		57 kJ/g

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Date of issue/Date of revision		: 2/5/2024	Date of previous issue	: 11/1/2023	Version : 16	7/13
6004-287	Integrity® Paint and Primer Semi-Gloss Exterior Pastel Base		ss Exterior		SHW-85-NA-GHS-US	

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Heavy Paraffinic Oil	LD50 Dermal LD50 Oral		>5000 mg/kg >5000 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Kaolin	Category 1	inhalation	lungs

Aspiration hazard

Name	Result
Heavy Paraffinic Oil	ASPIRATION HAZARD - Category 1

or critical hazards. or critical hazards. or critical hazards.

: Not available.
<u>cts</u>
: No known significant effects
: No known significant effects
: No known significant effects

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Date of issue/Date	of revision	: 2/5/2024	Date of previous issue	: 11/1/2023	Version : 16	8/13
6004-287 Integrity® Paint and Primer Semi-Gloss Exterior Pastel Base				SHW-85-NA-GHS-US		

Section 11. Toxicological information

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Delayed and immediate ef	fects and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health et	ffects
Not available.	
General	: Causes damage to organs through prolonged or repeated exposure.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity Acute toxicity estimates Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium Dioxide	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Date of issue/Date	e of revision	: 2/5/2024	Date of previous issue	: 11/1/2023	Version : 16	9/13
6004-287	Integrity® Paint and Pr Pastel Base	rimer Semi-Glo	ss Exterior		SHW-85-NA-GHS	-US

Section 12. Ecological information

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

```
Disposal methods
```

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	UN3082	UN3082
UN proper shipping name	-	-	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Zinc Pyrithione, Diuron)	ENVIRONMENTALL HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Zinc Pyrithione, Diuron). Marine pollutant (Zinc Pyrithione, Diuror
Transport hazard class(es)	-	-	-	9 • • • •	9
Packing group	-	-	-	Ш	ш
Environmental hazards	No.	No.	No.	Yes.	Yes.
Additional information	-	-	-	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.	This product is no regulated as a dangerous good when transported in sizes of ≤ 5 L or ≤ 5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Emergency
	rision : 2/5/202 rity® Paint and Primer Semi el Base		issue : 11/1/202		on : 16 10, - 85-NA-GHS-US

Section 14. Transport information						
				<u>schedules</u> F-A, S- F		
Special precautions for user	: Multi-modal shipping descri consider container sizes. The mode of transport (sea, air, suitably for that mode of tra to shipment, and compliance of the person offering the per dangerous goods must be to and on all actions in case of	ne presence of a ship etc.), does not indica nsport. All packaging e with the applicable oduct for transport. F rained on all of the ri	pping description for ate that the product i must be reviewed f regulations is the so People loading and u sks deriving from the	a particular s packaged for suitability prior ble responsibility unloading		
Transport in bulk according to IMO instruments	: Not available.					
	Proper shipping name	: Not available.				

Section 15. Regulatory information

TSCA 5(a)2 proposed significant new use rules: 2-Methyl-4-isothiazolin-3-one; reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet, where applicable.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

International lists

: Australia inventory (AIIC): Not determined. China inventory (IECSC): Not determined. Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined. Korea inventory (KECI): Not determined. New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): Not determined. Taiwan Chemical Substances Inventory (TCSI): Not determined. Thailand inventory: Not determined. Turkey inventory: Not determined. Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

	Classification	Justification
CARCINOGENICITY - Cat SPECIFIC TARGET ORG	Calculation method Calculation method	
<u>History</u>		
Date of printing	: 2/5/2024	
Date of issue/Date of revision	: 2/5/2024	
Date of previous issue	: 11/1/2023	
Version	: 16	
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coe MARPOL = International Convention for the Prevention as modified by the Protocol of 1978. ("Marpol" = marin N/A = Not available SGG = Segregation Group UN = United Nations	fficient on of Pollution From Ships, 1973

Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs

Date of issue/Date	of revision	: 2/5/2024	Date of previous issue	: 11/1/2023	Version	:16	12/13
6004-287	Integrity® Paint and Primer Semi-Gloss Exterior Pastel Base				SHW-85-	NA-GHS-US	i
	Fastel Dase						

Section 16. Other information

obtained from any other source.