SAFETY DATA SHEET

65000

Section 1. Identification **Product name** : PRO-HIDE® GOLD ULTRA Exterior Flat White **Product code** : 65000 Other means of : Not available. identification **Product type** : Liquid. Relevant identified uses of the substance or mixture and uses advised against Paint or paint related material. Manufacturer : Valspar 101 W. Prospect Avenue Cleveland, OH 44115 **Emergency telephone** : (800) 424-9300 number of the company **Product Information** : 1-877-825-7727 **Telephone Number** Transportation Emergency : (800) 424-9300 **Telephone Number** Section 2. Hazards identification **OSHA/HCS** status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). : CARCINOGENICITY - Category 1A **Classification of the** SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 substance or mixture Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 11.6% (oral), 11.6% (dermal), 11.6% (inhalation) **GHS label elements** Hazard pictograms Signal word : Danger **Hazard statements** : May cause cancer. Causes damage to organs through prolonged or repeated exposure. **Precautionary statements** General : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. **Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. : IF exposed or concerned: Get medical advice or attention. Response Storage : Store locked up.

| Date of issue/Date | of revision | : 2/5/2024 | Date of previous issue | : 10/1/2023 | Version | :4 | 1/13 |
|--------------------|---|------------|------------------------|-------------|---------|-----------|------|
| 65000 | 00 PRO-HIDE® GOLD ULTRA Exterior Fl. White | | at | | SHW-85- | NA-GHS-US | |

Section 2. Hazards identification

| Disposal | : Dispose of contents and container in accordance with all local, regional, national and international regulations. |
|----------------------------------|--|
| Supplemental label elements | WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure. |
| | Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage. |
| Hazards not otherwise classified | : None known. |

Section 3. Composition/information on ingredients

| Substance/mixture | : Mixture |
|-------------------|------------------|
| Other means of | : Not available. |
| identification | |

CAS number/other identifiers

| Ingredient name | % by weight | CAS number |
|---------------------------------------|-------------|------------|
| Titanium Dioxide | ≥10 - ≤25 | 13463-67-7 |
| Crystalline Silica, respirable powder | ≥10 - ≤25 | 14808-60-7 |
| Amorphous Diatomaceous Earth | ≤3 | 7631-86-9 |
| Heavy Paraffinic Oil | ≤1 | 64742-54-7 |
| Benzophenone | ≤0.3 | 119-61-9 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

| Eye contact | Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. |
|--------------|---|
| Inhalation | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
| Skin contact | Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse. |

Section 4. First aid measures

| Section 4. First a | | | |
|-----------------------------|---|--|--|
| Ingestion | : Wash out mouth with water. Remove dentures if any. If material has been swallow and the exposed person is conscious, give small quantities of water to drink. Stop i exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery pos and get medical attention immediately. Maintain an open airway. Loosen tight cloth such as a collar, tie, belt or waistband. | | |
| Most important symptoms/ | effects, acute and delayed | | |
| Potential acute health effe | <u>cts</u> | | |
| Eye contact | : No known significant effects or critical hazards. | | |
| Inhalation | : No known significant effects or critical hazards. | | |
| Skin contact | : No known significant effects or critical hazards. | | |
| Ingestion | : No known significant effects or critical hazards. | | |
| Over-exposure signs/sym | <u>ptoms</u> | | |
| Eye contact | : No specific data. | | |
| Inhalation | : No specific data. | | |
| Skin contact | : No specific data. | | |
| Ingestion | : No specific data. | | |
| Indication of immediate me | dical attention and special treatment needed, if necessary | | |
| Notes to physician | Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. | | |
| Specific treatments | : No specific treatment. | | |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. | | |

See toxicological information (Section 11)

White

Section 5. Fire-fighting measures

| Extinguishing media | | | | |
|--|---|------|--|--|
| Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. | | | |
| Unsuitable extinguishing media | : None known. | | | |
| Specific hazards arising from the chemical | : In a fire or if heated, a pressure increase will occur and the container may burst. | | | |
| Hazardous thermal decomposition products | Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides | | | |
| Special protective actions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. | | | |
| Date of issue/Date of revision | : 2/5/2024 Date of previous issue : 10/1/2023 Version : 4 | 3/13 | | |
| 65000 PRO-HIDE® GO | LD ULTRA Exterior Flat SHW-85-NA-GHS-US | | | |

Section 5. Fire-fighting measures

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

| Personal precautions, protec | <u>tiv</u> | e equipment and emergency procedures |
|--------------------------------|------------|--|
| For non-emergency personnel | : | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
| For emergency responders | : | If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| Environmental precautions | : | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). |
| Methods and materials for co | nt | ainment and cleaning up |
| Small spill | : | Stop leak if without risk. Move containers from spill area. Dilute with water and mop up |

place in an appropriate waste disposal container. Dispose of via a licensed waste
disposal contractor.Large spill: Stop leak if without risk. Move containers from spill area. Approach release from
upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash
spillages into an effluent treatment plant or proceed as follows. Contain and collect
spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or
diatomaceous earth and place in container for disposal according to local regulations
(see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated
absorbent material may pose the same hazard as the spilled product. Note: see
Section 1 for emergency contact information and Section 13 for waste disposal.

if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and

Section 7. Handling and storage

| Precautions for safe handlin | iā. |
|--|--|
| Protective measures | : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. |
| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |

Section 7. Handling and storage

| Conditions for safe storage, | : Store in accordance with local regulations. Store in original container protected from |
|------------------------------|---|
| including any | direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials |
| incompatibilities | (see Section 10) and food and drink. Store locked up. Keep container tightly closed |
| - | and sealed until ready for use. Containers that have been opened must be carefully |
| | resealed and kept upright to prevent leakage. Do not store in unlabeled containers. |
| | Use appropriate containment to avoid environmental contamination. See Section 10 for |
| | incompatible materials before handling or use. |

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

| Ingredient name | CAS # | Exposure limits |
|---------------------------------------|------------|--|
| Titanium Dioxide | 13463-67-7 | OSHA PEL (United States, 5/2018). TWA: 15 mg/m ³ 8 hours. Form: Total dust ACGIH TLV (United States, 1/2023). TWA: 2.5 mg/m ³ 8 hours. Form: respirable fraction, finescale particles |
| Crystalline Silica, respirable powder | 14808-60-7 | OSHA PEL Z3 (United States, 6/2016). TWA: 250 mppcf / (%SiO2+5) 8 hours. Form Respirable TWA: 10 mg/m³ / (%SiO2+2) 8 hours. Form: Respirable OSHA PEL (United States, 5/2018). [Silica, crystalline] TWA: 50 μg/m³ 8 hours. Form: Respirable dust ACGIH TLV (United States, 1/2023). [Silica, crystalline] TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction NIOSH REL (United States, 10/2020). [SILICA, CRYSTALLINE (AS RESPIRABLE DUST)] TWA: 0.05 mg/m³ 10 hours. Form: respirable dust |
| Amorphous Diatomaceous Earth | 7631-86-9 | NIOSH REL (United States, 10/2020). [SILICA, AMORPHOUS] TWA: 6 mg/m ³ 10 hours. |
| Heavy Paraffinic Oil | 64742-54-7 | OSHA PEL (United States, 5/2018). [Oil mist, mineral] TWA: 5 mg/m ³ 8 hours. ACGIH TLV (United States, 1/2023). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2020). [OIL MIST MINERAL] TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist |
| Benzophenone | 119-61-9 | OARS WEEL (United States, 4/2022). TWA: 0.5 mg/m ³ 8 hours. |

Occupational exposure limits (Canada)

| Date of iss | sue/Date of revision | : 2/5/2024 | Date of previous issue | : 10/1/2023 | Version : 4 | 5/13 |
|-------------|-------------------------|------------------|------------------------|-------------|------------------|------|
| 65000 | PRO-HIDE® GOLI White | D ULTRA Exterior | Flat | | SHW-85-NA-GHS-US | |

Section 8. Exposure controls/personal protection

| | - | |
|-----------------|------------|--|
| Ingredient name | CAS # | Exposure limits |
| Quartz | 14808-60-7 | CA British Columbia Provincial (Canada, 6/2022). [Silica, Crystalline - alpha quartz and Cristobalite Respirable] TWA: 0.025 mg/m³ 8 hours. Form: Respirable CA Quebec Provincial (Canada, 6/2022). [Silica Crystalline -Quartz] TWAEV: 0.1 mg/m³ 8 hours. Form: Respirable dust. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 0.025 mg/m³ 8 hours. Form: Respirable particulate CA Ontario Provincial (Canada, 6/2019). [Silica, Crystalline (Quartz/Tripoli)] TWA: 0.1 mg/m³ 8 hours. Form: Respirable particulate matter. CA Saskatchewan Provincial (Canada, 7/2013). TWA: 0.05 mg/m³ 8 hours. Form: respirable fraction |
| Benzophenone | 119-61-9 | OARS WEEL (United States, 4/2022). TWA: 0.5 mg/m ³ 8 hours. |

Occupational exposure limits (Mexico)

| | CAS # | Exposure limits |
|---------------------------------------|-------|--|
| Crystalline Silica, respirable powder | | NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction |

Biological exposure indices (United States)

No exposure indices known.

Biological exposure indices (Canada)

No exposure indices known.

Biological exposure indices (Mexico)

No exposure indices known.

| Appropriate engineering controls | If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. |
|----------------------------------|--|
| Environmental exposure controls | Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. |
| Individual protection measure | |
| Hygiene measures | Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety |

| Date of issue/Da | te of revision | : 2/5/2024 | Date of previous issue | : 10/1/2023 | Version : 4 | 6/13 |
|------------------|-------------------------|------------------|------------------------|-------------|------------------|------|
| 65000 | PRO-HIDE® GOLE White | 0 ULTRA Exterior | Flat | | SHW-85-NA-GHS-US | |

showers are close to the workstation location.

Section 8. Exposure controls/personal protection

| | • • |
|------------------------|--|
| Eye/face protection | : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. |
| Skin protection | |
| Hand protection | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
| Body protection | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Other skin protection | : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. |

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

| Appearance | | | | | | | | |
|---|--|-------------------------------|-------------|-------------|------|--|--|--|
| Physical state | : Liqu | id. | | | | | | |
| Color | : Whi | te. | | | | | | |
| Odor | : Not | available. | | | | | | |
| Odor threshold | : Not | available. | | | | | | |
| рН | : 9 | | | | | | | |
| Melting point/freezing point | : Not | available. | | | | | | |
| Boiling point, initial boiling point, and boiling range | : 100 | °C (212°F) | | | | | | |
| Flash point | : Clos | ed cup: Not applicable. | | | | | | |
| Evaporation rate | : 0.09 |) (butyl acetate = 1) | | | | | | |
| Flammability | : Not | available. | | | | | | |
| Lower and upper explosion limit/flammability limit | | | | | | | | |
| Vapor pressure | : 2.3 | kPa (17.5 mm Hg) | | | | | | |
| Relative vapor density | : 1 [A | ir = 1] | | | | | | |
| Relative density | : 1.29 |) | | | | | | |
| Solubility(ies) | : | | | | | | | |
| Media | | Result | | | Τ | | | |
| cold water Partially soluble | | | | | | | | |
| Partition coefficient: n- octanol/water | : Not | applicable. | | | - | | | |
| Auto-ignition temperature | : Not | available. | | | | | | |
| Date of issue/Date of revision | : 2/5 | 5/2024 Date of previous issue | : 10/1/2023 | Version : 4 | 7/13 | | | |
| 65000 PRO-HIDE® GOL White | 65000 PRO-HIDE® GOLD ULTRA Exterior Flat | | | | | | | |

Section 9. Physical and chemical properties

| Decomposition temperature | : Not available. |
|---------------------------|---|
| Viscosity | : Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt) |
| Molecular weight | : Not applicable. |
| Heat of combustion | : 0.543 kJ/g |

Section 10. Stability and reactivity

| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
|------------------------------------|--|
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : No specific data. |
| Incompatible materials | : No specific data. |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|--------------------------|---------|------------------------|----------|
| Benzophenone | LD50 Dermal LD50 Oral | | 3535 mg/kg >10 g/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|---------------------------------|----------------------|---------|-------|----------------------|-------------|
| Titanium Dioxide | Skin - Mild irritant | Human | - | 72 hours 300 ug l | - |
| Amorphous Diatomaceous Earth | Eyes - Mild irritant | Rabbit | - | 24 hours 25 mg | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|---------------------------------------|------|------|---------------------------------|
| Titanium Dioxide | - | 2B | - |
| Crystalline Silica, respirable powder | + | 1 | Known to be a human carcinogen. |
| Amorphous Diatomaceous | - | 3 | - |
| Benzophenone | - | 2B | - |

| Date of issue/Date | of revision | : 2/5/2024 | Date of previous issue | : 10/1/2023 | Version | :4 | 8/13 |
|--------------------|----------------------------|------------------|------------------------|-------------|---------|-----------|------|
| 65000 | PRO-HIDE® GOLD UL White | TRA Exterior Fla | at | | SHW-85- | NA-GHS-US | |

Section 11. Toxicological information

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

| Name | | Route of exposure | Target organs |
|---------------------------------------|------------|----------------------|---------------|
| Crystalline Silica, respirable powder | Category 1 | inhalation | - |

Aspiration hazard

| Name | Result |
|----------------------|--------------------------------|
| Heavy Paraffinic Oil | ASPIRATION HAZARD - Category 1 |

| Information on the likely routes of exposure | lot available. | |
|--|---------------------|--------------------------------|
| Potential acute health effe | | |
| Eye contact | lo known significan | t effects or critical hazards. |
| Inhalation | lo known significan | t effects or critical hazards. |
| Skin contact | lo known significan | t effects or critical hazards. |
| Ingestion | lo known significan | t effects or critical hazards. |
| | | |

| Symptoms related to the | physical, | chemical and | l toxicologica | I characteristics |
|-------------------------|-----------|--------------|----------------|-------------------|
| | | | | |

| Eye contact | : No specific data. |
|--------------|---------------------|
| Inhalation | : No specific data. |
| Skin contact | : No specific data. |
| Ingestion | : No specific data. |

Delayed and immediate effects and also chronic effects from short and long term exposure

| <u>Short term exposure</u> | |
|--------------------------------|---|
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| Long term exposure | |
| Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| Potential chronic health ef | <u>'fects</u> |
| Not available. | |
| General | : Causes damage to organs through prolonged or repeated exposure. |
| Carcinogenicity | : May cause cancer. Risk of cancer depends on duration and level of exposure. |
| Mutagenicity | : No known significant effects or critical hazards. |
| Teratogenicity | : No known significant effects or critical hazards. |
| Developmental effects | : No known significant effects or critical hazards. |
| | |

| Date of issue/Date | of revision | : 2/5/2024 | Date of previous issue | : 10/1/2023 | Version | :4 | 9/13 |
|--------------------|----------------------------|------------------|------------------------|-------------|---------|-----------|------|
| 65000 | PRO-HIDE® GOLD UL White | TRA Exterior Fla | at | | SHW-85- | NA-GHS-US | |
| | VVIIILE | | | | | | |

Section 11. Toxicological information

Fertility effects

: No known significant effects or critical hazards.

Numerical measures of toxicity Acute toxicity estimates

Not available.

Section 12. Ecological information

<u>Toxicity</u>

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|---------------------------------------|----------------------------------|----------|
| Titanium Dioxide | Acute LC50 >1000000 µg/l Marine water | Fish - Fundulus heteroclitus | 96 hours |
| Amorphous Diatomaceous | Acute EC50 2.2 g/L Fresh water | Daphnia - <i>Daphnia magna</i> - | 48 hours |
| Earth | | Neonate | |
| | Chronic NOEC 12.5 mg/l Fresh water | Daphnia - Daphnia magna - | 21 days |
| | | Neonate | |
| Benzophenone | Acute LC50 10.89 mg/l Fresh water | Fish - Pimephales promelas - | 96 hours |
| | | Larvae | |
| | Chronic NOEC 1.03 mg/l Fresh water | Fish - Pimephales promelas - | 32 days |
| | | Embryo | |

Persistence and degradability

Not available.

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|-------|-----------|
| Benzophenone | - | 12.02 | Low |

Mobility in soil

Soil/water partition : Not available. coefficient (K_{oc})

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

| Date of issue/Date | of revision | : 2/5/2024 | Date of previous issue | : 10/1/2023 | Version | :4 | 10/13 |
|--------------------|----------------------------|-----------------|------------------------|-------------|---------|-----------|-------|
| 65000 | PRO-HIDE® GOLD UL White | TRA Exterior FI | at | | SHW-85- | NA-GHS-US | |

Section 14. Transport information

| | DOT Classification | TDG Classification | Mexico Classification | ΙΑΤΑ | IMDG |
|--|--|---|--|---|---|
| UN number | Not regulated. | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| UN proper shipping name | - | - | - | - | - |
| Transport hazard class(es) | - | - | - | - | - |
| Packing group | - | - | - | - | - |
| Environmental hazards | No. | No. | No. | No. | No. |
| Additional information | - | - | - | _ | - |
| special precautions ransport in bulk ac MO instruments | conside mode o suitably to shipn of the p dangero and on | odal shipping descrip r container sizes. Th f transport (sea, air, for that mode of tran nent, and compliance erson offering the pro- ous goods must be tr all actions in case of able. | e presence of a shi etc.), does not indic nsport. All packaging e with the applicable oduct for transport. rained on all of the r | oping description for ate that the product g must be reviewed regulations is the s People loading and sks deriving from th | a particular is packaged for suitability prior ole responsibility unloading |

Section 15. Regulatory information

TSCA 5(a)2 proposed significant new use rules: 2-Methyl-4-isothiazolin-3-one; reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet, where applicable.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.


| Date of issue/Date | e of revision | : 2/5/2024 | Date of previous issue | : 10/1/2023 | Version | :4 | 11/13 |
|--------------------|---------------|------------|------------------------|-------------|---------|-----------|-------|
| 65000 | | | Flat | | SHW-85- | NA-GHS-US | 5 |

Section 15. Regulatory information

| International lists | : Australia inventory (AIIC): Not determined. |
|---------------------|--|
| | China inventory (IECSC): Not determined. |
| | Japan inventory (CSCL): Not determined. |
| | Japan inventory (ISHL): Not determined. |
| | Korea inventory (KECI): Not determined. |
| | New Zealand Inventory of Chemicals (NZIoC): Not determined. |
| | Philippines inventory (PICCS): Not determined. |
| | Taiwan Chemical Substances Inventory (TCSI): Not determined. |
| | Thailand inventory: Not determined. |
| | Turkey inventory: Not determined. |
| | Vietnam inventory: Not determined. |

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

| | Justification | | | |
|---|--|--|--|--|
| CARCINOGENICITY - Cat SPECIFIC TARGET ORGA | Calculation method Calculation method | | | |
| History | | | | |
| Date of printing | : 2/5/2024 | | | |
| Date of issue/Date of revision | : 2/5/2024 | | | |
| Date of previous issue | : 10/1/2023 | | | |
| Version | : 4 | | | |
| Key to abbreviations | ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations | | | |

Indicates information that has changed from previously issued version.

Notice to reader

| Date of issue/Date | of revision | : 2/5/2024 | Date of previous issue | : 10/1/2023 | Version | :4 | 12/13 |
|--------------------|----------------------------|------------|------------------------|-------------|---------|----|-------|
| 65000 | PRO-HIDE® GOLD UL White | | SHW-85- | NA-GHS-US | | | |
| | White | | | | | | |

Section 16. Other information

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.