



# Valspar® Fast Acting Wood Stripper

VL1031382-16

## GENERAL DESCRIPTION

Valspar Fast Acting Wood Stripper removes oil and latex finishes for a fresh start.

## PRODUCT FEATURES

- Ready-to-use solution, no mixing required.
- It is a biodegradable product which requires neutralization with Valspar All-In-One Wood Prep

## RECOMMENDED USES

Exterior wood decks, siding, fences, railings, steps and outdoor furniture.

## COMPOSITION

Base and Fill Levels  
(oz./gal.)

50

Valspar Fast Acting Wood Stripper  
(VL1031382-16)

128

## BEFORE APPLICATION

**TEST IT:** On a small, hidden area to determine its effectiveness. TO PROTECT FROM DAMAGE, COVER OR REMOVE ANY ITEMS THAT ARE WITHIN RANGE OF OVERSPRAY. IMMEDIATELY RINSE OFF SPLASHES OR OVERSPRAY FROM SIDING AND OTHER ITEMS WITH WATER.

## APPLICATION

Application: APPLY LIBERALLY to surface using a brush or pump sprayer. Do not apply to hot or wet surfaces. Let stand for 15 minutes. Do not allow to dry. RINSE using a garden hose with nozzle at maximum pressure or use a pressure-washing unit. Do not exceed 1000 PSI. After rinsing, neutralize with Valspar All-in-One Prep. IMPORTANT: All surfaces must be thoroughly neutralized with Valspar All-in-One Wood Prep, rinsed and dried a minimum of 2 days, depending on temperature and humidity prior to recoating. Any stripper not rinsed from the surface will cause coating adhesion problems. IMPORTANT: USE EXTREME CAUTION WHEN WORKING ON THE SURFACE TO BE STRIPPED. WOOD STRIPPER WILL CAUSE THE SURFACE TO BECOME VERY SLIPPERY. USE A FACE SHIELD OR GOGGLES WITH SIDE SHIELDS, RUBBER GLOVES AND PROTECTIVE FOOTWEAR FOR PROTECTION FROM HARMFUL CHEMICALS. REMOVE ANY CONTAMINATED CLOTHING IMMEDIATELY

## CLEANUP

Rinse equipment and overspray areas thoroughly with water.

## YOUR CLEAN WOOD WILL NEED PROTECTION FROM WATER DAMAGE AFTER CLEANING

Wait 2-3 days, depending on weather conditions, for the wood to dry thoroughly before applying an oil-based waterproofer or stain. Use Valspar® Exterior Stain & Sealers to protect your wood from the elements and provide the highest level of waterproofing protection available.

## COVERAGE

Will strip approximately 150-200 sq. ft. (14-18 m<sup>2</sup>) of weathered finish.

## REGULATORY COMPLIANCE

Current as of: 3/9/2021

CARB 2000 SCM	Yes
OTC	Yes
US National	Yes

## CAUTION

DANGER! Contains Sodium Hydroxide and Propylene Glycol. **KEEP OUT OF THE REACH OF CHILDREN.** Harmful if inhaled. Causes eye, skin and respiratory tract burns. **Use only with adequate ventilation.** Do not breathe spray mist. Avoid contact with eyes, skin and clothing. Wear protective equipment during application, including acid resistant rubber gloves, goggles, boots, dust mask and other appropriate clothing. Wash thoroughly after handling. **DO NOT TAKE INTERNALLY. Do not mix with other products or chemicals such as ammonia or acids, as this will release hazardous gases. First Aid: Eye Contact:** Flush thoroughly with water for at least 15 minutes. If irritation persists, get medical attention.\* **Skin Contact:** Flush skin thoroughly with soap and water for at least 15 minutes. If irritation persists, get medical attention.\* Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean contaminated shoes. **If Inhaled:** If affected by spray mist, move to fresh air. If breathing difficulty continues, get medical attention.\* **If Swallowed:** Give large amounts of water immediately. Do not induce vomiting. Get medical attention immediately.\* Call poison control center, hospital emergency room or physician immediately. **WARNING:** This product contains chemicals to the State of California to cause cancer and birth defects or other reproductive harm.