



# Valspar® Aluminum Barn & Fence Paint

## GENERAL DESCRIPTION

Valspar® Aluminum Barn & Fence Paint is easily applied and provides long-lasting protection on exterior surfaces such as storage sheds, outbuildings, and fences. Valspar® Aluminum Barn & Fence Paint is self-priming, as well as resistant to fading and mildew.

### **Product Features:**

- Self-Priming
- Fade Resistant
- Mildew Resistant Coating
- Ideal for Storage Sheds, Outbuildings & Fences

## WHERE TO USE

Ideal for use on properly prepared and primed exterior surfaces including chain-link fences, grain bins, tanks, roofing, piping, machinery, and equipment.

## SHIPPING AND PACKAGING

### **Freight Classification:**

Paint or paint related material. Protect from freezing.

### **Packaging:**

Gallon – 4 per carton

## COMPOSITION

### **Base and Fill Levels**

(oz./gal.)

Aluminum

128

## APPLICATION

Mix well before and during use. Do not shake with mechanical shaker or overly agitate, as a dull, non-uniform, mottled appearance will result. Paint only when surface and air temperatures are 50-90°F (10-32°C). No reduction necessary. Apply with a natural-bristle brush, ¼ inch woven roller cover with a solvent-resistant core or airless spray (2000 PSI, .017"-.019" tip).

### **Airless Spray:**

**Pressure:** 2000 PSI

**Tip:** 0.017–0.019"

**Brush:** Premium-quality brush

**Roller:** Premium-quality synthetic roller 3/8-1/2inch nap

## CLEANUP/STORAGE/ DISPOSAL

Clean brushes and tools with a regionally compliant cleaner following manufacturer's safety instructions. Wash hands with soap and water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

## PRODUCT SPECIFICATIONS

- o **Vehicle Type:** Alkyd resin
- o **Viscosity:** 20-30 Krebs Units
- o **Flashpoint:** 102.2 °F
- o **VOC:** < 500 g/L as per 40 CFR 59.406
- o **Volume Solids:** 50.6%
- o **Weight Solids:** 60.0%
- o **Weight Per Gallon:** 9.42 lbs./gal.
- o **Practical Coverage:** Covers approximately 400-600 sq. ft./gallon, depending on surface texture and porosity.
- o **Recommended Film Thickness:** 4.0 mil Wet 2.0 mil Dry
- o **Dry Time @ 77 °F and 50% Relative Humidity**
  - **To The Touch:** 2 hours
  - **Recoat:** 24 hours
- **Application Temperature:** 50-90°F (10-32°C)
- **Storage Temperature:** 40–90 °F (5–32°C)

### SURFACE PREPARATION

Remove surface contaminants with an appropriate cleaner, rinse thoroughly and allow to dry. Remove peeled or damaged paint. Sand glossy surfaces dull. Seal stains with the appropriate primer.

**Aluminum and Steel Siding:** Thoroughly remove all chalk and surface contamination by vigorously washing with a non-residue (TSP) cleanser or substitute, then rinsing surface well. **Previously Painted Surfaces:** Scrape off loose and peeling paint, sand, then spot-prime. Clean with an all-purpose cleanser (TSP or substitute). Dull glossy surfaces with gloss remover or sandpaper.

**Masonry:** Wire brush loose material from chalking areas and prime with an exterior latex primer.

**Metal:** Remove rust and spot-prime with an anti-rust primer.

### LEAD WARNING

**WARNING!** Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

### LIFETIME LIMITED

#### WARRANTY

This warranty is made to you, the product purchaser who owns the property where the product is applied. This warranty is not transferable, except that if a contractor purchased and applied the product to the property, then the warranty is transferable to you. This warranty is only valid when the product is applied and maintained according to product application and maintenance instructions to a properly prepared surface. If the product fails to perform in accordance with applicable product literature, Valspar shall, upon presentation of proof-of-purchase to the store where the product was purchased, either replace an equivalent quantity of product free of charge or refund the original purchase price. This warranty shall not apply to any defect, damage or product failure resulting from improper surface preparation, structural defects, environmental damage, failure of a previous product, deterioration or defect in the underlying substrate, or improper application of the product. Your exclusive remedy and the sole liability of Valspar under this warranty, is the replacement of product or refund, and does not include labor or costs associated with the application or removal of any product. **IN NO EVENT SHALL VALSPAR BE LIABLE FOR ANY TYPE OF INCIDENTAL, CONSEQUENTIAL, SPECIAL, EXEMPLARY, PUNITIVE OR INDIRECT DAMAGES, WHETHER OR NOT PURCHASER IS ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. ALL IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, SHALL HAVE THE SAME DURATION AS THE ABOVE EXPRESS WARRANTY.** Some states do not allow limitations on how long an implied warranty lasts or limitations on incidental or consequential damages, so portions of the limitations above might not apply to you. This warranty gives you specific legal rights and you may have other rights that vary from state to state. Valsparpaint.com

### CAUTIONS

#### **ALIPHATIC HYDROCARBONS METALLIC PIGMENT**

Contents are **COMBUSTIBLE**. Keep away from heat and open flame.

**VAPOR HARMFUL.** Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. Avoid contamination with water. Water can cause evolution of gas which may result in dangerously increased pressure in closed container.

**FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately.

**DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

**DANGER:** Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

Valspar, Cleveland, Ohio 44115  
1-877-VALSPAR (825-7727)  
valsparpaint.com  
Revised: 04/18/2023