



Valspar® Porch, Floor And Patio Paint – Oil Gloss

No. 48220 Series

GENERAL DESCRIPTION

Valspar® Porch, Floor And Patio Paint is a polyurethane fortified alkyd, high gloss paint designed for long lasting floor protection. Suitable for many interior and exterior uses, this extremely durable enamel resists scuffing and abrasion while retaining its high gloss appearance.

PRODUCT FEATURES

- Long lasting floor protection
- Extremely durable paint
- Enamel resists scuffing
- Suitable for interior and exterior uses

RECOMMENDED USES

Use paint on properly prepared concrete, wood, porches, basement floors, stairs, breezeways, primed metal, indoor and outdoor floors.

Not for use on exterior wood decks, garage floors or other automobile parking areas.

SHIPPING AND PACKAGING

Freight Classification: Paint or paint related material.

Packaging:

Gallon – 4 per carton

Case Weight: 41 lbs.

COMPOSITION

Base and Fill Levels
(oz./gal.)

Base 2 (48232)	124
Base 4 (48233)	116
Light Gray (48220)	128
Dark Gray (48222)	128

APPLICATION AND CLEANUP

Mix well before and during use. Intermit all cans of the same color. To increase traction, add an anti-skid additive when applying the finishing coat. Use a premium-quality roller, polyester brush, pad applicator or airless sprayer. DO NOT USE ANTI-SKID ADDITIVE IF APPLYING BY SPRAY. Apply liberally over the full length of the surface to avoid lap marks. If applied by airless sprayer, back-roll to ensure proper penetration. Finish with long, even strokes in one direction. Clean tools with mineral spirits. Do not allow water to pond or puddle on newly painted surfaces.

CARE AND WASHING

Do not allow water to pond or puddle on newly painted surfaces. Allow to cure 7 days before washing. Always use a mild detergent and soft sponge when cleaning the surface. Stubborn stains may require the use of an ammoniated household cleaner. Do not use cleaners containing abrasives or abrasive scouring pads to clean the surface.

SYSTEM RECOMMENDATIONS

Concrete and Masonry:

1–2 Coats: Valspar Oil Porch & Floor Paint

Bare Wood:

1–2 Coats: Valspar Oil Porch & Floor Paint

Previously Coated Surfaces:

1–2 Coats: Valspar Oil Porch & Floor Paint

Metal:

1 Coat: Valspar® Armor Anti-Rust Primer

1–2 Coats: Valspar Oil Porch & Floor Paint

PRODUCT SPECIFICATIONS

Vehicle Type: Polyurethane Modified Alkyd

Pigment Type: Titanium Dioxide

Viscosity: 98–108 Krebs Units

Flashpoint: 101 °F

Sheen: 80+ Units @ 60° angle

VOC (g/L): less than 400 g/L

VOC (lbs./gal.): 3.09

Volume Solids: 52%

Weight Solids: 67%

Weight Per Gallon: 9.4 lbs./gal.

Practical Coverage: Covers up to 500 sq. ft. (46 m² per 3.78 L) depending upon surface porosity. Do not thin.

Recommended Film Thickness:

3.2 mil Wet 1.7 mil Dry

Dry Time @ 77 °F and 50% Relative Humidity

Recoat: 24 hours

Light Foot Traffic: 24 hours

Normal Use: 72 Hours

Washing: Allow at least 7 days before washing. Use mild detergent and sponge.

Application Temperature: 50–90 °F (10–32 °C)

Storage Temperature: 40–90 °F (4–32 °C)

REGULATORY COMPLIANCE

Current as of: 1/25/2017

SCAQMD	No
CARB 2000 SCM	No
CARB 2007 SCM	No
OTC/LADCO	No
US National	Yes

STORAGE AND DISPOSAL

Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.



Valspar® Porch, Floor And Patio Paint – Oil Gloss

No. 48220 Series

SURFACE PREPARATION

General:

Read the Lead Warning paragraph. The surface must be clean, dry and free of all loose or peeling paint. Thoroughly clean surface and remove wax and grease with an all-purpose cleaner (TSP or substitute). Clean joints and cracks to remove all foreign material. Patch voids with appropriate crack patching material. Areas where ponding water is evident should be leveled prior to application. Although not required, a coat of Concrete Primer prior to application of Anti-Skid Porch and Floor Paint coats will increase the adhesion to these properly prepared surfaces.

Concrete:

New concrete, masonry surfaces and mortar should be cured 60 days. Remove all form release or curing agents. New, unpainted or smooth-worn concrete must be etched with a concrete cleaner, degreaser and etcher for proper penetration and adhesion. Follow all label instructions. Remove all loose material or dust. After cleaning, degreasing and etching, apply two coats of Oil Porch & Floor Enamel — a thin first coat and the second coat as normal.

Etching:

New, unpainted or smooth-worn concrete must be etched with a muriatic acid solution for proper penetration and adhesion. Before preparing acid solution, READ ALL CAUTIONS AND WARNINGS on acid packaging. Wear appropriate protective clothing, goggles and rubber gloves when handling acid. Mix 1 quart of muriatic acid and 1 gallon of water. Flush floor with acid solution. DO NOT BREATHE VAPORS and make certain there is good ventilation. After 30 minutes, or when acid solution stops bubbling, rinse with water while scrubbing the floor with a stiff broom to remove all powdery residue. Allow to dry. Properly etched concrete will feel like rough sandpaper.

Bare Wood:

Remove sap from knots and sappy areas. Spot prime then prime entire area with appropriate Valspar® Exterior Oil-Based Primer.

Metal:

Hand or power tool clean steel to remove loose mill scale and rust. Remove oily residues and contaminants with solvent or appropriate cleaning solution. Change rags often, to assure that residual contaminants are completely removed. Prime with Valspar® Armor Anti-Rust Primer.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

LIMITED WARRANTY

This product is warranted for your complete satisfaction with the application, appearance and performance properties. This warranty covers product that is applied to a properly prepared surface in accordance with label directions and excludes failure due to deterioration of the underlying surface, structural defects or failure of previous product. If the product fails to perform as warranted, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT, AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.

CAUTIONS

WARNING! COMBUSTIBLE LIQUID AND VAPOR. VAPOR HARMFUL.

WARNING! Contains Petroleum Distillates and Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. **Use only with adequate ventilation.** Keep away from heat, sparks and flame. Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. DO NOT TAKE INTERNALLY. NOTICE: Reports of commercial painters have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the vapors may be harmful or fatal. Delayed effect from long-term exposure: Cancer hazard. Contains crystalline silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist. **WARNING:** This product contains a chemical known to the State of California to cause cancer. **First Aid: Eye Contact:** Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention.* **If Inhaled:** If affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.* **If Swallowed:** Do not induce vomiting. Get medical attention immediately.*

*Call poison control center, hospital emergency room or physician immediately.

UCS 6.1

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

This product contains less than 400 g/L VOC

8725 W. Higgins Rd., Chicago, IL 60631
888.313.5569
valsparpaint.com
Revised: 1/25/17
Version: 48220D