

## PRODUCT DESCRIPTION

**2000™ Paint + Primer** delivers professional grade performance that everyone can afford. The acrylic formula provides great coverage for color changes, saving time on projects. This **Valspar®** product great for customers that want a professional product that includes excellent touch up and sprayability. Optimal for residential and commercial properties. Ideal for properly prepared interior walls, and ceilings, previously painted or bare drywall, plaster, masonry and primed metal.

## RECOMMENDED USES

Properly prepared interior walls and ceilings including previously painted and primed plaster, wood, brick, drywall, cement and metal.

## PRODUCT INFORMATION

Regulatory Compliance/ Certifications 6/5/2018			
SCAQMD	Yes	MPI #	52 (Pend) 145 (Pend)
CARB 2000 SCM	Yes	GPS-1	Pending
CARB 2007 SCM	Yes	GPS-2	Pending
OTC/LADCO	Yes	LEED (US) LEED (Can)	Yes
US National	Yes	UL Greenguard Gold	Yes

BASE & FILL LEVELS	SPECIFICATIONS
<p>High Hiding White (670350, 670353) 128 oz/gal                      Pastel Base (670351, 670354) 124 oz/gal                      Neutral Base (670352) 116 oz/gal</p>	<p><b>VEHICLE TYPE:</b> Vinyl copolymer  <b>PIGMENT TYPE:</b> Titanium Dioxide  <b>VISCOSITY:</b> 90–100 Krebs Units  <b>SHEEN:</b> 25–35 Units @ 85° angle  <b>FLASHPOINT:</b> N/A  <b>VOC:</b> &lt; 50 g/L – 0.42 lb/gal as per 40 CFR 59.406  <b>VOLUME SOLIDS:</b> 32%  <b>WEIGHT SOLIDS:</b> 45%  <b>WEIGHT PER GALLON:</b> 10.4 lbs. /gal.  <b>PRACTICAL COVERAGE:</b> Covers approximately 350–450 sq. ft. per gallon (32–42 m<sup>2</sup> per 3.78 L). Less on rough or porous surfaces. Thin with up to 8 oz. water per gallon only if paint is too thick for sprayer.  <b>RECOMMENDED FILM THICKNESS:</b>                      4.0 mil Wet      1.3 mil Dry</p>
<p><b>FEATURES</b></p> <ul style="list-style-type: none"> <li>• Paint + primer delivers outstanding hide &amp; coverage</li> <li>• Excellent touch-up</li> <li>• Excellent burnish resistance</li> <li>• Washable film</li> <li>• Sheen equivalent to MPI gloss level #3, defined as ‘a traditional egg-shell-like finish’</li> <li>• Easy application spray, brush and roll</li> </ul>	
<p><b>APPLICATION</b></p> <p>Stir paint thoroughly. Intermix containers to ensure uniform color. Apply with a premium-quality roller, polyester brush or airless sprayer. Surface conditions and application technique can also impact coverage.</p> <p><b>Airless Spray:</b>                      Pressure: 2000 PSI                      Tip: 0.015”–0.021”</p> <p><b>Brush:</b> premium-quality polyester brush  <b>Roller:</b> premium quality synthetic, 3/8” nap  <b>Dry Time @ 77 °F and 50% Relative Humidity</b>                      To The Touch: 1 hour                      Recoat: 4 hours  <b>Application Temperature:</b> 50–90 °F (10–32 °C)</p>	<p><b>SYSTEM RECOMMENDATIONS</b></p> <p><b>Drywall/Wallboard/Plaster (new):</b>                      1 Coat: Valspar Interior Drywall Primer-Sealer or Valspar 2000 Satin                      1–2 Coats: Valspar Ultra 2000 Interior Latex Satin Paint</p> <p><b>New Wood/Composition Board:</b>                      1 Coat: Valspar Int/Ext Stainblocking Bonding Primer                      1–2 Coats: Valspar 2000 Interior Latex Satin Paint</p> <p><b>Interior Concrete Block:</b>                      1 Coat: Valspar Block filler                      1–2 Coats: Valspar 2000 Interior Latex Satin Paint</p> <p><b>Masonry:</b>                      1 Coat: Valspar Masonry and Stucco Primer                      1–2 Coats: Valspar 2000 Interior Latex Satin Paint</p> <p><b>Previously Painted Surfaces:</b>                      1–2 Coats: Valspar 2000 Interior Latex Satin Paint</p> <p>Recommended one coat primer if the painting project requires a bold color transition. This will improve the topcoat hiding power.</p>



## SURFACE PREPARATION

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.

Revised  
7/29/2019

**General:** Read the Lead Warning paragraph. Thoroughly clean the surface and allow to dry. Remove all wax, grease, dirt, chalk, mildew, loose and peeling paint and other foreign matter. Remove gloss from shiny surfaces. Repair all cracks and nail holes with patching compound. Painting over wallpaper is not recommended. New or bare surfaces should be primed with an appropriate Valspar® primer.

**Drywall and Plaster:** Fill cracks, pits and voids with patching compound. Allow new plaster to fully cure and sand smooth. Remove all sanding dust. Prime new and bare surfaces with Valspar® Interior Drywall Primer-Sealer.

**Wood:** Sand wood smooth and patch holes and imperfections with wood filler or putty and sand smooth. Remove all sanding dust. Prime new and bare surfaces with Valspar® Interior/Exterior Stainblocking Bonding Primer.

**Concrete Block:** Concrete block surfaces and mortar should be fully cured, usually 30 days. Remove all loose material or dust. Fill pores of bare concrete block with Valspar® Block filler, then top coat.

**Masonry:** New concrete, masonry surfaces and mortar should be cured, usually 30 days. Remove all form release or curing agents. Remove all loose material or dust. Prime bare surfaces with Valspar® Masonry and Stucco Primer, then top coat.

## LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## CLEANUP AND DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulation.

## CAUTIONS

WARNING! Contains Crystalline Silica. **KEEP OUT OF THE REACH OF CHILDREN.** May cause eye and skin irritation. Use **only with adequate ventilation.** Avoid breathing vapors, spray mist or sanding dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. When sanding, wear a dust mask. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **DO NOT TAKE INTERNALLY.** Delayed effect from long-term exposure: Cancer hazard. Contains crystalline silica, which can cause cancer. Risk of cancer depends on duration and level of exposure to dust from sanding surfaces or spray mist. **WARNING:** This product contains a chemical known to the State of California to cause cancer. **First Aid: Eye Contact:** Immediately flush with plenty of water for at least 15 minutes. If irritation persists, get medical attention.\* **If Inhaled:** If affected by inhalation of vapor or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.\* **If Swallowed:** Drink 2 glasses of water. Get medical attention immediately.\*

\*Call poison control center, hospital emergency room or physician immediately.

UCL 3.1

## CAUTIONS CONT'D

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:**  
1-888-345-5732

Valspar  
Cleveland, OH  
valsparpaint.com  
888.313.5569  
VALPRO2KINTSAT