



Valspar® Signature Ceiling Paint

No. 670365 Series

GENERAL DESCRIPTION

Valspar Signature Ceiling Paint + Primer glides on with ease, offers superior hide and cleanly covers ceilings in a single coat. It leaves a smooth finish plus is an excellent stain-blocker. The No-Mess Formula defies spatter and drips for an effortless painting experience.

PRODUCT FEATURES

- Paint + Primer
- Superior hide in a single coat
- Excellent stain-blocking
- Defies spatter and drips
- Provides a mold- and mildew-resistant finish
- GREENGUARD Gold certified
- Tintable
- Lifetime warranty

RECOMMENDED USES

Properly prepared durable textured or plain interior ceilings including previously painted and primed plaster, drywall, acoustical tile and wood.

See surface preparation for "blown on" soft-fibered ceiling surfaces.

SHIPPING AND PACKAGING

Freight Classification: Paint or paint related material. Protect from freezing.

Packaging:

- Gallon – 4 per carton (670365)
- 5 Gallon pail – each (670366)

COMPOSITION

Base and Fill Levels

(oz./gal.)

White

128

APPLICATION

Stir paint thoroughly. Intermix containers to ensure uniform color. Apply with a premium-quality roller, polyester brush or airless sprayer. Paint the ceiling, rolling from dry area into wet area using firm, crisscross strokes. Finish with long, even strokes in one direction.

Thinning: Thin only for spray application with up to 8 oz. of water per gallon of paint (236 mL per 3.78 L).

Airless Spray:

Pressure: 2000 PSI

Tip: 0.017–0.021"

Brush: Premium-quality polyester

Roller: Premium-quality roller 3/8-3/4" nap

SYSTEM

RECOMMENDATIONS

Bare Drywall and Plaster:

2 Coats: Valspar Interior Latex Ceiling Paint

Stains:

1 Coat: Valspar Bonding Stainblocking Primer-Sealer

1–2 Coats: Valspar Interior Latex Ceiling Paint

Acoustical Tile:

1–2 Coats: Valspar Interior Latex Ceiling Paint

"Blown-on" Soft-Fibered Ceilings:

1 Coat: Appropriate interior oil primer

1–2 Coats: Valspar Interior Latex Ceiling Paint

Previously Painted Surfaces:

1–2 Coats: Valspar Interior Latex Ceiling Paint

PRODUCT SPECIFICATIONS

Vehicle Type: Acrylic resin

Pigment Type: Titanium Dioxide

Viscosity: 97-105 Krebs Units

Sheen: 0-5 units at 85°

Flashpoint: N/A

VOC (g/L): < 50 g/L □ 0.42 lb./gal as per 40 CFR 59.406

Weight Per Gallon: 10.65 lbs.

Volume Solids: 31%

Weight Solids: 45%

Practical Coverage: Covers approximately 400 sq. ft. per gallon (37 m² per 3.78 L) depending on surface porosity. Significantly less on acoustical tile.

Recommended Film Thickness:

4.0 mil Wet 1.2 mil Dry

Dry Time @ 77 °F and 50% Relative Humidity

To Touch: 30-60 minutes

Recoat: 2-4 hours

Washing Instructions: Wait at least 7 days before washing with a mild detergent and soft sponge

Application Temperature: 50–90 °F (10–32 °C)

REGULATORY COMPLIANCE

Current as of: 3/18/2020

SCAQMD	Yes
CARB 2000 SCM	Yes
CARB 2007 SCM	Yes
OTC/LADCO	Yes
US National	Yes

CLEANUP AND DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations.



Valspar® Signature Ceiling Paint

No. 670365 Series

SURFACE PREPARATION

General:

Read the Lead Warning paragraph. Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Remove gloss from shiny surfaces. Patch cracks and spot prime prior to painting. For best results on heavily stained areas, apply one coat of an appropriate interior latex primer.

Acoustical Tile:

Vacuum or dust tiles to remove embedded dust. To maintain the sound-absorbing qualities of the tile, do not use a primer. Apply ceiling paint directly to the tiles. Two or more coats may be needed to achieve an even finish. Test vinyl coated tiles to ensure adhesion. Do not attempt to fill or clog acoustical perforations.

“Blown-on” Soft-Fibered Ceilings:

Caution! All water-based paints will loosen or deteriorate a “blown on” soft-fibered ceiling surface and make for a difficult repair. If you are not sure about your ceiling texture type, apply a small test area in a closet or other hidden spot. If deterioration occurs and if painting is necessary, priming with an oil-base primer may help minimize the deterioration. Do not use a latex primer.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

LIFETIME LIMITED WARRANTY

If this product, when applied according to product application instructions to a properly prepared interior surface, fails to perform to your complete satisfaction for as long as you own your home, Valspar shall, upon presentation of proof of purchase to the store where the product was purchased, either replace an equivalent quantity of product free of charge or refund the original purchase price. This warranty shall not apply to any defect or damage resulting from improper surface preparation, structural defects, failure of a previous paint or improper application of the product. This is your sole remedy under this warranty. This warranty is made to the original residential consumer paint purchaser and is not transferable. This warranty excludes (1) labor or costs associated with labor for the application or removal of any product, and (2) any indirect, special, incidental or consequential damages. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state. Valsparpaint.com/1-877-VALSPAR.

CAUTIONS

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.** **DANGER:** Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations. For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:

1-888-345-5732

Valspar, Cleveland, Ohio 44115

Revised: 3/18/20